

Douglas County Surveyor's Record of
Government Corners Renewed

27

T. S.

6

R. W. W. M.

<p>SECTION CORNER BETWEEN 6 and 7 T. 26-6 and 1 and 12 T. 27-7. Set 1" Iron Pipe from one original bearing tree others gone. Corner in creek. Marked the following trees Fir 14" dia. bears N.42°E., 16.8 ft. Fir 24" dia. bears S.42°E., 97.3 ft. White Fir 20" dia. S.55$\frac{1}{2}$°W., 57.4 ft. Fir 14" dia. bears N.39°W., 45.4 ft.</p>	<p>10 G. G. Stewart Deputy Chas. Kaiser Wit. V. J. Borsik Johnson; Littrel, Sirdi May 17, 1922 See also Rev. Dick Guthrie Vol. 122 Witnesses</p>
<p>NORTHWEST CORNER OF D.L.C. # 56. Renewed from old pipe, set by F. C. Frear as corner. Set pipe for corner in edge of pavement, in a projection on side of pavement. Set in 6" concrete on Edenbower Pavement by Davis house. (SEE ALSO #45 & #193) VOL. 4 PG 53</p>	<p>11 F.C. Frear Roadmaster Jan. 9, 1923 P.D. Wolford Jan. 7, 1929</p>
<p>N.E. CORNER D.L.C. # 56 Renewed from old stake set by State Highway Engineers and later permanently established by auto axle set in 15" x 15" concrete on center line with Edenbower Pavement.</p>	<p>12 H.L. Eppstein J.H. Wolford Richardson Jan. 7, 1929</p>
<p>SECTION CORNER OF 15, 16, 21 and 22. Renewed from old B.T. Set Dodge rear axle, and marked the following trees Maple 12" dia. bears N.35°W., 37 ft. old B.T. Black Oak 14" dia. bears S.55$\frac{1}{2}$°E., 98 ft. White Oak 15" dia. bears S.71$\frac{1}{4}$°W., 102 ft.</p>	<p>13 H.L. Eppstein J.H. Wolford Richardson Jan. 7, 1929</p>
<p>S.W. CORNER D.L.C. # 50 WM MCKINNEY D.L.C. Found 4 x 5 rock as called for in original notes. Blazed and scribed B.T.s as follows Black Oak 8" dia. bears N.43°E., 62 lks. marked S.W. CL. 50 C.S.B.T. White Oak 8" dia. bears N.70°E., 66 lks. marked S.W. Cl. 50 C.S.B.T.</p>	<p>14 Ben B. Irving N. E. Richardson Cliff Mabley April 1, 1928</p>
<p>S.E. CORNER WM. MCKINNEY D.L.C. # 50. Found original B.T. old surface rotted out but figures plain on reverse chip. This corner comes in present traveled portion of county road, Roseburg to Melrose. As it is planned to regrade this section soon did not set anything for corner point but marked new B.T.s as follows Laurel 12" dia. bears East 22 lks. scribed thru bark S.E. Cl. 50 C.S.B.T. Black Oak 10" dia. bears N.55°E. 30 lks. blazed and scribed S.E. CL. 50 C.S.B.T. Corner is located 6 ft. right of center line station 196+01 on the new road survey.</p>	<p>15 Ben B. Irving Dec. 1931 N. E. Richardson Art Boyer R.L. Irving Bert Jensen</p>
<p>S.W. CORNER OF THE ISAAC JONES D.L.C. NO. 65 Set a brass plate in concrete post 6 x 6 x 36" in ground at fence intersection. This fence corner has been in place as the property corner for a great many years and has been used by the adjoining property owners for the true corner.</p>	<p>16 H.L. Eppstein Roscoe Conh Kenneth Conh Fred Goff Nov. 1923</p>
<p>N.W. CORNER OF D.L.C. # 50 Exterior L corner set from testimony of Fred Goff as to location of witnesses tree and distance from interior L corner. Black Oak 20" dia. bears S.18°E., 229.8 feet</p>	<p>17 H.L. Eppstein Roscoe Conh Kenneth Conh Fred Goff Nov. 1923</p>
<p>CORNER SECTION BETWEEN 32, 33, 4, and 5. A Stone is buried in ground for this corner, witness trees in Section 5, 32, 33 in place. Tree in Section 4 gone. No trees near.</p>	<p>18 H.L. Eppstein Roscoe Conh Kenneth Conh Fred Goff Nov. 1923</p>