

Douglas County Surveyor's Record of
Government Corners Renewed

27

T. S.

6

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

102

Section Corner to Sections 2 - 3 - 10 - 11.

Found - Orig. 20", now 30" Oak Stump S. 71 $\frac{1}{2}$ ° E. 433.0 ft., shows #181
good reverse scribe marks on chip.

Orig. 18", now 32" Oak Stump N. 70° E. 252.4 ft. We open
& find good scribe "BT".

BT's. to West in field, not found.

Set Brass Cap at Corner Mkd: County Surveyor's

S 3	S 2
S 10	S 11

 T27-6W
Office, 1961

Set 3" Iron Rod 30.7 ft. East of Sec. Cor & in Field Fence Line.

New BT's: 30" W. Oak bears N. 68 $\frac{3}{4}$ ° E. 275.4 ft. scribed S2 T27S R6W CS BT.

15" B. Oak bears S. 30° W. 517.0 ft. scribed S10 T27S R6W CS BT.

No trees near to N. W. S. E.

RE-RENEWED SET CORNER NO.

FD 12/63
G. Bauchman
M 95-71

103

Sec. Cor. to Secs. 2 & 3, T27-6W. & Secs. 34 & 35, T26-6W.

Found - All Orig. BT's. Orig. 6", now 18" W.O. S. 57 $\frac{1}{2}$ ° W. 44.2 ft.,
center rotted.

Orig. 6", now 24" B.O. N. 86° W. 28.4 ft., shows scar.

Orig. 10", now 34" B.O. N. 10° E. 79.2 ft. We open & find
good scribing "W".

Orig. 8", now 24" B.O. S. 73° E. 89.8 ft., shows scar.

Set - Brass Cap at Corner Mkd: County Surveyor's

S 34	S 35
S 3	S 2

 T26S
Office, 1961

New BT's: 24" B.O. N. 86° W. 28.4 ft. (O. BT.) scribed S34 T26S R6W CS BT.

12" W.O. N. 20° E. 84.0 ft. scribed S35 T26S R6W CS BT.

9" B.O. S. 15° E. 53.0 ft. scribed S 2 T27S R6W CS BT.

9" W.O. S. 29° W. 14.7 ft. scribed S 3 T27S R6W CS BT.

Fd. by:
B. Rogers
Nov. 1982
M 93-27

R6W
BT.

James W. Hyron, Deputy County Surveyor
Milo Godfrey
January 1961
C. S. File 49/79

104

$\frac{1}{4}$ Sec. Cor. To Sec. 3, T27-6W. & Sec. 34, T26-6W.

Found - Both Orig. BT's. We open N. W. BT. & find good reverse
scribing "BT". Both BT's. now 40" W. Oaks, check
record bearing & distance.

We also find 1" Iron Pipe at Corner.

Set Brass Cap at Corner Mkd: County Surveyor's

S 34	T26S
S 3	T27S

 R6W
Office, 1961

New BT: 11" W. Oak N. 61 $\frac{1}{2}$ ° E. 81.0 ft. scribed $\frac{1}{4}$ S34 CS BT. - Fo. O.K. July 24

FD OUT OF GROUND -
RE-SET - M 95-71
12/83 G.
Bauchman

FD C.C.
8/90
M 110-44

105

Sec. Cor. to Sec. 5 & 4, T27-6W. & Secs. 32-33, T26-6W.

Found - Orig. 18", now 50" Maple N. 9° W. 46.2 ft., center
burned out, now shell only, no scribing found.

All other BT's. gone

We find 2" x 8" x 18" Stone 6" under surface & under
N. S. Fence. Stone Set on End. REN. #18

Set Brass Cap at Corner & alongside Corner Stone Mkd:

County Surveyor's

S 32	S 33
S 5	S 4

 T26S R6W
Office, 1961

New BT's: 36" Maple bears N. 14 $\frac{3}{4}$ ° W. 51.6 ft. scribed S32 T26S R6W CS BT.

10" Myrtle bears N. 51° W. 113.7 ft. scribed S32 T26S R6W CS BT.

No other Trees near.

RE-RENEWED SET CORNER NO.

FD OK 2/90
HEIMBURGER
M 109-574RB

FD 12/63
M 95-71
G. Bauchman

FDOK PER LAUG
M 108-17 5/89

106

$\frac{1}{4}$ Corner sections 9 and 16.

Found - Orig. 16", now down 40" B. Oak, N. 20 $\frac{1}{2}$ ° W. 430.3 ft. We
open & find good scribing "S".

No trace of Orig. S. W. BT. found.

Note - Corner falls in County Roadway. We Set Wit. Cor. 40' West.

Set - Brass Cap at Wit. Cor. Mkd/ 40' East to

S 9
S 16

 T27S R6W
County Surveyor's

Office, 1961

New BT's: 16" W. Oak bears S. 28 $\frac{1}{2}$ ° W. 10.6 ft. scribed WC $\frac{1}{4}$ S16 CS BT.

12" B. Oak bears N. 28 $\frac{1}{2}$ ° E. 13.0 ft. scribed WC $\frac{1}{4}$ S 9 CS BT.