

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 6 W. R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

Wm. B. Paulin
Feb. 6, 1962
C. S. File
No. 51/227

N. E. Corner D. L. C. No. 43.
Found - Stone set at 4-way Fence Corner.
Fence running N - S - E - W.
Set - Iron Rod beside Stone.

Ps. 7/8/1
E. Wade
M. 88-26
+ M. 102 25
J. Melino
6/86

107

Milo E.
Godfrey
C.S. File
No. 44/68

Section Corner to Sections 10 - 11 - 14 - 15.
Set a 1" Iron Pipe with Brass Cap attached inside a 2" Iron
Pipe previously set as recorded in Renewed Corners Volume 2,
Corner No. 29, T27S R6W.

June 13, 1962

SEE
NEW BT.
REN. #128

108

A. Boyer, Deputy
Wit: N.E. Richardson
P. D. Wolford
Sept. 27, 1936

Meander Corner between Secs. 19, T27-5W. & Sec. 24, T27-6W.
On Elk Island 3" x 3" Red Cedar Post and 1" Bolt 30" long
from which: A Balm of Gilead 20" diam. bears S. 62° W. 39.8 ft.
A Balm of Gilead 15" diam. bears N. 50° W. 30.5 ft.
mkd: T27S R5-6 S14 S24.

RE-RENEWED, SEE CORNER NO. #132

SEARCHED FOR
NOT FOUND
JUNE 17, 1966
C.S. 53/38
V.R.T.

109

Sec. Cor. to Sec. 13 & 24; T27-6W. & Secs. 18 & 19, T27-5W.
On Elks Island. Set a 1/2" x 1 1/2" Iron Rod 27" long 15" below
ground surface, for corner, from which:
A 30" Balm tree bears N. 62° W. 155 ft.
A 14" Black Oak bears S. 78° W. 101.7 ft.
A 30" Cherry, bark blazed, bears S. 85 1/2° E. 255 ft.

SEE CORNER NO. #130

110

H. L.
Eppstein
Wit. A. Boyer
N.E. Richardson
9/27/36

Meander Corner between Sec. 13, T27-6W. & Sec. 18, T27-5W.
On Elks Island 3" x 3" Cedar Post & 3/4" Iron Rod 24" Long, from which:
Ash 6" diam., bark blaze bears S. 38° E. 23.8 ft.
Ash 6" diam., bark blaze, bears S. 87° W., 21.6 ft. Mkd:
CS M.C. S13-18 BT.

(Searched for, not found - 6/17/66 - C.S. 53/38 V.R.T.)
(SEARCHED FOR, N.F. 8/25/87 C.S. 62/45 LEA)

111

A. Boyer
Claude Crocker
J. Wolford
1934 - 37 - 38

Township Corner - Corner to Sections 36, T27-6W. & Sec. 31, T27-5W.
Set corner from old BT's. Set 3/4" x 36" Round Bolt for corner
from which new BT's. were made as follows:
White Oak 12" diam. bears N. 22° W., 58.5 feet
White Oak 14" diam. bears N. 31° 30' E. 20 feet.

RE-RENEWED, SEE CORNER NO. #184

112

Ben B. Irving
N.E. Richardson
B.A. Lane
1934

1/4 Corner to Sec. 24, T27-6W. & Sec. 19, T27-5W.
As this corner was lost, I set it in by Proportionate measurement.
Set - 1/2" x 30" Iron Pipe 6" under ground in alley of Block 57, City
of Roseburg from which the intersection of alley with Mosher
Street centerline bears S. 27° E. 170.92 feet. No tree near.

113

Meander Corner Sec. 24, T27-6W & Sec. 19, T27-5W.
An Iron Pipe set for Corner. Old BT's. not cut out as they
are in owner's yard, Washington Hughes.

114

Frank Cain
B.A. Lane
N.E. Richardson
1935

Meander Corner between Sections 18 and 13, R5 & 6W. (See also #25)
All indication of corner gone. Corner, 5/8" x 42 1/2" Iron Rod set
by proportionate measurement, 4.8 ft. south of the south rail, S.P. RR.
A channel iron 1 1/4" x 18", 14" in ground, under right of way fence.
A bridge bears N. 16° 30' W. 62 feet about 455 feet from B.C. RR curve
left north of cut on R. R.
A W. Oak 14" diam. bears S. 60° 30' W. 117.4 feet mkd: M.P. CS BT.

SEE CORNER NO. #133

115