

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

M. E. Godfrey, Deputy
Wm. Stoffel - Stone - Darby
May 14, 1964
C. S. File No. 49/139

North $\frac{1}{4}$ Corner Sec. 1 only, T28-6W. (South Line T27-6W)
Found - $\frac{3}{4}$ " Iron Pipe at Corner. (See Ren. No. 85, T28-6W)
12" W. Oak S.67°W. 20.0 ft., scribing visible.
20" W. Oak N.45°E. 65.2 ft. This tree mkd. in 1961.
Alongside Iron Pipe at Corner Set Brass Cap Mkd: County Surveyor's
T28S R6W $\frac{1}{4}$ S 1 Office, 1964
Did not mark any new trees.

123

M.E. Godfrey
& Crew
July 1964
C. S. File
No. 52/87

Sec. Cor. To Secs. 1 & 2, T27-6W. & Secs. 35 & 36, T26-6W.
Found - 20" W. Oak N.3 $\frac{1}{2}$ °W. 62.7 ft. Cut open & found scribing "S" on
partially rotted face.
26" W. Oak N.15 $\frac{1}{2}$ °E. 72.6 ft., both upper & lower scars show
very plainly.
30" W. Oak S.60 $\frac{1}{2}$ °W. 137.9 ft., no scars visible.
El. Oak, uprooted & dead several years, S.52°E. 114.2 ft.
Did not open.
Set - Brass Cap at Cor. Mkd: County Surveyor's T26S S35 | S36
Office, 1964 T27S S 2 | S 1 R6W
New BT's: 14" W. Oak S.47°E. 15.0 ft. Mkd: T27S R6W S1 CS BT.
12" W. Oak S.49°W. 26.2 ft. Mkd: T27S R6W S2 CS BT.
6" In. Cedar N.64°W. 33.2 ft. Mkd: S35 CS BT.
6" W. Oak N.52°E. 16.8 ft. Mkd: T26S R6W S36 CS BT.

124

Wilford N. Haines
For J. H. Cannon
August 1964
MapS. File No. M 28 - 50
N 28 - 51

$\frac{1}{4}$ Section Corner to Sections 16 and 21.
Found - No trace of Orig. BT's., but this point is close to calculated
position for $\frac{1}{4}$ corner and has been used for many years as
corner so I take it the most logical position for $\frac{1}{4}$ Corner.
Set - 1" x 1" x 36" T. Iron by Pipe and Scribed:
12" W. Oak N. 03 $\frac{1}{2}$ ° E. 17.8 feet.
16" W. Oak S. 22° E. 18.5 feet.

125

Center of Section 21.
Set - 1" x 1" x 36" T. Iron
Scribed - 16" B. Oak S.66°W. 5.5 feet.
12" W. Oak S. 80°E. 17.3 feet.

126

$\frac{1}{4}$ Section Corner to Sections 21 and 28.
Found - No Trace of Original $\frac{1}{4}$ Corner nor Orig. BT's.
Set - $\frac{1}{2}$ " x 48" Bolt and Scribed:
10" W. Oak S.36°E. 52.8 feet
12" W. Oak N.27°E. 70.7 feet.

127

(FD. 3/4" I.B.)
FD. B.T. OK 12/80
J. Gossion
M 86-17
M 91-31

Bruce A.
Shaner
May 1965
C. S. File
No. M 29 - 72

Section Corner to Sections 10 - 11 - 14 - 15.
Found - Brass Cap at Cor. Mkd: County Surveyor, 1962. (See Ren. #108)
11" Apple Tree N.57°36'W. 412.5 ft.
Did not find 12" Catalpa Tree, O.B.T. #129
New BT: 8" Catalpa Tree with RR Spike on N.W. Side, S.20°E. 384.5 ft.
May 29, 1965

128

James W. Byron, Co. Surv.
Bruce Rogers
John Powell & J. Brady
July - Nov. 1965
C. S. File No. 53/38

Section Corner to Secs. 10 - 11 - 14 - 15.
(See Renewed Cors. #108 and #128, above)
Found - July 13, 1965, Brass Cap as recorded in Ren. #108, & BT's:
Catalpa Tree S.20°E. 384.5 ft.
Apple Tree N.57°W. 412.5 ft.
Referenced Thus: Chisled + on face of concrete curb as shown in
sketch, Nov. 4, 1965.

129

This corner in Lot 6,
"Verncrest Subd." on
Troost Street.

