

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T.S. R. 6 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Vernon "Ray" Tracy
Jack Heriatage & E. West
Sept. 1, 1967
C. S. File 53/38

Section Corner to Secs. 1 & 12, T27-6W. & Secs. 6 & 7, T27-5W. 135
Found - 5/8" Iron Bolt 8" below surface of ground. See Ren. #118.
12", now 20" W. Oak, N. 40° E. 75.6 ft., alive, shows good scars. We do not open.
20", now 26" W. Oak, N. 46° W. 132.0 ft., alive, shows good upper scar, lower blaze shows "BT" scribe.

Set Brass Cap at Cor. Mkd: County Surveyors R T 27 S R
Set flush with ground. Office 6 S 1 | S 6 5
Reset bolt alongside. 1967 W S 12 | S 7 W

Also set 6.0 ft. steel fence post 2.0 ft. south of corner.
This corner lies 75.0 ft. south of Newton Creek in open field.

Sept. 1, 1967

MICROFILM TO HERE 10/67

Don E. Garrett
For - Wulff
C.S. 55/62
M 35 - 44

1/4 Corner to Sec. 18, T27-6W and Sec. 13, T27-7W. 136
Set by Proportional measurement. T27S
Set - Brass Cap for 1/4 Cor. Stamped L.S. 544 1/4 S 13 S 18
Feb. 1968 R7W R6W
Scribed - 18" Oak bears N. 12 1/2° W. 181.2 ft. scribed 1/4 S13 BT.
12" Oak bears N. 87° E. 55.0 ft. scribed 1/4 S18 BT.

Feb. 3, 1968

FD. S.C. 4/24
P. DOLAN
M 96-70

SEPT 768

Herbert L. Northcraft
For: Les Black
RM 1 - 70

1/4 Corner to Sec. 24, T27-7 and Sec. 19, T27-6W. 137
Found - Rock at 1/4 corner, as of Hicks' Survey, 1914, See M 33 - 41.
New Witness Trees: 8" W. Oak N. 60° W. 13 ft.
8" W. Oak East 10.8 ft.

June, 1968

Don E. Garrett
For Darley E. Ware
January, 1969
Map File M 37 - 14

1/4 Corner to Sections 2 and 11. 138
Found - Old 16" B.T. Stump, inside face visible, scribed "B",
bears S. 49° 30' E. 40.9 ft.
Old White Oak, inside, well rotted, bears N. 81° 54' W. 71.5 ft.
Set - Brass Cap mkd: T27S R6W 1/4 Cor. S2/S11, 1969 L.S. 544
New Bearing Trees: 28" W. Oak bears N. 61° 52' E. 82.6 ft. scribed 1/4 S2 BT.
12" B. Oak bears S. 75° 28' W. 80.3 ft. scribed 1/4 S11 BT.

1/4 Corner to Sections 10 and 11.

FDCK PER BADSHMAN
C.S. 63/58 JUNE-87

139

Set by proportion.
Set - Brass Cap Mkd: T27S R6W 1/4 Cor. 10/11, 1969 L.S. 544
New BT's: 13" Bl. Oak bears N. 25° 03' W. 19.3 ft. scribed 1/4 S10 BT.
13" White "Y" Oak bears N. 17° 05' E. 87.7 ft. " 1/4 S11 BT.

FD. OR 11/17 - PEARLE D.C.S.O. C.S. 59/42

RE-RENEWED, SEE CORNER NO. #193

Roger Gee
For Ray
Graves
M 32 - 42

1/4 Corner to Sections 16 and 17. 140
Set - 1" x 48" Iron Rod at mid point on section line.
Bearing Tree: 48" Black Oak bears N. 81° 30' W. 132.07 ft.

Nov. 1966

RE-RENEWED, SEE CORNER NO. #180

FD. I.P. 8/90
M 110-59

Sec. Cor. to Sections 30 & 31, T27-6W.
and Secs. 25 & 36, T27-7W.
Set - 1 1/4" Iron Rod by proportionate measurement

141

Roger H. Gee
For. E.C. Ziegler
Map M 33 - 48

1/4 Corner to Sec. 25, T27-7W. and
Sec. 30, T27-6W.
Set - 1 1/4" Iron Rod
P. Pole N. 74° 58' W. 198.0 ft.
12" Fir S. 87° 40' E. 169.3 ft.

142

Oct. 1967