

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

143

Section Corner to Sections 6 and 5 only, T28-6W.
Found - 1961 Co. Surv. Brass Cap, properly mkd., but disturbed from original position. See Ren. #83, T28-6W.

Orig. 24" W.Oak S.61°W. 679.8 ft., tree opened before, scribe visible, "S" & other marks.

24" B.Oak S.88°W. 497.0 ft., tree partially grown over, parts of scribing visible.

Set - New Brass Cap at Cor. with Steel Post alongside & old Brass Cap in hole, set in concrete mkd: County Surveyor's Office, 1970

New BT: 24" B.Oak N.20°W. 534.3 ft. scribed T27S R6W S CSBT.

Set - 5/8" I. Rod N.20°W. 29.1 ft. in E.-W. Fence Line.

Note - Brass Cap 7" underground.

12/70

S32
S 6 | S 5

John M. Powell
W. Penley
C.S. File No. 49/50

144

1/4 Corner to Sections 2 and 3.

Found - Orig. 10", now 27" W. Oak bears N. 58 1/4°E. 69.3 ft., shows upper & lower scar. I do not open. Orig. BT. rescribed "1/4 S2 BT".

Set Brass Cap Stamped 1/4 S 3/S 2 T27S R6W RPLS 544 1972

New BT: 10" W.Oak bears N.72°E. 56.9 ft. scribed 1/4 S2 BT.

145

S. E. Corner D. L. C. No. 45.

Found - 1" I. Pipe, unrecorded.

Orig. 28" B.Oak bears N.77°W. 45.0 ft., face rotted out.

New BT: 8" W.Oak bears S.75°W. 80.0 ft. scribed:

"SE DLC 45 BT."

146

S. W. Corner D. L. C. No. 45.

Set - Brass Cap stamped SW Cor. DLC 45 SE Cor. DLC 51

T 27 S R 6 W RPLS 544 1972

147

S. W. Corner D.L.C. #53

Found - Brass Cap marked County Surveyors Office

Note - Markings on cap must be read from north side. Ren. No. 49

30" W.O., now stump bears N.2°W., 113.6 ft., scribing visible.

10" now 12" B.Oak bears S.43°E., 118.7 ft. showing well healed blazes.

New bearing object - N.W. corner of concrete block building (dimensions 9 ft. N & S, 10 ft. E & W) bears S.86 1/2°E., 31.45 ft.

Note - Corner lies in N-S fenceline approx. 80 ft. north of center line of west Military Ave.

2/1/74

148

S.E. Corner D.L.C. 56

See Ren. #50 & 131

Found - 3 1/4" I.R. Buried 8" in loose silt from which a :

10" now 11" Hawthorn bears S.23°W., 9.8 ft. scribing "RP B" visible on unhealed blaze. (See M4-11).

Found - Orig. 4" now 24" B.Oak with a well healed scar at RP-C as noted by E.S. Woodford in M4-11.

Found no trace of orig. I.Pin at "RP-C".

We set - A 5/8" x 30" I.Rod, flush with the ground with plastic survey cap attached, mkd. "DOUG. CO. SURVEYOR" at the intersection of the record distances from RP-B and the aforementioned 24" B.Oak bearing tree. This 24" B.O. BT will be destroyed and the area covered with fill material.

We reference "RP-C" as follows:

A chiseled + on the most NW easterly concrete pier of the Washington Street Bridge, 6' above ground, bears N.80 1/4°W., 57.20 ft. (Note: this is the same chiseled mark as noted in Ren. #131.)

MARCH 71

Don E. Garrett
For Walter Welker
May, 1972 M 45 - 71

Jan 1973

Gary L. Langlitz
P. Earle
C.S. 56/43
2/1/74

Gary Langlitz
P. Earle
Aug. 19, 1974
C.S. 57/2