

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 6 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

152

Section Corner for Secs. 1, 2, 11 and 12.

Found - A 1" I.P. with brass cap marked "County Surveyors Office"
T27S S2 S1 S11 S12 R6W

An orig. B. Oak, 13" now 30" bears N.22 1/2°E., 24.2 ft. (Rec. Y. Oak at 22.4 ft.). We open and find old ax marks no scribing center decayed.

A Y. Oak now a burned stump bears S.62°W., 66.9 ft. (Rec. S.60°W., 68.6 ft.) No scribing found.

A 18" Y. Oak now 36" bears N.85°W., 90.4 ft. (Rec. N.88 1/2°W.) Tree has faint blaze.

A 5" now 7" Madrone bears S.55°E., to face S.59°E. to center at base 9.6 ft. Tree has rotted blaze "BT" visible. Ren. #42

A 9" now 13" B. Oak bears S.57°W., 40.5 ft. Tree has well healed double blaze.

New BT's- A 6" B. Oak bears S.72°E., 19.1 ft. Tree double blazed and scribed "T27S R6W S12 CS BT".

A 9" B. Oak bears N.84°E., 20.0 ft. Tree double blazed and scribed "T27S R6W S1 CS BT".

8/10/77

153

1/4 Corner for Sec. 6 and Sec. 1 of T27-7

Found - A 1 1/4" I.P. bent over 3" above ground bears S.58°E., 1.2 ft. with a 1"x26" hollow drill rod at the south edge set 6" below ground.

A 13" now 42" W. Oak bears S.52 3/4°W., 23.1 ft. with a well healed blaze. (OBT)

A 10" now 26" W. Oak bears S.65°E., 44.7 ft. (Rec. S.67 1/2°E., 43.1 ft.) with a well healed double blaze. (Lower part of upper blaze is rotted) Ren. #9

Set - A 1" x 36" I.P. with a brass cap set 4" above ground marked:
"Douglas County Surveyor

R	T 27 S	R
7	S 1 S 6	6
W	1/4	W

No new accessories..Corner is 40 ft.South of Orchard Lane, 1 ft. North of an East-West fence, 16 ft. West of a fence to the South.

3/23/78

154

Section Corner for Sec 1; and Sec. 6, T27-5; Sec. 36, T26-6; Sec. 31, T26-5.

Found - A 1" O.D. Iron pipe firmly set in a mound of stone. Ren. #119

We find depressions in the ground and fragments of oak roots at the approx. record postions of the orig. NE. SE, and NW bearing trees. There is no identifiable evidence at these positions.

A 10" now 13" Fork of a W. Oak alive with well healed double blaze bears S.63°W., 27.8 ft. (measured to center of root crown at ground level). (Rec. S.55°W., 27.8 ft.)

A 6" now 10" W. Oak, alive with well healed double blaze bears S.14°E., 15.4 ft. (Rec. S.14°E., 15 ft.)

A 6" now 9" W. Oak, alive with well healed double blaze bears N.70°E., 48.0 ft. (Rec. N.73°E., 48 ft.).

A 10" now 17" W. Oak, alive with well healed double blaze bears N.48°W., 73.3 ft. (Rec. N.50°W., 74.1 ft.)

Set - At the location of the found 1" O.D. Iron pipe, we set a 1" x 30" I. Pipe with brass cap attached 28" in the ground, surrounded with rock and the found iron pipe alongside. We Mark the brass cap: Douglas Co. Surveyor T 26 S

R 6 W	S 36 S31	R 5 W
	S 1 S 6	

No new accessories.

155

Section corner for Secs. 23, 24, 26 and 25.

Found - A 2" x 36" Galv. I.P. approx. 1 in. above ground. In center of pipe is a wooden hub with a PK nail. Pipe located in middle of horse pasture.

A 16" White Oak, now 30" bears S.77°W., (Rec. S.75°W.) 287.4 ft. with healed over double blaze. Also on tree, L and A bark scribed. Ren. #5

A 8" White oak, now 29" bears S.14°E., (Rec. S.16°E.) 256.6 ft. (Rec.C.S. 60/17 256.1 ft.) with healed over top and bottom blaze, middle part was chopped out at one time, visible "7S". Ren. #5

A 15" White Oak, now a 20" bears N.2°W., (Rec. N:0°E.) 575.5 ft. with rotted out blaze. No original evidence left.

L. E. Monrean
Mike Cline
Doug. Co. Sureyors
Office
Aug. 10, 1977
C.S. 59/38

R. B. Kimberling
P.L. Earle
Doug. Co. Surveyor
Office
March 23, 1978
C.S. 59/46

Gary Langlitz, Doug. Co.
Surveyors Office
S.J. Flause, F.C. Silagy
April, 24, 1978
C.S. 59/46

Karen Reed
P. Earle - F. Silagy
Doug. Co. Surveyors
Office
Dec. 13, 1978