Douglas County Surveyor's Record of Government Corners Renewed

27 T. S. 6 R. W. W. M.

KURZ-CHAPMAN CO., EUGENE, ORE. STORE

19

¼ CORNER BETWEEN 15 and 16.
Location determined from deed description ties and location of County Road as given in old recorded surveys. Set in 1" Iron Pipe driven 6" underground on center line of County Road at terminus trees of.
Black Oak 20" dia. bears S.2°E., 29 ft. blazed and scribed
S. 15 - 16 C.S. B.T.

RE-RENEWED, SEE CORNER NO. #160

20

S.E CORNER OF D.L.C. # 43
Measured from Iron Pipes on Laurel Crest Plat and from N.E. corner of Cl. 43. I set 1 x 30" shaft for corner. I marked the following trees
White Oak 30" dia. bears N.71°E., 466 ft. marked S.E.
Cl. 43 C.S. B.T.

RE-RENEWED, SEE CORNER NO. 101

21

CORNER BETWEEN 9-10-16-15.
This corner was a chipped river boulder buried in field by previous surveyor. I set a 1¼ x 18" Iron Bar under stone with charcoal around from which
Oak 40" dia. bears S.83°30'W., 185 ft.
South corner (concrete basement) of Ben F. Jones house bears N.67°30'W., 156.7 ft.

RE-RENEWED, SEE CORNER NO. 47

Chuck 159.33 ZBJ

Nov. 15, 1934
Wit. H. L. Epstein Co. Sur.
C.W.Crocker Witnesses
Ray Webber Jacob W. Jones
Harry Titus Ben F. Jones
Ernest Brown Bert A. Lane
VOL 4 Pg. 50-58

22

E.S.E. CORNER OF D.L.C. # 55
I set Iron pipe for corner from one old B.T. on which the marking was plain. Marked new B.T.s as follows
White Oak 20" dia. bears S.49°28'W., 97 ft.
White Oak 30" dia. bears S. 5°02'W., 116.5 ft.
Bear true carried from C. and G. Survey.

RE-RENEWED, SEE CORNER NO. 121

Apr. 6, 1935

23

CORNER OF SECTIONS 18, 17, 19, and 20.
I Set 3 x 3 x 30" Oak stake from two old bearing trees from which the new bearing trees are as follows
Red Fir 16" dia. bears S.51°E., 12.9 ft.
A Laurel 12" dia. bears S.61½°W., 44.9 ft.
Black Oak 14" dia. bears N.86°W., 43.8 ft.
Black Oak 10" dia. bears N.32¾°E., 41.3 ft.

RE-RENEWED, SEE CORNER NO. 67

24

¼ CORNER BETWEEN 13 and 18
On East line of T.27-6W. Set ½ x 48" pipe inside 2 x 48" pipe about 250 ft. south of H. Burg hous in fence row. I marked the following trees
White Oak S.57°W., 223.5 ft. 10" dia.
White Oak 18" dia. bears S.24¼°W., 242.3 ft.

25

M.C. ON RIGHT BANK OF S. UMPQUA RIVER ON EAST LINE OF T.27-6W. BETWEEN 13 and 18.
Set an Iron Rod 5/8" x 4½', with 3 prongs on top, 4.8 ft. from S. P. R. R. South Rail White Oak 14" dia. bears S.60½°W., 117.4 ft. A Chanel Iron 1¼ x 18" under right of way fence bears N.16¼°W., 62 ft. Corner is about (½) 45' South of B.C. of R.R. curve north of cut on R.R.

(See Rem # 115)

Mar. 26, 1935
F. C. Frear
Witnesses
P. D. Wolford
J. H. Wolford

26

N.W. CORNER OF Cl. 63
Wagon skein
Inside of East Rail of S.P.R.R. 59.1 ft. West. Soldiers Home Smoke stack S.45½°W., Beacon on Mr. Nebo S.3½°W., Mt. Rose △ Sta. S.89°E.(July 1948) Set 1" x 36" iron pipe with brass cap for cor. Stamped ~~Scribed~~ C. S. DLC #63 (Evans, Richardson, Kershner)

RE-RENEWED, SEE CORNER NO. 62

27

E. CORNER OF Cl. 39
Rock 26 x 10 x 10" 8" under ground. Marked a bearing tree as follows
White Oak 8" dia. bears S.75°W., 213.9 ft. marked C.S.
Cl. 39 B.T.

RE-RENEWED, SEE CORNER NO. 65

28

S.W. CORNER OF Cl. 39
Plow Share. Notch in Curb South 8.7 ft. Right corner of lower step of Caskey house S.4°W., 69.2 ft.

See M 16-2

RE-RENEWED, SEE CORNER NO. #174

(FD. plow share 1/25, R. WARE M 90-61)