

Douglas County Surveyor's Record of  
Government Corners Renewed

T 27 T. S. R 6 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

192

C O N T - -

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
March 9, 1990  
C.S. 64/6

10" now 11" dia. W. Oak with a fully healed double blaze bears  
S.28½°E., 25.3 ft. (Rec. S.33°E., 25.3 ft.) Ren. No. 31  
16" now 24" dia. 4 ft. high D. fir stump with a fully healed  
double blaze bears N.41°W., 49/6 ft. (agrees w/rec.) Ren. #31  
14" now 18" dia. 5½ ft. high D. fir stump with a fully healed  
double blaze bears N.32°E., 30.3 ft. (Rec. N.32°E., 29.7 ft.)  
Set - A 2 3/8" dia. Brass cap on a 1 3/8" O.D. x 32" long iron pipe,  
is set at referenced position of 1" i.P. BC/IP protrudes  
5" above ground with 1" I.D. x 30" long I.P. from Ren. #31 set  
along east side of BC/IP. 1" IP protrudes 4" above ground.  
New BTs - 6" dia. W. Oak double blazed and scribed "T27S R6W S23 CS BT"  
bears N.75½°E., 6.5 ft.  
9" dia. Madrone bark scribed "T27S R6W S27 CS BT" bears  
S.22½°W., 34.8 ft.  
Corner lies at the intersection of an east-west and south running barbed  
wire fence line. These fence lines are old and not maintained. A lot of  
wire is on the ground.

3/9/90

FD. 9/90; 1990-0064A&B

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
April 25, 1990  
C.S. 64/6

1/4 Corner for Sections 10 and 11  
Found - 1969 2½ dia. brass cap on a 1½" O.D. iron pipe protruding  
23" above ground. I.P. is bent, top is approx. 9" east  
of plumb. Ren. #139  
13" now 16" dia. B. oak with a fully healed double blaze bears  
N.27°W., 19.3 ft. (Rec. N.25°03'W., 19.3 ft.) Ren. #139  
13" now 14" dia. W. oak with a fully healed double blaze bears  
N.16°E., 80.3 ft. (Rec. N.17°05'E., 80.3 ft.) Ren. #139  
5/8" iron rod protruding 7" above ground 5" south of fence line  
bears S.1½°E., 79.43 ft. (Rec. S.0°¼'W., 79.29 ft.) Per M37-14  
Set - Brass cap/iron pipe is referenced at plumb position, BC/IP  
measures 36" long. BC/IP is straightened and returned to  
referenced position. BC/IP now protrudes 7" above ground.  
New Accessories:  
3/4" Iron rod protruding 4" above ground (R/W pin 8" south of  
fence line) bears S.37°W., 83.81 ft.  
3/4" iron rod protruding 3" above ground (R/W pin in fence line)  
bears S.47 3/4°E., 157.99 ft.  
Corner is 18" south of a 2 way fence corner, fences run north and east.

4/25/90

193