

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 6 R. W. W. M.

SECTION CORNER BETWEEN 10, 11, 14 and 15
Set a 2 x 30" Iron Pipe from which
Apple Tree 11" dia. bears N.57°36'W., a distance of
412.5 ft.
Catalpa tree 12" dia. marked with a 2 x 12" blaze on
the N.W. side bears S.23°E. a distance of 370 ft.
A 1 1/4 by 24" Iron Bolt on the S.W. corner of the Junction of
the County Road bears S.14°41'W. a distance of 462.0 ft.
Set from property ties to S.E. and S.W. also to N.E. and
N.W. all of which check back to location used for this corner.

29

A Boyer
J.M. Morgan
H. B. Church
Oct. 9, 1944
C.S. 33/32

SEE COR. #108
FOR BRASS CAP SET
6-13-62

SECTION CORNER BETWEEN 22, 23, 27, and 26.
Location identified from original bearing tree in S.W.
Quadrant and from fence corner. Drove a gun barrel for
corner, from which
Fir 11" dia. bears N.20°37'W., 35.5 ft.
White Oak 36" dia. bears N.44°54'E., 32.5 ft. O.B.T.
Fir 8" dia. bears S.27°49'E., 28.6 ft.

Ben E. Irving
Wit.
H. C. Boyle
R. L. Irving
June 3, 1926

*This corner was set
from a false description
of the original
from as shown on map 1945*

N.W. CORNER OF D.L.C. # 55
This corner was set by G. G. Stewart from the stump of
an old B.T. scribe marks visible. Also checked by Cole. A
stake was in place, with pile of stone. A White Oak 24"
diam. marked and scribed by Stewart but now rotting bears
N.9 1/2°E., 237.2 ft. As this corner had never been recorded
I marked a new B.T. 24" White Oak bears N.1°E., 209.2 ft.

30

H.L. Eppstein C.S.
Wit.
James Campbell
E. E. Richardson
Dec. 24, 1940

Section Corner Sections 22-23-26-27
Corner as set erroneously 1926 destroyed as noted above.
Correct location identified from original bearing trees as
follows: 36" Oak N44 1/2°E 157 lks. original scars had been chopped out
and all scribe marks rotted off. Old oak stump S 75 1/2°W 78 lks
burned off even with the ground position correct. Old oak tree
fallen down but found scars which when chopped out bears the
reverse of scribe marks R6WT27W S26, original face obliterated.
A 12" W. Oak N 46°W 136 lks checked for position which when
chopped out revealed the BT. All bearing checked. Distances
checked when measured on the slope instead of horizontal..

31

Ben. B. Irving
County Surveyor
Witness.
N.E. Richardson
Deputy.

Drove a 1"x30" pipe 28" in the ground for the corner from
which a fir 16" diam bears N 41°W 49.6 ft. scribed T27S R6W S22
CS BT; a fir 34" diam bears N 32°E 29.7 ft. scribed T27S R6W S23
CS BT; a W. Oak 19" diam bears S 33°E 25.3 ft. scribed T27S R6W
S26 CS BT. There was no tree or other object in the SW quadrant
suitable for witness.

#192

NW COR. ISAAC JONES DLC #65
Set and iron pipe 1 1/2"x30" with a brass cap at
intersection of N line and W line of Isaac Jones
DLC #65. Inscribed "NW Cor DLC # 65" and with the
County Surveyors stamp.
W. Oak 15" dia. bears N 69°59' E 284.3 feet.
W. Oak 15" dia. bears S 30°37' E 394.9 feet.

32

N.E. Richardson
Dep. Co. Sur.
Wit.
Milo Godfrey
Les Kershner
July 8, 1946

SW COR DLC#56
Set and iron pipe 1"x36" with a brass cap, 24 ins. in
ground mkd. SW cor. DLC#56, Douglas County Surveyors
office from which an
Iron Pin bears N 20° 00' W 34.15 ft.
W. Oak 28" diam bears N 60° 07' E 112.0 ft.
Iron Pin bears S 79° 12' E 79.9 ft.
Iron Pin bears S 18° 44' E 126.66 ft.

33

N.E. Richardson
Surveyor
Milo E. Godfrey
Les Kershner
Witnesses
C.S 38/170

April 23, 1947

NW COR. D.L.C. #64
Set 5/8" x 30" Iron Rod with a mound of rock.
Remarked three O. B. T's.

34

N. E. Richardson
Dep. Cnty. Surv.
M.E. Godfrey-Wit.
L. S. Kershner-Wit.

August 7, 1947

RE-RENEWED, SEE CORNER NO. #150