

Douglas County Surveyor's Record of  
Government Corners Renewed

27 T. S. 6 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97196

SEC. COR. 5-6-7-8

Found rock 7" x 9" with cross on it, from which  
28" W. O. bears S 66 $\frac{1}{2}$ ° W 96.9 ft.  
36" W. O. bears N 53 $\frac{1}{2}$ ° E 206.0 ft.  
12" W. O. bears S 26 $\frac{1}{2}$ ° E 3.8 ft.

*FD. 12/83  
M 95-71  
C. BAUGHMAN  
L/S R. WARE  
M 90-57*

45

Richardson-Surv.  
Godfrey - Wlt.  
Matthews  
Dec. 1949

NWInt.  $\angle$  Cor. Wm. McKinney DLC 50

Rock 6"x12"x4" underground in the Co. Road leading from Melrose  
road to Old Conn Ferry. New B.T.s all O.B.T.s having been  
destroyed.

Black Oak 24" diam. bears S 67° 55' E 105.2 ft.

46

RESET SEC. COR. 9 - 10 - 15 - 16

*See also COR # 21*

Over iron rod set concrete post 6" x 6" x 24" with brass plate 3 $\frac{1}{2}$ "  
dia. top of ground surface.  
Marked brass plate

COUNTY T 27 S  
9 | 10  
16 | 15  
R 6 W  
OFFICE

**RE-RENEWED, SEE CORNER NO. # 169**

BB Irving - Surv.  
Witness - RL Irving  
March, 1939

BB Irving - Surv.  
Ben F. Jones - Wlt.  
April 5, 1951

48

1 Corner 29-30

Set brass cap. Trees as listed in original govt. field notes.

**RE-RENEWED, SEE CORNER NO. # 82**

A.R. Evans 1952  
File 41 Envelope 57

Southwest corner Donation Land Claim No. 53.

Found Brass Cap at corner. - *See Cor. No. 44*

Blazed and Scribed:

30" W. O., N. 2° W., 113.6 feet, on N., S. Fence line.

10" B. O., S. 43° E., 118.7 feet.

Note: L. P. and B. T. for this D. L. C. corner have been destroyed.

49

James Byron  
Ray Irving  
September 21,  
1955.  
G. S. File  
47/5.

50

Southeast corner of the J. R. Huntley D. L. C. No. 56.

Location of corner point determined by running the East and South lines  
of D. L. C. No. 56.

Set a 2 inch x 4 inch hub at corner point. Since this point is not safe  
from being washed out, I set two  $\frac{3}{4}$  inch x 42 inch iron reinforcing  
rods on the high bank of river and far enough back from the river channel  
to be safe for reference points and mark a witness tree for each  
reference point.

The first reference point bears S. 81° 48' E., 411.26 feet from corner,  
from which:

A 10 inch Hawthorne bears - S. 23° W., 9.8 feet.

The second reference point bears S. 59° 16' 30" W., 115.77 feet from the  
first reference point, from which:

A 4 inch B. Oak bears N. 9° 45' W., 27.9 feet.

E. S. Woodford  
August, 1956  
C. S. File No. 42/221.  
M 4-11

131

*ALSO SEE OLD REV. Vol. 1691*