

Douglas County Surveyor's Record of  
Government Corners Renewed

27 T.S. 6 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

James W. Byron  
M. Godfrey  
J. Fee  
June 14, 1957  
C.S. File No. 47/200

Section Corner to Sections 24, 25, 19, & 30. R 6W R 5W 51  
Set Brass Cap in corner flush with ground surface marked: 24/19 T 27S  
County Surveyor's Office, 1957 25/30  
18 inch High Brick Wall bears S.34°27'50"E. 1.4 feet & S.55°30'10"W. 0.2 ft.

James W. Byron  
R. Irving  
J. Fee  
For Earl Wiley  
April, June, 1955  
C.S. File No. 46/155 - M 7 - 23

Section Corner to Sections 21, 22, 27, & 28. 52  
Found - 2" I. P. at old fence Corner. Also 30" B.O. S.36½°W. 88.6 ft.  
We open & find good scribe (R6 S2) Scribed about 30 years ago.  
From Corner: 12" Madrone bears S.64°E. 27.0 ft. scribed S27 CS BT.  
10" W. O. bears N.54°E. 5.5 ft. scribed S22 CS BT.  
18" B. O. bears S.17°W. 84.5 ft. scribed S28 T27 R6 CS BT.  
18" W. O. bears N.62½°W. 106.5 ft. scribed S21 T27 R6 CS BT.

FD I.P. OK  
1/18/55  
D. BENTZ  
M 97-31

FD OK 12/13 - GARRETT M 52-14

¼ Section Corner to Sections 21 & 22. 53  
¼ Corner located on True Line & at Midpoint N. W. Corner Section 22 &  
S. W. Corner Section 22.  
Set Brass Cap 1" above surface marked ¼ S 21/22 County Surveyor's  
Office, 1955.  
Set ¾" I. R. at base of 12" Anchor Post (fence) scribe B. O.  
Blaze & Scribe 12" W. O. N.60°31'30"W. 134.5 ft. scribed ¼ S21 CS BT.  
N.62°W. 1/11/61

FD OK 12/23 - GARRETT - M52-14

6/12/55 - J. COXMAN - 6/12/55 - M81-19  
1/18/57

James W. Byron  
M. Godfrey  
S. Bilow  
Jan. 3, 1958  
C.S. File 49/55

Renewal of N. E. Corner D. L. C. #56, T27S, R6W. 54  
Found 1" Axle set in Concrete. REN #12  
Set 1" Pipe with Brass Cap stamped "County Surveyor's Office, 1958,  
T. 27 S., R. 6 W., N. E. Corner D. L. C. 56".  
See Sketch in File for exact location of Brass Cap.

FD OK  
1-30  
M. WEINBUCHER  
M 101-71

FD. 84  
D. BENTZ  
DEPT. L-7

Ben. Irving  
For. Vets  
Admin.  
May, 1952  
C.S. File 45/77

Section Corner to Sections 13, 14, 23, & 24. 55  
Set 1" I. P. - Brass Cap marked Co. Surveyor's Office,  
From Which: S.W. Corner Dining Hall bears N.27°W. 33.0 ft.  
24" Spruce bears S.46°E. 48.0 ft. (Not Marked)

FD OK  
2/18/52  
R. WARE  
M 100-28

REN #3

FD OK 12/14  
D. BENTZ  
M 90-63

James W. Byron  
M. Godfrey  
S. Bilow  
Jan. 16, 1958  
C.S. File 49/62

¼ SECTION TO SEC. 1, T21/R6 & SEC. 6, T21/R5 56  
Found Machine Gun Barrel at Corner. (SEE REN #39 T21-5)  
Also Found White Oak 20" diam. S.83°W. 77.7 ft., showing good scars.  
Did not chop open.  
No trace of S. E. Tree marked by B. Irving in 1934 could be found.  
Blaze & Scribe: 6" Madrone N.60°E. 29.7 ft. Scribe Madrone "¼ S6 CSET."  
DID NOT SET NEW CORNER, BARREL IN GOOD CONDITION.

FD OK  
11/30  
S. SHAW  
RM 3-38

James W. Byron  
M. Godfrey  
S. Bilow  
Jan. 3, 1958  
C.S. File No. 49/61

Section Corner to Sections 24 & 25. 57  
No Trace of Original BTs. can be found. See C.S. File 49/61.  
Set Brass Cap at corner marked ¼ S24 T27S, R6W, County Surveyor's  
Office, 1958  
From Which: Bearing object chisled cross in concrete near East End  
of Concrete Curb, bears N.28°E. 9.0 ft.  
18" W. Oak bears S.41°E. 6.0 ft. scribed ¼ S25 CS BT.

James W. Byron, Deputy  
Milo Godfrey  
S. A. Bilow  
Sept. 9, 1958  
C. S. File No. 49/62

Section Corner to Sections 6 & 7, T27S R6W, & Secs. 1 & 12 T27S R7W. 58  
Found - Stewart's 24", now 36" R. Fir S.42°E. 97.3 ft. I open & find  
good scribing "S". REN #10  
All other BT's gone except N.E. BT. which is down, has been  
washed out. Shows good scar. I do not open.  
Note - Corner falls in Creek. I set Witness Corner 80.0 ft. South  
of true Corner.  
Set Brass Cap at Witness Corner Mkd: Wit. Cor. North 80.0 ft. to S 1/S6  
County Surveyor's Office, 1958 S12/S7 T27S  
New BT's: R7W R6W  
18" R. Fir bears S.78°E. 25.5 ft. scribed W.C. S7 T27S R6W CS BT.  
8" R. Fir bears S.41°W. 25.0 ft. scribed W.C. S12 T27S R7W CS BT.  
11" R. Fir bears N.39°W. 63.2 ft. scribed W.C. S1 T27S R7W CS BT.  
14" Myrtle " N.26°E. 14.4 ft. scribed S6 CS BT WC. This tree  
scribed high above wire fence.

FD OK 4/6/58  
R. WARE  
M 96-57