

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 6 R. W. W. M.


KOKE-CHAPMAN CO., EUGENE, ORE. 97106

James W. Deputy, Dpty County Surveyor
Milo Godfrey
Clete Putnam
December 1960
C. S. File No. 49/79

74
1/4 Section Corner to Sections 17 and 20.
Found - Orig. 24", now 36" W.Oak S.31 1/4°E. 386.8 ft. We open &
find good scribing "S".
Orig. N.E. BT. not found.
Set Brass Cap at Corner Mkd: County Surveyor's 1/4 S17 T27S R6W
Office, 1961 S20
New BT's: 15" W.Oak bears N.34°E. 31.0 ft. scribed 1/4 S17 CS BT.
7" B.Oak bears S.47°W. 10.0 ft. scribed 1/4 S20 CS BT.

FD. OK. 8/84
D. BENTZ
M 97-23

75
Section Corner to Sections 8 - 9 - 16 - 17.
Found - B.Oak, now 30", S.43°E. 25.7 ft. Chopped this tree open
& found good scribing.
12" W.Oak, now 20", N.10°E. 40.9 ft. This tree is in
good condition, shows good scar.
10" B.Oak, now 19", S.35°W. 64.7 ft. This tree dead, but
standing, shows scar.
No trace found of N. W. Tree.
Set Iron Pipe with Brass Cap Mkd: County Surveyor's S 8 | S 9 T27S R6W
Office, 1960 S17 | S16
New BT's: 9" W.Oak S. 2°E. 9 ft. mkd. T27S R6W S16 CS BT.
11" D.Fir S.32°W.19 ft. mkd. T27S R6W S17 CS BT.
11" D.Fir N.32°W. 29.2 ft. T27S R6W S 8 CS BT.

76
Section Corner to Sections 7 - 8 - 17 - 18.
Found - Orig. 18", now down 28" Laurel N.52°E. 35.0 ft. We open
& find good reverse scribing "T".
No other Orig. BT's. found.
Set Brass Cap at Corner Mkd: County Surveyor's S 7 | S 8 T27S R6W
Office, 1960 S 18 | S17
Fence Corner Thus: 
New BT's: 20" B.O. N.67°W. 13.9 ft. scribed S 7 T27S R6W CS BT.
18" R.Fir S.58°W. 134.0 ft. scribed S18 T27S R6W CS BT.
7" W.Oak S.87 1/2°E.119.3 ft. scribed S17 CS BT.
20" B.Oak N.66°E. 81.9 ft. scribed S 8 T27S R6W CS BT.

FD. B.C.
4/84
R. WARE
M 90-57

77
1/4 Section Corner to Sections 7 and 8.
Found - Orig. 12", now 18" Maple Snag, shows good reverse scribing "1/4 S",
N.75°E. 21.8 ft.
Orig. 16", now 22" B.Oak S.55°W. 54.8 ft., shows good scars.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960 S 7 | S 8 T27S R6W
New BT's: 20" R.Fir bears N.14 1/2°E. 19.8 ft. scribed 1/4 S 8 CS BT.
5" B.Oak bears S.62°W. 24.3 ft. scribed 1/4 S 7 CS BT.

FD. 4/84
R. WARE
M 90-57

78
Section Corner to Sections 17 - 16 - 20 - 21.
Found - Orig. 6", now 18" W.Oak N.41 1/2°W. 55.4 ft., shows scars.
I do not open.
Orig. 20", now 32" W.Oak S.63°W. 169.0 ft. We find bearing #189
should be S.59°W. Shows scars.
Old Laurel Stump checks dist. for N.E. BT. Bearing record
N.88 1/2°E. We find should be N.83°E.
Orig. 9", now 18" B.Oak S.23 1/2°E. 86.5 ft. We find to be 82.5 ft.
We open & find good scribing
Also find 1 1/2" Iron Pipe at Corner & East West Fence.
Set Brass Cap at Corner Mkd: County Surveyor's S17 | S16 T27S R6W
Office, 1960 S20 | S21
New BTs: Orig. N. W. BT. is O. K.
5" W.Oak bears S.66°E. 42.4 ft. scribed S21 CS BT.
6" W.Oak bears N.39°E. 50.0 ft. scribed S16 T27S R6W CS BT.
10" W.Oak bears S.69°W. 122.8 ft. scribed S20 T27S R6W CS BT.

RE-NEWED, SEE CORNER NO. 189