

Douglas County Surveyor's Record of  
Government Corners Renewed

27 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Angle Point (Ford's  $\frac{1}{4}$  Sec. 33). 121  
Found - Brass Cap at Corner Mkd: AP (1924 survey)  
1924  
Stump of S.W. BT., good scribing.  
S. E. BT. not found.  
New BT's: 8" Cedar bears N.76°W. 16.2 ft. scribed AP CS BT.  
(scribed high above fence)  
R.Fir bears S.8°W. 33.4 ft. scribed AP CS BT.

Angle Point 10;  $\frac{1}{4}$  Cor. S 33. 122  
Found - Brass Cap and both BT's. N.E. BT., face rotted.  
New BT: 17" Laurel bears N. 9 $\frac{1}{2}$ °E. 34.9 ft. scribed  $\frac{1}{4}$  S33 CS BT.

South  $\frac{1}{4}$  Corner to Section 36. 122A  
Found - Brass Cap at Corner. BT's. not found.  
New BT's: 15" Ash bears S.84°E. 21.3 ft. scribed  $\frac{1}{4}$  S36 CS BT.  
12" Ash bears N.86°W. 10.7 ft. scribed  $\frac{1}{4}$  S36 CS BT.  
Corner is 4 feet North of Fence.

Renew Section Corner S33/S34 123  
AP 12  
Found - Stump, now 18", N. 63°E. 21.8 ft., shows old scars &  
burned areas. No scribing found.  
Also find AP which bears N.32°E. 90.4 ft., checks dist. &  
bearing. We do not find N. W. BT.  
Find Brass Cap (1924 survey) laying on Stump near corner.  
Reset - Brass Cap at Corner & 1.5 ft. West of New Wire Fence.  
New BT's: 8" R.Fir bears N.60 $\frac{3}{4}$ °W. 94.0 ft. scribed T27S R7W S33 CS BT.  
9" R.Fir bears N.60°E. 102.2 ft. scribed T27S R7W S34 CS BT.

Renew Angle Point which bears N.32°E. 90.4 ft. from Sec. Cor. S33/S34.  
Found - Brass Cap at Corner. 124  
New BT's: 12" Laurel bears S.71°E. 63.9 ft. scribed AP CS BT.  
12" W.Fir bears N.29°W. 41.3 ft. scribed AP CS BT.

South  $\frac{1}{4}$  Section Corner to Section 35 only. 125  
Found Iron Pipe with Brass Cap set in 1924.  
Corner is in Fence Corner - Fences E. W. & N.  
Also Found Iron Pipe with Brass Cap set in 1924 (for Angle Point)  
N.15°W. 32 feet., record 33 feet.  
New BT's: 16" Pine N.15°W. 242.7 ft. Mkd:  $\frac{1}{4}$  S35 CS BT.  
Note - This same Tree bears N.15°W. 210.7 ft. from Brass Cap at A. P.

South  $\frac{1}{4}$  Corner to Section 31. 126  
Found - Brass Cap. Both Orig. BT's. & Eppstein's S.W. BT. REN.#22  
New BT's: 6" W.Oak bears N.25°E. 29.6 ft. scribed  $\frac{1}{4}$  S31 CS BT.  
8" W.Oak bears N.67 $\frac{1}{2}$ °W. 44.9 ft. scribed  $\frac{1}{4}$  S31 CS BT.

Renew A.P. (N.38°19'E. 52.5' from S.E. Cor. Sec. 31, T27-7W. 127  
Found - Brass Cap & Stump of S. W. BT.  
New BT'S: 8" Pine S.40 $\frac{1}{2}$ °E. 34.7 ft. scribed AP CS BT.  
7" R.Fir N.4°W. 41.0 ft. scribed AP CS BT.

Renew A.P. (S.38°21'W. 7.39 Chains from N.E. Corner Sec. 6, T28S R7W. 128  
Found - Brass Cap. S.W. BT., now Stump - S.E. BT. shows scar.  
New BT'S: 20" Myrtle bears N.63 $\frac{1}{2}$ °E. 40.0 ft. scribed A.P. CS BT  
6" W.Fir N.55 $\frac{1}{2}$ °W. 42.6 ft. scribed A.P. CS BT.

North  $\frac{1}{4}$  Corner Section 36. (T.28-7) 129  
Found - Brass Cap, out of ground. Reset from, now 24" W.O. S.85°W.  
15.0 ft., shows good scribe.  
New BT: 8" R.Fir bears S.18°E. 45.0 ft. scribed N  $\frac{1}{4}$  S6 CS BT.

James W. Byron, Deputy County Surveyor  
Milo Godfrey  
Clete Putnam  
February 1961  
C. S. File No. 49/79