

Douglas County Surveyor's Record of  
Government Corners Renewed

27 T. S. 7 R. W. W. M.

- This Cor is to* **13**
- ✓ N.W. CORNER OF HUNTLEY D.L.C. # 38 and 42. **CORNER NO. #152**  
Renew corner with Oak Stake from which original tree  
bears S.72°30'E., 2.24 lks. (Rec. 224 Lks)
- ✓ INTERIOR L CORNER OF D.L.C. # 38 and 43. *Located in T28-7*  
Renew corner with Oak stake. Set from original trees.
- ✓ CORNER OF SECTIONS 16, 17, 20, and 21. **CORNER NO. 80** **14**  
Reestablished from original bearing trees all standing  
by setting a 1½ x 48" Iron Pipe and remarking the B.T.s
- ✓ ¼ CORNER BETWEEN 1 and 12 **15**  
Reestablished from one original bearing tree faintly  
scribed. I Drove a ½" Iron Bar and post for corner and  
marked the following trees - 12/19/69- SEARCHED FOR, NOT FOUND  
Black Oak 24" dia. bears N.52½°E., 14.1 ft. *AREA LOGGED*  
Black Oak 12" dia. bears S.23°W., 21.9 ft. *BURNT. J.M.P. C.S. 54/23*
- ✓ CORNER TO SECTIONS 23, 24, 25, and 26. **16**  
I renewed this corner from three original B.T.s which  
check for distance and direction. The hole where the fourth  
tree stood is visible also checking for direction and distance.  
I set a ½ x 30" Iron Rod also 4 x 4 x 40" Oak Post for **97**  
corner.
- ✓ ¼ CORNER BETWEEN SECTIONS 25 and 26. **17**  
I renewed this corner from the original tree S.47°W., 12'  
lks. which I chopped open and found scribe mark. I set a  
cedar post and a mound of rock. I marked the following  
trees **5** **172**  
A White Oak 10" dia. bears N.68°00'W., 39 ft.  
A White Oak 10" dia. bears N.75°30'W., 30 ft.  
I also set a steel auto axle at the corner. *Changed 12/27/70*
- ✓ ELL CORNER OF D.L.C. # 42. - *SEARCHED FOR, NOT FD. - DEC '69 - J.M.P. C.S. 54/23* **18**  
Set 8" x 12" x 18" Rock for corner from original Bearing  
Tree which is badly rotted. Marked the following tree  
White Oak 36" dia. bears N.15°W., 33.2 ft.
- ✓ ¼ CORNER BETWEEN 11 and 12. **19**  
Drove ½" Iron Pipe from one standing original Bearing Tree  
and one stump. Marked the following trees **103**  
White Oak 18" dia. bears N.84°W., 60.7 ft.  
White Oak 6" dia. bears S.29½°W., 50 ft.
- ✓ N.W. EXTERIOR CORNER OF CLAIM # 43. **20**  
Location identified from O. B. T., a 24" White Oak scribed  
"N.W. Cl. 43 C.S." Set post scribed "N.W. Cl. 43 C.S." from  
which the O.B.T. bears S.63½°E., 66 lks. which I reblazed and  
scribed N.W. Cl. 43 C.S. B.T. and a new B.T.  
A White Oak 16" dia. bears S.40°E., 76 lks. scribed **71**  
N.W. Cl. 43 C.S. B.T.
- ✓ S.W. CORNER OF D.L.C. # 44 **21**  
Location identified from corner tree which it was nec-  
essary to chop down leaving as a corner post that portion  
originally blazed and from O.B.T. as described in the records  
of the County Surveyor. Reblazed and scribed original B.T.  
and set as an additional B.T. **72**  
A 24" Fir which bears N.59°W., 27.7 ft.
- ✓ ¼ CORNER SOUTH, LINE SECTION OF 31. **22**  
Standard Government Pipe set by Hatch, U. S. Surveyor.  
I marked new witness trees as follows **126**  
A Fir 10" dia. bears S.75°E., 20.3 ft.  
A White Oak 24" dia. bears S.56°30'W., 46.5 ft.

F. C. C. Freer Dep.  
Wit.  
W. S. Hamilton  
W. Dyser  
Oct. 11, 1919

G. C. Stewart  
Oct. 30, 1922  
Wit.  
F. Scott  
A. Conn  
G. Kaiser  
Wit.

J. W. Cole  
Co. Sur.  
Wit.  
G. W. Finley  
Harry Brown

J. W. Cole  
Mr. Vashow  
Apr. 28, 1924

G. C. Stewart  
Geo. Cooper  
and son  
Oct. 24, 1924

Ben B. Irvine  
Wit.  
N. E. Richardson  
Alvin Anderson  
Nov. 19-21, 1929

H. I. Eppstein  
Wit.  
B. Lane  
Bob Mathews  
Fritzpatrick  
Pros.  
June 1930