

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 7 W. R. W. W. M.

N. E. Corner D. L. C. No. 43.

Found - Witness Corner (Brass Cap) & Both BT's. as recorded, *Cor. #51*
Note - These BT's. are to be removed. *& Coc. #116*

New BT's: 20" W. Oak bears S.23°W. 68.5 ft. scribed W. C. Cl. NE 43 CSBT.
8" W. Oak bears S.18°E. 57.0 ft. scribed W.C. Cl. NE 43 CS BT.

Byron &
Crew
8/8/62
C.S. File
No. 49/79

1/4 Corner to Sec. 6, T27-6 and Sec. 1, T27-7W.

Found - Original Bearing Tree and

Set - 1 1/4" Iron Pipe for Corner

Marked the following trees:

W. Oak 10" diam. bears S.67 1/2°E. 43.1 ft.
W. Oak 30" Diam. bears S.56°W. 22.5 feet.

B. B. Stewart,
Deputy
May 17,
1922
Wit: Sindh
Johnson &
Littrel

Initial Point "Town of Melrose" and

True Corner for N. E. Corner D. L. C. No. 43.

See Vol. 5, Page 18, Plat Books & Renewals No. 136, 116, & 51.

Diligent search of area failed to recover any trace of

2" Iron Pipe, the Original Monument. It is presumed to have been
destroyed in road construction.

Monument replaced by Intersection of distances, as shown on
map of survey by Lecklider, M 20-33, and from our notes on tie to
said initial point from Brass Cap, Wit. Corner to N.E. Cor. DLC #43,
See C. S. File No. 49/79.

Initial Point re-monumented by 3/4" reinforcing rod driven in
asphalt pavement on approximate center line of "Orchard Lane",
Co. Road No. 253.

Witness Points: C.S. Brass Cap (Wit. Cor. to N.E. Cor. DLC #43)
bears S.48°26'E. 40.75 feet.

Aluminum cap on Steel Tube, (Survey Point
set by Lecklider), bears S.0°31'E. 30.0 feet.

SEE RM 1-24

Milo E. Godfrey, Deputy
Wm. Stoffel & Mike Stone
Feb. 21, 1964
C. S. File No. 49/79

Sec. Cor. to Secs. 3 & 4, T27-7W. &

Secs. 33 & 34, T26-7W.

Found - 18" Dead, White Oak, old BT., N.47°W. 52.8 feet.

9" White Oak N.37 1/2°E. 129.5 ft., scars very plain.

1960 BT. (See Ren. #112)

3-Way Fence Corner S.64 1/2°W. 18 ft., fences E-W. & N.

Brass Cap, which had been taken out & thrown in to
the brush. Set both caps at cor., old cap buried.

Set - Brass Cap at Cor. Mkd: County Surveyor's T26S S33/S34
Office, 1964 T27S S4/S3 R7W

New BT: 4" Madrone S.48 1/2°E. 86.1 ft. Mkd: S 3 CS BT.

Milo E. Godfrey & Crew
Nov. 17, 1964
C. S. File No. 52/87

Center of Section 31.

Set - Drift Bolt 1" x 18", from which:

Witness Trees: 5" W. Oak N. 29° W. 20.5 feet.

5" W. Oak S. 44 1/2° W. 9.0 feet.

N. E. Corner Section 6. T28-7

Set - Std. Gov't. Pipe

Witness Trees: 24" Red Fir S. 47° W. 56.3 ft.

5" B. Oak S. 72° W. 26.0 ft.

N. W. Corner Section 6, R7W. T28

Fnd. O.K. H. STOCKHOFF
M 87-69

Set - Std. Gov't. Pipe.

Witness Trees: 10" W. Oak S. 41° 30' E. 112.0 ft.

15" Fir S. 80° 30' E. 71.1 ft.

N. E. Corner Section 6, R7 1/2 W.

Set - Std. Gov't. Pipe.

Witness Trees: 24" Red Fir S. 23° W. 30.0 ft.

12" Red Fir S. 63° W. 20.0 ft.

136

137

138

139

140

141

142

143

H. L. Epstein, Co. Surveyor
Map Subd. of Section 31
June 30, 1950
C.S. File No. 14/14 M 1 - 73