

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHARMAN CO., EUGENE, ORE. 21881

H.L. Eppstein,  
Co. Surv.  
June, 1930  
M 1 - 73

N. W. Corner Section 6, R7 $\frac{1}{2}$ W.  
Set - Std. Gov't. Pipe.  
Witness Trees: 24" Red Fir S. 30° 30' E. 32.8 feet.  
30" Red Fir S. 11° W. 29.5 feet.

**RE-NEWED, SEE CORNER NO. #201**

144

John M.  
Powell &  
Crew  
Dec. 21,  
1965  
C.S. File  
No. 49/79

S. W. Corner D. L. C. No. 41.  
Found - Stone Set at Fence Corner.  
18", now 37" E. Oak, now dead snag, N. 66 $\frac{1}{2}$ ° E. 124.1 ft.  
Opened this tree for scribe "B".  
Set - Brass Cap at D.L.C. Cor. Alongside Stone Mkd:  
County Surveyor's Office, 1965  
T27S R 7 W  
S.W. Cor. /  
D.L.C.#41  
New BT: 6" D.Fir S. 62° E. 18.2 ft. scribed DLC CS BT.

*Fd. by: Shanar  
Jan. 1984  
M 96-44 A & B*

145

Don E.  
Garrett  
For H. Reed  
M 22 - 76

N. W. Corner D. L. C. No. 52.  
Found - Set Stone - See Ren. #31.  
Fir Bearing Tree, now Stump, scribed "BT".  
New BT: 12" Fir bears N. 83° E. 12.5 ft. scribed CL 52 BT.  
9" Fir bears S. 39° E. 26.7 ft. scribed CL 52 BT.

Jan. 6, 1966

146

Vernon "Ray" Tracy  
Mike Stone & Jack Heritage  
March 1966  
C. S. File No. 54/23

Wit. Cor. to Sec. Cor. to Secs. 35 & 36, T26-7W.  
and Secs. 2 & 1, T27-7W.  
Found - Iron Pipes used as references, See Ren. #44, T27-7W.  
1" I. P. N. 58° E. 26.8 ft. : : 1" I. P. S. 51° E. 29.0 ft.  
Do not find I. P. set for corner now I.P. referenced N.W.  
Corner falls in Road.  
12", now 24", D. Fir S. 40° W. 81.0 ft., recorded as W. Fir,  
we chop out "BT".  
Set - Wit. Cor. 23.0 ft. E. of true corner. Wit. Cor.  
Brass Cap Mkd: County Surveyor's R7W T26S S 35 | S 36  
Office, 1966 T27S S 2 | S 1  
23 ft. W. to Corner.  
New BT's: 8" Cedar N. 42° W. 56.0 ft. Mkd: W.C. T26S R7W S35 CS BT.  
9" Cedar S. 65° W. 48.2 ft. Mkd: W. C. T27S R7W S 2 CS BT.  
No trees close to East - Use old reference I. P's., as follows:  
1" I.P. N. 1° W. 13.8 ft. and 1" I.P. S. 2° W. 18.6 ft.  
Witness Cor. lies on E. edge of Road, course N. & S. in old N-S Fence.  
March 31, 1966

MICROFILM TO HERE 10/67

147

¼ Corner to Sections 19 and 20.  
Set by Proportional Measurement.  
Set - Brass Cap stamped "¼ Cor. S19, 20 T27S R7W LS 544.  
Bearing Tree: 4" Madrone bears N.69°W. 21.6 ft. scribed "¼ S19 BT".  
16" Cedar bears S.86°15'E. 140.7 ft. scribed "¼ S20 BT".

148

Don E. Garrett  
For Hayward Reed  
January 1, 1968  
Map File M 33 - 27

Section Corner to Sections 17 - 18 - 19 - 20.  
Found - Remains of O. BT. stump S.82°E. 400 lks.  
Set - Brass Cap stamped " 17,18,19 & 20, T27S R7W LS 544".  
Scribed BT's: 6" Madrone bears N. 67° W. 39.0 ft. scribed S18 T27 R7 BT.  
11" D. Fir bears S. 66°15'W. 58.2 ft. scribed S19 T27S R7W BT.  
8" D. Fir bears S.76°E. 54.9 ft. scribed S20 T27 R7 BT.

149

Wit. Corner to Sections 20 - 21 - 28 - 29.  
Found - Ash Clump in position of O.B.T. S. 66° W. 366 lks.  
Set - Brass Cap stamped "W.C. Sec. 20,21,28 & 29, T27S R7W, 14.57 ft. East  
to Cor. LS 544".  
Scribed BT: 8" Ash bears N.80°W. 177.8 ft. scribed WC S20 T27S R7W BT.

150