

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 7 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 91881

FD OK 5/92 D. BENTZ 1992-48

151

$\frac{1}{4}$ Corner to Sections 28 and 29.
Found - O.B.T. 36" Oak bears S. 2° E. 110.22 ft., face rotted out.
O.B.T. 12" W. Oak bears S. 47° E. 9.6 ft., scribing partly visible,
(no record)
Set - Brass Cap stamped " $\frac{1}{4}$ Cor. 28, 29 T27S R7W LS 544".
Bearing Trees: 12" W. Oak bears S. 64° 45' W. 25.4 ft. scribed $\frac{1}{4}$ S29 BT.
14" W. Oak bears N. 19° 30' E. 22.8 ft. scribed $\frac{1}{4}$ S28 BT.

Don E. Garrett
For: Reed
Map File
M 33 - 27

Jan. 1, 1968

152

N.W. Corner D. L. C. No. 38.
Found - No trace of Plow Point as recorded in Vol. 2, Pg. 7. *Rev. #13*
9" Laurel, now fragmentized, S. 25° E. 64.0 ft., scribe found.
16", now 23" B. Oak, S. 74 $\frac{1}{2}$ ° E. 105.6 ft., tree previously
opened, scribe visible.
Set - Brass Cap at N.W. Cor. DLC #38. County Surveyor's Office
T 27 S R 7 W
N.W. Cor
1968 DLC 38
New BT: 14" B. Oak S. 28° E. 85.6 ft. mkd. N.W. DLC #38 CS BT.
S.E. BT. O.K. and tagged.

John M. Powell &
F. Jones
Feb. 1, 1968
C.S. File No. 49/79

FD O.K.
by G. Grubb
Mar. 1982
M 91-62

153

$\frac{1}{4}$ Corner to Sec. 13, T27-7W. & Sec. 18, T27-6W.
Set by proportional measurement.
Set - Brass Cap for $\frac{1}{4}$ Cor. Stamped: LS 544 $\frac{1}{4}$ S 13 | S 18
Feb. 1968 R7W R6W
Scribed: 18" Oak bears N. 12 $\frac{1}{2}$ ° W. 181.2 ft. scribed $\frac{1}{4}$ S13 BT.
12" Oak bears N. 87° E. 55.0 ft. scribed $\frac{1}{4}$ S18 BT.

Don E. Garrett
For: Wulff
C.S. 55/62
M 35 - 44

FD OK
R. Dolan
M 96-70

2/3/68

154

$\frac{1}{4}$ Corner to Sections 15 and 22.
Found - County Surveyor's Brass Cap, properly mkd. in 1954, *Ren. #53*.
10" Fir, now low cut stump, S. 47° W. 20.9 ft., scribe visible.
12", now 14" Laurel, alive, N. 3° W. 29.8 ft., scribe visible
on unhealed blaze.
New BT: 18" B. Oak S. 23° W. 48.1 ft. mkd: " $\frac{1}{4}$ S22 CS BT.
Note - Brass Cap is now set in concrete with fence corner post,
fences E. and N. Power & Telephone lines directly overhead.

SEPT 68

Vernon "Ray" Tracy
Jack Heritage & V. Perron
September, 1968
C. S. File No. 54/23

FD OK
by Quimby
May 1984
M 96-55

155

Section Corner to Sections 14 - 15 - 22 - 23.
Found - 1954 County Surveyor Brass Cap in place, See *Ren. #52*.
10", now 14" Fir, recently sawed down, N. 85° E. 31.0 ft.,
shows scar.
10", now 10" Fir sawed stump, S. 24° E. 32.3 ft. (Rec. 33.3'),
"BT" scribe visible on unhealed blaze.
8", now 13" Fir, now down, N. 42° W. 25.0 ft., shows scar.
10", now 10" Fir sawed stump, S. 72° 30' W. 46.6 ft. scribe
visible on unhealed blaze.
New BT's: 7" D. Fir N. 30° E. 31.8 ft. mkd: T27S R7W S14 CS BT.
10" D. Fir N. 62° W. 22.6 ft. mkd: T27S R7W S15 CS BT.
8" D. Fir S. 32° W. 35.9 ft. mkd: T27S R7W S22 CS BT.
9" D. Fir S. 11° E. 28.5 ft. mkd: T27S R7W S23 CS BT.

FD OK
M. Rump
M 107-79

This corner lies on gentle westerly slope approx. 200 ft. west
of power line road.

9/18/68

156

$\frac{1}{4}$ Corner to Sec. 24, T27-7W. and Sec. 19, T27-6W.
Found - Rock for $\frac{1}{4}$ Corner, as of Hicks' Survey, 1914, See M 33 - 41.
New Witness Trees: 8" W. Oak N. 60° W. 13 ft.
8" W. Oak East 10.8 ft.

Herbert L. Northcraft
For: Les Black
RM 1 - 70

June, 1968

157

$\frac{1}{4}$ Corner to Sections 13 and 14.
Found - Oak Stump/or Orig. Tree N. 58° W.
Maple with Blaze and Remains of N. 58° E. Tree in evidence.
Reset $\frac{1}{4}$ Corner a/c to Hicks' Survey, 1914, See M 33 - 41.
Set - Brass Cap Mkd:
New BT's: 12" Fir N. 16 $\frac{1}{2}$ ° E. 55.3 ft. mkd: $\frac{1}{4}$ S 13 T27S R7W BT 750
8" W. Oak S. 32 3/4° E. 39.7 ft. mkd: $\frac{1}{4}$ S 13 T27SR7W BT 750.

Herbert L. Northcraft
Sept. 1968
For Sheppard & Phillips
M 33 - 44

See Also Map 52