

Douglas County Surveyor's Record of
Government Corners Renewed

T. 27 S. T. S. R. 7 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

Vernon "Ray"
Tracy &
Crew
C. S. File
No.
54/23

Vernon "Ray" Tracy
J. Heritage & V. Perron
5-27-69 C.S. File 54/89
M 38 - 5

John M. Powell
Frank Jones & W. Penley
C.S. File No. 54/23

Int. "L" D, L. C. No. 48.
Found - Orig. 10", now 20" W. Oak, alive, S. 27 $\frac{1}{2}$ °W. 36.3 ft., prev.
opened, scribe marks in very poor condition, visible, Ren. #4
Find hole for Hick's N.W. BT. & no trace of N.E. BT. due to road.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T 27 S R 7 W
Int. L. DLC 48
New BT's: 10" D. Fir N. 33 $\frac{1}{2}$ °W. 69.9 ft. mkd: "Int. L DLC 48 CS BT.
8" D. Fir S. 43°W. 54.0 ft. mkd: "Int. L DLC 48 CS BT.
This corner lies 60 ft. E. of Co. Rd., course NE - SW., See M 33 - 41.
12/6/68

158

$\frac{1}{4}$ Corner to Section 24 and Section 25.
Found - stumps of O.B.T.s as follows:
Orig. 12" now 28" B. oak N. 30°W. 25 Ft. Badly decayed - no scribe fd.) Ren.
Orig. 24" now 38" B. Oak S. 38°W. 43.6 Ft. Badly decayed - no scribe fd.) #8
Bearings & distances fit orig. field notes: At Cor. point
Set - 1" I.P. & Brass Cap Mkd:
County Surveyor's Office, 1969 T. 27 S R 7 W
 $\frac{1}{4}$ S24 S25
This corner lies at fence Cor. - fences N. - W. & E. Mk. new B.T.s
13" D. Fir N. 60°E. 36.2 Ft. Mkd. $\frac{1}{4}$ S24 CS BT
18" D. Fir S. 12°E 7.1 Ft. Mkd. $\frac{1}{4}$ S25 CS BT 5-27-69

159

WITNESS CORNER FILE
Section Corner to Sections 9 - 10 - 15 - 16.
Found - Orig. 15", now 27" W. Oak, N. 20°E. 55.4 ft., shows good scar.
1960 C.S. Brass Cap, this corner to fall in road due to new
(Ren. #81) construction. Remove Brass Cap & Reset for Wit. Corner.
21", now 23" D. Fir, N. 54°W. 82.6 ft., shows good scar.
15", now 18" D. Fir S. 61°E. 125.5 ft., shows good scar.
Reset Brass Cap for Wit. Cor. Mkd: County Surveyor's Office W.C. 25 ft. T 27 S R 7 W
1969 South to S 9 | S 10 S 16 | S 15
Reblaze & Rescribe: 27" W. Oak N. 41 $\frac{1}{2}$ °E. 33.3 ft. mkd: W.C. T27SR7W S10 CS BT.
23" D. Fir N. 71°W. 69.7 ft. mkd: W.C. T27SR7W S 9 CS BT.
18" D. Fir S. 53°E. 140.8 ft. mkd: W.C. T27SR7W S15 CS BT.
5/8" R/W Pin S. 57°E. 18.2 ft. Str. 217+00.
12/9/69

160

WITNESS CORNER FILE
Section Corner to Sections 15 - 16 - 21 - 22.
Found - 1954 Brass Cap 6" under surface of road, See Ren. 54.
14", now 17" B. Oak, S. 39°W. 50.0 ft., some scribe marks visible.
10", now 12" B. Oak, N. 17 $\frac{1}{2}$ °W. 85.8 ft., some scribe marks visible.
16" B. Oak, Stump N. 30°E. 80.5 ft., opened for scribe.
(This tree will be in road)
Reset Brass Cap for Wit. Cor. Mkd: County Surveyor's Office W.C. 32' T 27 S R 7 W
1954 to East. S 16 | S 15 S 21 | S 22
New BT's: 15" W. Oak N. 45°E. 115.4 ft. mkd: W.C. T27SR7W S15 CS BT.
8" W. Oak N. 4°W. 14.6 ft. mkd: W.C. T27S R7WS16 CS BT.
8" D. Fir S. 14 $\frac{1}{2}$ °W. 20.2 ft. mkd: W.C. T27SR7W S21 CS BT.
This Witness Corner lies in N. - S. Fence Line.
12/9/69

161

$\frac{1}{4}$ Corner to Sections 35 and 36.
Found - 1 $\frac{1}{2}$ " x 1" I. Bar S. 79°E. 30.7 ft., See Ren. #41.
 $\frac{1}{2}$ " Iron Rod with 1" Cap, 10" underground in center of County Road.
34" Locust, now stump, N. 59 $\frac{1}{2}$ °E. 30.1 ft.
30" Locust, now stump, S. 83°E. 25.8 ft.
Set - Brass Cap for Wit. Cor. flush with ground, marked:
County Surveyor's Office W.C. 60 ft. E. to Cor. T 27 S R 7 W
1969 S 35/ S 36
New BT: 20" Maple S. 69°E. 175.30 ft. mkd: "W.C. $\frac{1}{4}$ S36 CS BT".
Bearing Objects: 3/4" I. Rod S. 79°W. 133.1 ft. at base of Tele. Pole 2-94B.
1" x 1 $\frac{1}{4}$ " I. Bar S. 88°E. 90.1 ft., near S.W. Cor. Lookingglass Store
Northerly corner of House S. 20°E. 6.8 ft.
12/9/69

162

175