

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

184

SW Corner DLC #44 (Sec. 2)
Found - 1" I.P. 6" below surface of graveled road. (pipe set per C.S. 45/86)
Stump hole of orig. 24" Oak bears N.80°E., 159.1 ft.
A 14" R. Fir now a stump bears N.44 1/2°E., 27.9 ft. to face.
Bottom of healed blaze remains on low cut stump. Ren. #72
No other BT's found.

I DO NOT SET NEW MONUMENT. New Accessories:
1. On a bearing of N.49 1/2°E., a 5/8" I. Rod 54.32 ft., A 5/8" I. Rod 85.07 ft. and a PK nail in a 6" Oak 104.32 ft. (Set by Powell, 1973 reference).
2. A D. Fir 10" bears N.69°E., 100.0 ft. Tree double blazed & scribed "SW C1 44 CS BT".

13/77

185

NNW Corner DLC #43
Found - Orig. 10" White Oak now a rotted stump, face split away, no scribing found. Stump bears S.63 1/2°E., 43.6 ft. Ren. #20
A White Oak 16" now down and rotted bears S.35°E., 50.2 ft.
A White Oak 6" now 8" bears S.59°E., 75.6 ft. (Rec. S.60°E.)
Tree has well healed blaze. Ren. #71
Set - 5/8" x 30 1/2" I. Rod at NNW corner DLC #43. Rod set 7" below surface of graveled road.
See attached narrative in C.S. 59/31.

3/3/77

186

Section corner to sections 10, 11, 14, and 15.
Found - Brass cap as per Ren. #86.
Orig. 36 in. diam., bears S. 22° E., 192.1 ft. (Record, S. 18° E.)
This Oak stump has opened blaze, no visible scribing.
Orig. 22 in. ash with rotted out blaze bears N. 61° E., 362.0 ft. (Rec. N. 63° E., 363.0 ft.)
A 8 in. now 10 in. diam., W. oak, bears N. 88° E., (Rec. N. 86° E.) 179.0 ft. with well healed single blaze.
A 12", now 15" diam., W. Oak bears S. 45° E., 148.3 ft. (Rec. S. 46 1/2° E., 147.6 ft.) with well healed single blaze.
An 8" now 13" diam., fir stump bears S. 3 1/2° W. (Rec. S 2 1/2° W) 299.5 ft. with possible bottom of blaze showing.
Set. - Reset brass cap described in Ren. #86 with "Reset 1977" stamped above 1960, 1.0 ft. below ground.
New BT's An 8" diam., ash bears S. 31 1/2° W., 350.3 ft. double blazed and scribed "T27S R7W S15 CS BT".
New BO A 5/8" x 30" rebar with alum.cap stamped "BO 1" bears N. 24 1/2° E., 136.0 ft. in fence line, N. 70° W. 148.5 ft. from fence corner.
Note: Set survey marker sign on steel fence post 1.0 ft. south of brass cap
Found 3" x 6' wooden post 2.0 ft. east of brass cap, painted orange and white.

Larry E. Monrean, Doug. Co. Surveyors Off.
Steve Flouse
March 3, 1977
C.S. 59/31

Rod Kimberling
Peter Earle
Mike Cline
CS 59/40
9-1-77
DCSO

9-1-77

187

S.W. Corner DLC #48 (Sec. 24)
Found - Stone monument. See Ren. #6
New BT- 14" Alder bears S.64°E., 34.3 ft. scribed PC BT. S.B.
PEAR TREE PER: E. KIMBERLING - DOUG. CO. SURVEYORS 1978 2/13/78

Glenn Baughman
Surveying Co.
Feb. 13, 1978
C.S. 58/153
#1168-63

S.W. Interior Corner DLC #48. (Sec. 24)
Found - Stone monument - See Ren. #6
New BT's - 7 1/2" D. Fir bears N.40°E., 7.6 ft. scribed PC BT.
1 1/2" D. Fir bears S.k8°E., 34.9 ft. scribed S.B.
VOID *Not DLC* *See Ren. #6* *PER: M33-41* *2/13/78*

188

2/13/78

189

1/4 Corner for Sec. 1 and Sec. 6 of T27-6
Found - A 1 1/4" I.P. bent over, 3" above ground bears S.58°E., 1.2 ft. with a 1"x26" hollow drill rod at the south edge, set 6" below ground.
A 13" now 42" W. Oak (OBT) bears S.52 3/4°W., 23.1 ft. with a well healed blaze.
A 10" now 26" W. Oak bears S.65°E., 44.7 ft. (Rec. S.67 1/2°E., 43.1 ft.) with a well healed double blaze. Ren. #137 (Lower part of upper blaze is rotted)
Set - A 1"x36" I.P. with a brass cap set 4" above ground marked: "Douglas County Surveyor"

R. B. Kimberling
P. L. Earle
Douglas Co. Surveyor
Office
March 23, 1978
C.S. 59/46

R T 27 S R
7 S 1 S 6 R
W 1/4 W

No new accessories. Corner is 40 ft. South of Orchard Lane, 1 ft. North of an East-West fence. 16 ft. West of a fence to the South. 3/23/78

RE-RENEWED SEE CORNER NO. ONLY