

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27 T. S. R 7 R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 31881

190

R. B. Kimberling
P.L. Earle
F.C. Silagy
Doug. Co. Surveyors
Office
April 18, 1978
C.S. 59/46

S. E. Exterior corner for DLC #48
Found - A 1" Iron rod at S.E wire fence corner, bears S.77°W., 1.9 ft. from corner.
A 30" Pine stump, badly rotted bears N.42 1/2°W., (Rec. N.46°W) 68.5 ft. (M 33 - 41)
A 8" now 23" W. Oak, (Measured below fork) bears N.79 1/2°W., 30.1 ft. with "CSC 48" carved in a partly healed single blaze.
A 10" Locust (measured South fork) bears N.26°E., 4.9 ft. with "SC 48 B" carved in a partly healed single blaze. Ren. #43
Set - I Set a 1" x 36" Iron pipe with a brass cap set 5" above ground and marked "Douglas County Surveyor" T 27 S R 7 W
1978 S.E. Ext
DLC 48

No new accessories.

4/18/78

1-79

Stephen Flause
Doug. Co. Surveyors
Office
Mr. Shawn Means
Karen Reed - Deputy
March 26, 1980
C.S. 61/6

1/4 Corner for Secs. 22 and 23. **191**
Found - A 1960 County brass cap properly stamped lying next to a N-S fence. Ren. #89
No original bearing trees found.
A 6" W. Oak now 7" bears N.83°W., 42.0 ft. with a well healed double blaze. Ren. #89
An 18" P. Pine now 21" bears N.44°E., 46.0 ft. with well healed double blaze. Ren. #89
Re-set - monument at record bearing and distances from bearing trees per Ren. #89. Stamped "Reset 1980" on cap. Placed a mound of stone around cap. Cap is 1 ft. east of a N-S fence.
New BT's - A 14" Madrone (diam. measured at trunk below double trunk) bark scribed "1/4 S23 CS BT", bears S.41°E., 45.6 ft.
A 5" trunk of a madrone having double trunks, (this trunk being the most northerly) barked scribed "1/4 S22 CS BT" bears S.46°W. 61.5 ft. (bearing taken to center of base.).

3/26/80

Larry E. Monrean, Deputy
Doug. Co. Surveyors
Office
K. Reed - K. Mosely
April 29, 1980
C.S. 61/6

1/4 Corner for Sect-ions 27 and 28. **192**
Found - A 1" x 36" I.P. with 1954 County brass cap properly marked protruding 0.8 ft. above ground. Ren. #56
An orig. 12" B. Oak now a 22", 2 ft. high stump bears S.34°E., 42.2 ft. (Rec. S.32°E., 41.6 ft.) The dist. 41.6 ft. is face measurement. We open stump to find old axe marks and orig. scribing "BT".
An orig. 12" B. Oak, now a rotted stump of indeterminate size bears N.60°W., 73.9 ft. (Rec. N.62°W.)
A 10" Fir, now a 17", 1 ft. high stump, bears S.18 1/2°W., 20.6 ft. (Rec. S.17°W.)
A 10" Fir, now tipped out with visible scribe "1/4 S27" (Rec. 1/4 S28) roothole bears S.56 1/2°E., 62.0 ft. (Rec. S.54°E.)
Left cap in position.

New Accessories:

A 10" Fir scribed "1/4 S27 CS BT" in a double blaze bears S.7°E., 56.3 ft.
A 7" Fir, scribed "1/4 S27 CS BT" in a double blaze bears N.43 1/2°E., 4.4 ft..
An 8" Fir scribed "1/4 S28 CS BT" in a double blaze bears N.41°W., 9.7 ft.
A 9" Fir scribed "1/4 S28 CS BT" in a double blaze bears S.40 1/2°W., 25.3 ft.

4/29/80

193

Robert L. Dolan LS#1076
For: Jesse Charles
May 1980
M 83 - 69

Section corner for Sections 8,9,16 and 17
Set - A brass cap.
BT'S- 10" Douglas Fir bears N.61°18'W., 30.8 ft. scribed "T27S, R7W, S8, BT".
11" Douglas Fir bears N.14°30'E, 26.7 ft. scribed "T27S, R7W, S9, BT".
8" Douglas Fir bears S31°02'E, 38.3 ft. scribed "T27S, R7W, S16 BT".
13" Douglas Fir bears S.14°18'W, 20.3 ft. scribed "T27S, R7W, S17, BT".

Note - Section corner set by double proportionate measurement.

6/4/80