

Douglas County Surveyor's Record of
Government Corners Renewed

T 27

T. S.

R 7

R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 9181

205

FD. OK 10/90
1990-0065
FD. OK 11/91
M. HEMOURSER M/M-5

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Jan. 4, 1990
C.S. 64/5

1/4 Corner for Section 1; and Section 6 of T.27-6
Found - 1978 County 2 1/2" dia. brass cap on a 1 1/2" O.D. iron pipe that protrudes 3" above ground. Ren. #189
A 1 1/2" O.D. iron pipe, that protrudes 3" above ground (Per Ren.#137)
1 1/2" O.D. IP bears S.58°E., 1.2 ft. from DCSO BC/IP (agrees with Ren. #189)
1" hollow drill rod noted in Ren. #189 as being 6" below ground along south edge of 1 1/2" O.D. iron pipe not looked for
13" now 44" dia. W. oak with a fully healed blaze bears S.52 3/4°W., 23.1 ft. (agrees with Ren. #189, and agrees with original notes of 13" SW BT) Orig. BT.
Orig. 12" W. oak bearing S.51°E 55.4 ft. is gone.
10" now 27" dia. W. oak with a partially healed blaze no scribing visible, bears S.66 3/4°E., 44.7 ft. (Rec. S.65°E., 44.7 ft. from Ren. #189) Bt per Ren. #137.
New BTs - 8" Ash double blazed and scribed "1/4 S6 CS BT: bears S. 36 1/2° E., 13.0 ft.
8" Ash double blazed and scribed "1/4 S1 CS BT" bears S.6°W., 13.8 ft.
Corner lies at the intersections of an East-West and South running fence lines.

1/4/90

206

Douglas County
Surveyors Office
S. J. Flause
T. Frnassen
April 6, 1990
C.S. 64/6

1/4 Corner for Sections 4 and 5
Found - A DCSO 2 1/2" dia. brass cap, properly stamped, on a 1 3/8" O.D. I.P. firmly set and protruding 7" above ground. Ren. #165
No evidence of orig. corner monuments called for in Ren. #s 40,50 is found.
No evidence of references to orig. corner or references to Renewals #40 and 50 is found.
From Ren. #165, three references are found:
A 6" D. fir now a dead 14" DBH D. fir with a fully healed double blaze bears S.01°W., 99.6 ft. (as per rec.) This tree was cut down immediately after measurement of B & D was made. Stump will be removed in near future.
A 4" +, with a deeply depressed center point, marked high on North face of an 8 ft. tall x 20 x 7 ft. solitary sandstone rock which bears S. 1/2°E., 179.1 ft. (Rec. South 179.1 ft.)
A 1/2" 5/8" iron rod now a 5/8" dia. I.R. firmly set and protruding 6" above ground bears N.50 1/2°E., 35.1 ft. (as per record)
No evidence of Garrett's iron rod (CS 55/138 is found.
This area has been disturbed by grading work.
New BTs - A 16" DBH D. fir scribed "1/4 S5 CS BT" on a double blaze, bears S.42°W., 76.7 ft. distant.
A 7" DBH D. fir scribed "1/4 S5 CS BT" on a double blaze bears N.29°W., 90.9 ft. distant.
On small bench on lower slope of the east face of the Callahan ridge.

4/6/90