

Douglas County Surveyor's Record of  
Government Corners Renewed

27 T. S. 7 R. W. W. M.

H. L. Eppstein Co. Sur.  
Witness  
B. A. Lane  
Bob Mathews  
Fritzpatrick Bros.  
June 1930

H. L. Eppstein  
N. E. Richardson  
N. C. Conn  
witnesses  
February 1929

- ✓ 1/4 CORNER BETWEEN SECTIONS 30 and 31. **SEE CORNER NO. 61** 23  
 I set a Cedar Post 4 x 4 x 36" in ground where old C.S. Post was, marking the following witness trees  
 White Oak 16" dia. bears S.47°15'W., 65 ft.  
 White Oak 12" dia. bears S.89°E., 135 ft.
- ✓ 1/4 CORNER ON WEST LINE OF SECTION 31. 24  
 Set 1 x 18" drift bolt for corner from two old B.T.s.  
 I marked two new witness trees as follows  
 Fir 10" dia. bears N.35°W., 27.0 ft.  
 Fir 12" dia. bears S.67°E., 26.2 ft.
- ✓ S.W. CORNER OF D.I.C. # 54. 25  
 I set from old B.T. Set 4 x 4 x 36" Cedar post for corner and marked for new witness tree  
 A White Oak 10" dia. bears N.55°E., 28.5 ft.
- ✓ SECTION CORNER OF 30 and 31. **SEE CORNER NO. 62** 26  
 Set Corner from three old witness trees. I set 4 x 4 x 36" Yew wood Post for corner. The three old witness trees being in good shape, I only marked new B.T. in section 30 as follows  
 Red Fir 20" dia. bears N.28°E., 45.0 ft.
- ✓ SECTION CORNER OF 36 and 31. 27  
 Set corner from old B.T., where I found remains of rotten post. For corner I set 1 x 18" Drift Bolt. Marked new B.T.s as follows  
 Fir 12" dia. bears N.5°W., 9 ft.  
 Fir 10" dia. bears S.88°E., 24.5 ft.
- ✓ SECTION CORNER OF 31 and 32. 28  
 Government Standard in place. Set by Minch U.S. Surveyor. Witness trees as follows  
 Fir 48" dia. bears N.2°E., 52.2 ft.  
 Chincapin 5" dia. bears N.34°W., 21 ft. cut down.  
 I marked the following tree.  
 Fir 48" dia. bears N.48°30'W., 46 ft.
- ✓ 1/4 CORNER BETWEEN SECTIONS 31 and 32. **SEE CORNER NO. #60 + 79** 29  
 This corner was lost, so I ran line from section corner of 31 and 32 north to section corner of 30, 31, 29, 32 and then set 1/4 corner by proportional distance between. Set post in field and marked as new B.T.s the following trees  
 A White Oak 10" in dia. bears S.4°E., 197.2 ft.  
 O. C. P. CO. Power Pole 2/18 S.34°W., 223.6 ft.
- ✓ SECTION CORNER BETWEEN SECTIONS 30, 29, 31, and 32 30  
 Set from two old B.T.s in section 30 and 29. I set a 4 x 4 x 30" Cedar Post for corner. Marking new B.T.s as follows  
 White Oak 10" dia. bears N.43°E., 54.5 ft.  
 White Oak 10" dia. bears S.60°W., 44 ft.
- ✓ N.W. CORNER OF CL. 52. 31  
 Set corner from old Oak B.T. scribe marks. Set 6 x 11 x 30" sandstone and 1x7" Pipe for corner. Marked new B.T. as follows  
 Fir 16" dia. bears S.50°E., 177 lks.
- ✓ S.E. CORNER OF CLAIM 53. 32  
 Corner gone but replaced from N.W. Corner of Claim 53 and S.E. Corner of Claim 52. Set Post and marked new witness trees as follows  
 White Oak 12" dia. bears S.58°W., 176 lks.
- ✓ S.W. CORNER OF CLAIM 52. 33  
 Corner gone but replaced from N.W. Cor. of Cl. 53 and S.E. cor. of 52. Set 2 x 18" galv. Iron Pipe and marked  
 Fir 12" dia. bears N.8°E., 23 lks. marked C.S. Cl. 52 B.T.