

Douglas County Surveyor's Record of  
Government Corners Renewed

27 T. S. 7 R. W. W. M.

34

✓ N.W. CORNER OF CLAIM 53.  
Set a 3 x 3 x 4" Laurel Post from old B.T. on Oak, for  
new B.T.s I marked the following tree  
Fir 10" dia. bears S.43°E., 23 lks. 67

35

INTERIOR "L" CORNER OF CLAIM 52.  
Set post from old White Oak B.T. and marked the following  
new B.T.  
Fir 10" dia. bears S.80°E., 46 lks. marked C.S. Cl. 52  
1.27 S. R. 7 W. B.T.

36

✓ S.E. CORNER OF CLAIM # 52.  
Set 2 x 18" Iron Pipe for corner by running in from N.W.  
corner of claim 53 East and Interior "L" Corner of claim  
52 and running South intersected I set corner. I marked the  
following tree  
Fir 14" dia. bears N.55°W., 48 lks. marked C.S. Cl. 52  
B.T.

37

✓ S.W. CORNER OF J. P. BOYER D.L.C. NO. 51  
Bearing of S.W. corner tree of Boyer Cl.  
Black Oak 18" dia. bears N.61½°W., 25 lks.

38

✓ CORNER BETWEEN 12 and 7 ON EAST SIDE OF TOWNSHIP  
Reset by running through to section corner. I marked  
the following trees  
A Black Oak 18" dia. bears N.33°15'W., 25½ links 102  
A Black Oak 30" dia. bears S.40°15'E., 20½ links

39

✓ SECTION CORNER BETWEEN 32, 33, 4 and 5. N. LINE(?)  
Set a 2 x 30" Iron Pipe from old B.T.s, They were in  
food shape. Remarkd Same  
Fir 15" dia. bears N.75°E., 18 lks. DEC. 1960 - FD. BRASS CAP  
Fir 15" dia. bears N.67°W., 45 lks. SET BY B.L.M. 1959  
Fir 18" dia. bears S.89°E., 90 lks. 163  
Fir 24" dia. bears S.23°W., 75 lks.

40

✓ CORNER BETWEEN 5 and 4  
Set 4 x 4 x 30" Fir stake. Otto Matthews set 2 x 30"  
Iron Pipe from 30" White Oak down but scribe marks still  
visible. Marked new Bearing Trees as follows  
Fir 24" dia. bears N.86°E., 24 ft.  
Fir 24" dia. bears S.49°E., 22.2 ft.

41

✓ 1/2 CORNER BETWEEN 35 and 36.  
Rock in center of County Road. I marked the following  
trees  
Locust 34" dia. bears N.59½°E., 30.1 ft. marked 162 & 175  
1/4 S. C. S. B.T.  
Locust 30" dia. bears S.83°E., 25.8 ft.  
1 1/4 x 1" bar. S.W. corner Nickens property, S.79°E.,  
30.7 ft.

42

✓ CORNER BETWEEN SECTIONS 4 and 9. Ren # 50c  
Rock (sandstone) 10 x 8" in place. Original Bearing Tree  
badly rotted. Set new Bearing Trees as follows  
Fir 24" dia. bears S.60°W., 18 ft. Blazed and scribed  
S. 9 C.S. B.T. 106  
Fir 18" dia. bears N.17°W., 45 ft. Blazed and scribed  
1/4 S. 4 C.S. B.T.

43

✓ RESET EXTERIOR "L" CORNER OF WM. MORIN D.L.C. NO. 48  
I set the corner by driving a 1 x 36" Iron Pine from which  
the following trees bear  
Forked White Oak 12" dia. bears N.77½°W., 28.6 ft.  
A Locust 10" dia. bears N.40½°E., 5.8 ft. #190

H. L. Eppstein Co. Sur.  
Wit.  
M. E. Richardson  
M. C. Coan  
Feb. 1929  
M. E. Germond  
Mar. 1909

Frank Cain  
July 8, 1910  
FB 55 9/20

M. E. Richardson  
E. A. Lane  
P. D. Wolford  
Otto Matthews  
May 1934

A. Boyer D.C.S.  
Ben Jacoby  
Geo. Morfon  
Jan. 2, 1944

Ben B. Irvine  
Richardson  
Bodie  
Kofan  
Nov. 23, 1934

Tree R  
J. H. Wolford  
I. D. Wolford  
Ceri Richmond  
Oct. 5, 1935

726-7  
32/33  
5/9  
727-1

SEE  
ALSO #  
REN 3