

Douglas County Surveyor's Record of  
Government Corners Renewed

27 T. S. 7 R. W. W. M.

June 2, 1938.  
V. 15, E. 11

Ben B. Irving D.C.S.  
Witnesses  
N. E. Richardson  
N. Conn  
October 10, 1938  
Notes V. 15 E. 11

Ben Irving  
County Surveyor  
Witness:  
N. E. Richardson  
12-20-48

SECTION CORNER BETWEEN 1 and 2, T27S, R 7.W., and 35 & 36, T26S, R7W.  
Renewed corner to sections from the 18" Black Oak S.37°W. 65 lks. in Section 2. Other trees gone. Set 1 1/2" Iron Pipe for corner. Marked new B.T. 44

White Fir 12" dia. bears S.40°W., 81 ft.

No trees in other sections near.

Set 1" pipe N.50°E., 21.8 ft. in section 35 147

Set 1" pipe N.58°E., 26.8 ft. in section 36

Set 1" pipe S.51°E., 29.0 ft. in section 1.

INTERIOR "L" CORNER OF SOBDY D.L.C. # 52 45

Bearing Tree dead. Drove 3/4" x 18" pipe along corner post. Marked the following tree (REN. #35)

Fir 30" dia. bears S.2°W., 61.5 ft. blazed and scribed D.L.C. 52 C.S.B.T.

S.E. CORNER OF D.L.C. # 52. 46

Set 3/4" x 40" pipe 30" in ground in mound of rock 24" in diameter and 12" high. Boulder 30" x 48" x 14" high bears S.65°W., 5 ft. with X and B.O. chisled on surface. Location identified by distance from Interior L Corner and hole where Oak tree had burned out for location of O.B.T.

N.E. CORNER OF D.L.C. # 52 AND N.W. CORNER OF D.L.C. # 51. 47

Sandstone 6" x 14" x 4" above ground has been in place for many years. Original B.T. completely obliterated. Blazed and scribed

A Ash 12" dia. bears North 0.7 ft. marked D.L.C. 52 and D.L.C. 51 C.S. B.T.

12/68 SEARCHED FOR - NOT FOUND V.R.T.

N.E. CORNER OF D.L.C. # 53 48

Drove a 3/4" x 36" Iron Pipe for the corner. Oak 12" dia. bears S.58°W., 17 lks. as set in 1929 by Co. Surv. Eppstein in place and in good shape.

S.W. CORNER OF D.L.C. # 51 49

On East boundary of D.L.C. 52 set by proportional measurement between the N.E. and S.E. corners of D.L.C. 52. Set a 3" x 3" x 24" Sandstone 12" in ground chisled 51 on N.E. face. (REN. #37)

Fir 14" dia. bears N.28°E., 16.6 ft. blazed and scribed S.W. C.51 C.S.B.T.

1/4 COR. BETWEEN 4-5 50

Reset from two old B. T's, stumps. (SEE ALSO REN. #40)

Set an iron pipe for the corner and marked two new B. T's.

18" Fir bears N 63° W 28.6 ft. 165

16" Fir bears N 88° E 29.0 ft.

SEC. COR. 3-4-9-10

Set rock 24 x 12 x 8 by B.T. SEE CORNER NO. 83 50-A

SEC. COR. 4-5-8-9

Set rock 30 x 18 x 10 by B.T. ER NO. # 105 50-B

1/4 COR. 4-9

Set rock 18 x 10 x 6 by the B.T. SEE CORNER NO. 42 50-C

1/4 COR. 10-15

Set rock 24 x 24 x 12 by B.T. SEE CORNER NO. 82 50-D

All by Wm. Thiel July 9, 1884

N.W. COR. DLC 40

Set rock 12 x 12 x 6 RE-RENEWED, SEE CORNER NO. 178 50-E

N.E. COR. DLC 40

Set rock 20 x 12 x 6 RE-RENEWED, SEE CORNER NO. 179 50-F

S.W. COR. DLC 43

Set rock 15 x 12 x 5" 50-G

Wm. Thiel Oct. 6, 1884