

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

64

Section Corner to Sections 19, 20, 29, & 30.

Found - Three of Orig. BT's.

Orig. 20" now 42" B. Oak, old face exposed, good scribing visible "R8W S".

Orig. 24" now 40", S.15°W. 7.9 ft., badly burned Snag, Face gone.

Orig. 20" now 36" Oak Snag S.59°E. 26.4 ft., shows old face rotted.

Also find hole for Orig. N.E. BT.

All BT's check for Bearing & Distance.

Fence Corner bears N.55°W. 48.6 ft.

Set Brass Cap at Corner Marked T27S R7 W County Surveyor's Office, 1958 $\frac{S19}{S30} | \frac{S20}{S29}$

New BT's: 18" R.Fir bears S.62°W. 36.2 ft. scribed T27S R7W S30 CS BT.

10" Laurel " N.25°E. 54.7 ft. scribed T27S R7W S20 CS BT.

42" B. O. (Orig.) N.45°W. 66.0 ft. scribed T27S R7W S19 CS BT.

No live Trees near in S. E. Quad.

65

$\frac{1}{4}$ Section Corner to Sections 19 & 30.

Found - Orig. 15" now 36" Fir Snag N.15°E. 8.0 ft. I open lower Section & find good scribing "BT".

Orig. BT. in S. W. Gone.

Set Brass Cap at Corner Mkd.: $\frac{1}{4}$ $\frac{S19}{S30}$ T27S R7W County Surveyor's Office, 1958

New BT's: 16" Laurel bears N.23°W. 73.7 ft. scribed $\frac{1}{4}$ S19 CS BT.

Chisled "Crow's foot" 4" high & "B.O" 2" high on top

Rock 8' x 2.5" x 3.5' high (near East Edge of Rock)

bears N.18°W. 63.3 ft.

Chisled "Cross & B.O" near Top 12"x 24"x 18" High Rock on

Top Spur S.E. bears S.2°W. 74.3 ft.

66

$\frac{1}{4}$ Section Corner to Section 30 & 29.

Found - Orig. 10", now 14" W.O. I open old scar & find good scribing, "BT". This BT. still partly alive.

Orig. N. W. BT. gone.

Set Brass Cap at Corner marked $\frac{1}{4}$ S30/S29 T27S R7W, County Surveyor's Office, 1958.

N. W. Fence Line is East 9.0 ft.

New BT's.: 14" R.Fir bears N.45°E. 64.2 ft. scribed $\frac{1}{4}$ S29 CS BT.

18" B.O. bears S.32 $\frac{1}{2}$ °E. 33.4 ft. scribed $\frac{1}{4}$ S29 CS BT.

67

N. W. Corner D.L.C. 53.

Found-BT. as recorded by Richardson, 1929: Ren. # 34

10" Fir S43°E. 15.2 ft., open face, good scribing "CL 53 CS BT."

This BT. now snag, partly rotted.

Set Brass Cap at corner marked: N.W. Cor. CL. 53 T27S R7W. County Surveyor's Office, 1958

N. S. Fence Line through Corner.

New BT's.: 6" Cedar bears S.64°E. 31.5 ft. scribed N.W. CL 53 CS BT.

17" Cedar bears N.13°E. 36.2 ft, scribed N.W. CL 53 CS BT.

68

N. W. Corner D.L.C. 54.

Found - Orig. 14" now 40" W.O. S.35°E. 79.2 ft. I find good scribing,

"C 54 27S 8W BT" on old open face. I find this BT was 24"

when scribed, not 14", as recorded. Checks good for ring Ct.

Note - Old E. W. Fence S.12.5 ft. New E.W.Fence S.25.6 ft.

Set Brass Cap at Corner marked: N. W. Corner D.L.C. 54, T27S R7W County Surveyor's Office, 1958.

New BT's.: 8" Cedar bears N.26°W. 4.0 ft. scribed NW CL 54 CS BT.

14" R.Fir bears S.42°W. 18.2 ft. scribed NW CL 54 CS BT.

69

S. W. Corner D.L.C. 54.

FD OR PER DOLAN
M.106-33A+B 5-88

Found - Cole's BT. N.55°E. 28.4 ft., now 20"W.O. I open & find good scribe mks.

Set Brass Cap at Corner Mkd.: S W Cor DLC 54 T27S R7W County Surveyor's Office, 1958.

New BT.: I rescribe Cole's BT. 20" W. Oak N.55°E. 28.4 ft. S W CL 54 CS BT.

6" B. O. bears S.85°E. 13.3 ft. scribed S W CL 54 CS BT.

James W. Byron
Deputy County Surveyor
M. Godfrey
S. Blilow
April 24, 1958
C. S. File No. 49/79