

Douglas County Surveyor's Record of
Government Corners Renewed

27 T. S. 7 R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 97196

James W. Byron
M. Godfrey
S. Bilow
July 3, 1958
C.S. File No. 49/79

1/2 Section Corner to Sections 17 & 20.
Found - Orig. 15", now 36" B. O. N.23°E. 113.5 ft. I open lower
Scar & find good scribing "BT" on partly rotted face.
No trace of Orig. S. E. BT. Area South of line has been
cultivated years ago, no old trees left.
Set Brass Cap at Corner Mkd: 1/4 S17 T27S R7W County Surveyor's
S20 Office, 1958
New BT's: 10" B.O. bears N.27°E. 21.2 ft. scribed 1/4 S17 CS BT.
32" B.O. bears S.73°W. 160.3 ft. scribed 1/4 S20 CS BT.

70

James W. Byron, Deputy Surveyor
Milo Godfrey
S. A. Bilow
May, 1957
C. S. File No. 49/111
RW 1-24

N. N. W. COR.
North West Corner D.L.C. #43.
Found - 3" Iron Pipe at Corner & Stump of Orig. S.E. BT, no scribing
found, stump partly rotted Checks bearing & distance. *Ren. #20*
B.B.I. S.E. BT., now 24" W.O. Snag scribing fair condition,
checks distance to Corner. Bearing recorded S.40°E. I find
bearing should be S.35°E.
Blaze & Scribe 6" W. O. S.60°E. 75.6 ft. N.W. CL. 43 CS BT.

71

South West Corner D.L.C. #44
Found - 1" Iron Pipe at Corner - 24" Fir, now dead, bark scribed,
Ren. #21 fair condition.
N.E. BT. 6" W.O. face rotted.
Blaze & Scribe 14" R. Fir N.44 1/2°E. 27.9 ft. SW CL 44 CS BT.
Note - Corner checks bearing & distance as shown in C.S. 45/86.

72

James W. Byron
Milo Godfrey
S. A. Bilow
Sept. 9, 1958
C. S. File No. 49/62

Section Corner to Secs. 1 & 12, T 27S, R7W, & Secs. 6 & 7, T27S R6W.
Found - Stewart's 24", now 36" R. Fir S.42°E. 97.3 ft. I open & find
good scribing "S". (*See Ren #10 T.27-6*)
All other BT's gone except N.E. BT. which is down, has been
washed out. Shows good scar. I do not open.
Note - Corner falls in Creek. I set Witness Corner 80.0 ft. South
of true Corner.
Set Brass Cap at Witness Corner Mkd: Wit. Cor. North 80.0 ft. to S 1/S6
1958, County Surveyor's Office, S12/S7 T27S
R7W R6W
New BT's: 18" R. Fir bears S.78°E. 25.5 ft. scribed W.C. S 7 T27S R6W CS BT.
8" R. Fir bears S.41°W. 25.0 ft. scribed W.C. S12 T27S R7W CS BT.
11" R. Fir bears N.39°W. 63.2 ft. scribed W.C. S 1 T27S R7W CS BT.
14" Myrtle " N.26°E. 14.4 ft. scribed S6 CS BT WC.
This tree scribed high above wire fence.

73

Pages 115-116
Pages 285

N. W. Corner D. L. C. No. 50.
Set Post and Marked New BT's.: Fir 36" N.78°30'W. 5 lks.
B. Oak 10" S.18°45'W. 53 lks.

74

N. E. Corner D. L. C. No. 50.
Set Post & Marked New BT's: W. Oak 8" N. 2°45'W. 42 lks.
W. Oak 8" S.53°15'W. 17 lks.

75

Int. L. Corner D. L. C. No. 49.
Set Post & Marked New BT's: W. Oak 8" South 49 lks.
B. Oak 8" N.36°15'E. 30 lks.

76

S. W. Ext. L. Corner D. L. C. No. 49.
Set Post & Marked New BT's: B, Oak 36" West 58 lks.
W. Oak 16" N.11°W. 28 lks.

77

N. W. Corner D. L. C. No. 49.
Set Post & Marked New BT'S: B. O. 36" N.53°E. 147 lks.
W. O. 10" N.57°E. 210 lks.

78

RUG '70 SEARCHED FOR, NOT FOUND - C.S. 54/23

Briggs
Per U. S. Fleurney
Jan. 27, 1902
Recorded in Vol. 2,
Pages 115-116
Pages 285