

Douglas County Surveyor's Record of
Government Corners Renewed

T, 27 S. T. S. R. 8 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

17

Closing Corner to Secs. 32 and 33, T27 $\frac{1}{2}$ -8W.
Found - 1961 Cadastral Brass Cap, out of position & buried.
RESET BRASS CAP at corner point from 1961 BT's., as follows:
Orig. 16", now 17" Hemlock, S.34°E. 38.3 ft., alive, scribe visible on
unhealed blaze.
Orig. 16", now 16" Cedar, Dead, S.43 $\frac{1}{2}$ °W. 85.1 ft., scribe visible on
unhealed blaze.
New BT: 10" Hemlock S.85°W. 22.1 ft. mkd: "T27 $\frac{1}{2}$ S R8W S32 CC CS BT".
This corner falls in west track of Cat. Skid Trail & 91 ft. N. &
95 ft. E. of Wilson Creek, course N.W.

5/14/70 18

$\frac{1}{4}$ Corner to Section 31 only, T27-8W.
Found - 10", now 12" Yew, N.10°E. (Rec.N4OE) 16.5 ft., scribe visible,
This scribe, in part, done with knife.
36", now 38" D.Fir, N.50°W. 11.2 ft., shows faint bark scribe, "SC"
done with scribe, definitely old enough. Other bark scribe
with knife, " $\frac{1}{4}$ S BT".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S $\frac{1}{4}$ S 31
Office, 1970 T 28 S $\frac{1}{4}$
Reblzd. & Rescbd: 38" D.Fir N.50°W. 11.2 ft. mkd: " $\frac{1}{4}$ S31 CS BT".
New BT: 16" Hemlock N.55°E. 23.7 ft. mkd: " $\frac{1}{4}$ S31 CS BT".

4/23/70 19

Standard Corner to Sections 32 and 33 only, T27-8W.
Found - 1961 Cadastral Brass Cap, pushed over & buried.
Reset BRASS CAP at Corner Point.
Found - C.S. BT., Ren. #16. 36" Cedar N.2°E. 39.9 ft., alive, scribe
visible on unhealed blaze, "T27S R8W S33 SC BT" (We add "CS")
All other Bearing Trees destroyed.
New BT: 7" Hemlock N.17°W. 31.4 ft. mkd: "T27S R8W S32 SC CS BT".
This corner lies on top of cut bank on westerly side of the Burnt Mtn.
access road approx. 60 ft. W. of centerline.

5/14/70 20

Standard Corner to Sections 33 and 34, T27-8W.
Found - 1961 Cadastral Brass Cap, properly set & mkd. with Lecklider's
Pipe & Cap alongside., See Ren. #10.
Orig. 22" Fir, alive, N.36°E. 37.6 ft., tagged, chopped open & scribe vis.
10", now 12" Hemlock, alive, N.29 $\frac{1}{2}$ °W. 10.6 ft., scribe visible on
partially healed blaze.
All other Bearing Trees are turned out stumps.
New BT: 10" Hemlock N.34°E. 23.6 ft. mkd: "T27S R8W S34 SC CS BT".
This corner lies 50 ft. West of top of ridge, course S.W. & N.E.

5/18/70 21

$\frac{1}{4}$ Corner to Section 33 only, T27-8W.
Found - 1961 Cadastral Brass Cap, out of place about 2 ft. & buried 2 ft.
Orig. 38" Fir, Alive, N.54°E. 24.4 ft., Rescribe visible on unhealed blaze.
10", now 12" Hemlock N.50 $\frac{1}{2}$ °W. 39.6 ft., alive, scribe visible on nearly
healed blaze.
No trace other Bearing Trees due to logging
RESET BRASS CAP at corner point.
New BT: 9" Hemlock N. 39° E. 13.5 ft. mkd: " $\frac{1}{4}$ S33 SC CS BT".

5/18/70 22

Sec. Cor. to Sec. 31, T27-8W. and Sec. 36, T27-9W.
Found - 16", now 22" Yew, N.68°W. 31.0 ft. (Rec.30.0) scribe visible, done
with pocket knife.
22", now 31" Hemlock, N.68°W. 21.0 ft. (Rec.20.0), shows pitched
over face.
Squared Post at corner, set by Lehanowsky, Eng. #1768. #80
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R 8 W S 31 R
Office, 1970 T28S 9 W S 1 SW
Reblazd & Rescbd: 22" Yew N.68°W. 31.0 ft. mkd: T27S R9W S36 CS BT.
31" Hemlock N.68°E. 21.0 ft. mkd: T27S R8W S31 CS BT.
I do not find any original evidence or bearing trees for this corner.

John M. Powell & Vernon "Ray" Tracy
W. Penley
V. Perron
C. S. File No. 54/113

RE-REVIEWED

4/21/70