

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 27 S. T. S. R. 8 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97301

23

Section Corner to Sections 5 - 6 - 7 - 8.  
Found - 12" Cedar, now down, N. 32 $\frac{1}{2}$ ° W. 80.5 ft., faint scribe "27 8"  
20" Hemlock, now down, S. 65° W. 15.8 ft., tree buried.  
No trace of N.E. nor S.E. Bearing Trees.  
Set - Brass Cap at Cor. mkd: T 27 S R 8 W County Surveyor's  
Office 1970  

S 6	S 5
S 7	S 8

  
New BT's: 6" Chinquapin S. 53° E. 13.8 ft. mkd: T27S R8W S 8 CS BT.  
16" D. Fir S. 32° W. 23.6 ft. mkd: T27S R8W S 7 CS BT.  
26" D. Fir N. 48° W. 52.2 ft. mkd: T27S R8W S6 CS BT.  
No trees available to the N.E.

10/23/70

24

$\frac{1}{4}$  Corner to Sections 9 and 10.  
Found - 40" D. Fir, now stump, N. 42° E. 42.5 ft., opened for scribe "B"  
on burnt face. No trace of N.W. BT.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 8 W  
Office, 1970  $\frac{1}{4}$  S 9 | S 10  
New BT's: 8" Tan Oak N. 3° E. 35.0 ft. scribed  $\frac{1}{4}$  S10 CS BT.  
8" Hemlock S. 88° W. 36.0 ft. scribed  $\frac{1}{4}$  S 9 CS BT.

10/13/70

25

Section Corner to Sections 7 - 8 - 17 - 18.  
Found - Old Yew Post with faint scribe marks at section corner.  
10", now 19" Yew, S. 27 $\frac{1}{2}$ ° E. 19.1 ft., not much scar.  
20", now 30" Hemlock, N. 22° W. 34.3 ft., scribe visible, "27 8".  
No trace of S. W. Bearing Tree.  
Possible Orig. BT., Hemlock N. 41° E. 55.2 ft. (Rec. 33.7) Has old face,  
no scribing.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 8 W  
Office 1970 

S 7	S 8
S 18	S 17

  
New BT's: 9" Hemlock N. 72° E. 17.4 ft. scribed T27S R8W S8 CS BT.  
11" Hemlock S. 7° W. 35.0 ft. mkd: T27S R8W S18 CS BT.  
Reblzd. & Rescbd: 19" Yew S. 27 $\frac{1}{2}$ ° E. 19.1 ft. mkd: "T27S R8W S17 CS BT.  
10/20/70

26

Section Corner to Sections 25 - 26 - 35 - 36.  
Found - 24", D. Fir, now 36" Stump, blow down, S. 56° 30' W. 42.9 ft.,  
Opened stump for scribe, "R8W".  
Stump Hole N. 26° E. 37.0 ft. (edge of hole). No trace of stump.  
No trace of any other Bearing Trees. Ring Count places age of  
S.W. BT. at 65 years. Tree down for some time. Orig. Survey 1896.  
After good search, use hole of the S. W. BT. to Set Corner.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R. 8 W. # 84  
Office, 1971 

S 26	S 25
S 35	S 36

  
New BT's: 7" W. Fir S. 47° E. 18.0 ft. scribed T27S R8W S36 CS BT.  
8" Cedar S. 44° W. 19.7 ft. scribed T27S R8W S35 CS BT.  
10" Hemlock N. 83° W. 22.4 ft. scribed T27S R8W S26 CS BT.  
13" Hemlock N. 46° E. 61.8 ft. scribed T27S R8W S25 CS BT.  
Note - This corner lies in partially logged area.

4/13/71

27

$\frac{1}{4}$  Corner to Sections 2 And 11.  
Found: Post (found point of rotted post) from which: STAMPED IN ERROR  
10" cedar bears N 72° W., 51 lks. (missing)  
12" cedar bears S 76° W., 34 lks. (a cedar present, but no  
evidence of face or scribing)  
Set: 1 $\frac{1}{2}$ " Iron pipe with Brass Cap marked  $\frac{1}{4}$  S  $\frac{2}{11}$  BT"  
New BT's: 6" Fir bears N 70° W., 4.8 ft. mkd.  $\frac{1}{4}$  S BT - tag, "W" nail.  
6" Fir bears S 31 $\frac{1}{2}$ ° W., 9.2 ft. mkd.  $\frac{1}{4}$  S BT - tag, "W" nail.  
Note: Transit survey was run from the SW cor. to the SE cor. of this  
section and the position for the  $\frac{1}{4}$  cor. was calculated. The  
post was found 4.5 ft. N 34° W. of the calculated position.

John M. Powell  
Willie Penley & J. Heritage  
C.S. File No. 54/119

MARCH 71

Weyerhaeuser Co.  
Craig Templin, Chief  
H. A. Lester  
J. W. McWhorter  
June 17, 1971  
C. S. File 55/208

JAN. 1972