

Douglas County Surveyor's Record of  
Government Corners Renewed

T 27 T. S. R 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

SW Section corner for Section 19 only.

Found no evidence of the original corner or its accessories. Re-established the corner by the single proportion method.

Set - 3/4" I.P.

From which:

60" D. Fir stump, bears N.73°E., 40.1 ft. Scribed SW COR S19 RP.

32" D. Fir stump, bears S.45°E., 100.3 ft. scribed NW COR S30 RP.

40

SEE 1976 BLM Resurvey

Vol. 39 Pg. 157H

Robert C. Adamek  
For: Weyerhaeuser Co.  
Nov. 1975  
C.S. 58/76  
M 58 - 54

West 1/4 Corner for Section 30 only.

Found - A B.L.M. reference point established before the original bearing trees and corner were obliterated. Reference:

BLM corner notes 27-8 A-19. 17" Yew which bears N.50°E., 19.8 ft.

Set - 3/4 I.P.

From which:

12" Hemlock bears S.10°E., 22.5 ft.

40" D. Fir stump, bears N.11°W., 28.1 ft.

41

11/7/75

1/76

1/4 Corner for Sec. 34 only. South boundary

Found - A Fir, 35" now 37" scribed "BT" uprooted, standing position, bears N.19°W., 21.1 ft.

A Fir, 40" now 31" scribed "1/4 S34" uprooted, standing position, bears N.63 1/2°E., 24.4 ft.

Note: Did not find monument set in 1961. (Cadastral)

Set - Brass cap at 1/4 corner stamped: County Surveyors Office 1976

L. E. Monrean  
J. H. Cook  
County Surveyors Office  
March 2, 1976  
C.S. 59/8

42

S C  
T27S R8W  
1/4 S34

New BT's - A Western Hemlock, 9", bears N.32°E., 48.6 ft. double blazed and scribed "1/4 S34 CS BT".

Fence post with witness sign, bears N.42°W., 2.8 ft.

Note: Did not scribe second BT as there are none accessible at this time.

Mag. Dec. 20° east

3/2/76

3/77

NW Cor Sec. 6 (Township corner)

Set - by double proportion a 2" brass cap monument

From which:

A 12" D. Fir bears N.76°W., 27.9 ft. scribed TWP Cor RP.

42" D. Fir bears S.78°E 50.1 ft. scribed TWP Cor RP.

19" D. Fir snag bears N.21°E., 15.8 ft. scribed TWP Cor RP.

13" Chinquapin bears N.89 1/2° W., 27.2 ft. scribed TWP Cor RP.

43

Robert C. Adamek  
For: Weyerhaeuser Company  
Elk Wallow Survey  
July 13, 1977  
M 66 - 12 C.S. 58/139

S 1/4 Cor Sec. 31, T26-8

Set - by single proportion a 2" brass cap monument

From which:

26" D. Fir bears N.49°E., 17.6 ft. scribed 1/4 Cor RP

27" D. Fir bears S.11 1/2°E., 47.6 ft. scribed 1/4 Cor RP.

44

West 1/4 Cor. Sec. 6

Set - by single proportion a 2" brass cap monument

From Which:

A 36" D. Fir bears N.20°E., 29.8 ft. scribed 1/4 Cor RP.

A 24" White Cedar bears S.06 1/4°E., 22.3 ft. scribed 1/4 Cor RP.

45

7/13/77

West 1/4 Cor Sec. 7

Set - by single proportion a "W" nail in a large buried log for the corner. Also scribed 1/4 S7 in a cedar log lying over the point. Referenced the point as follows:

4" D. Fir bears N.26°W., 37.2 ft.

24" D. Fir stub bears S.38°W., 3.2 ft.

The area has recently been logged and scarified.

46

47

SW corner Sec. 7

Set - by single proportion a 1 1/2" brass cap monument

From which:

A 10" Hemlock bears S.84°W., 30.8 ft. scribed STD CNR RP.

A 6" Hemlock bears S.49°E., 22.3 ft. scribed STD CNR RP.

7/13/77