

Douglas County Surveyor's Record of
Government Corners Renewed

T 27

T. S. R 8

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Robert C. Adamek
For: Weyerhaeuser Company
Elk Wallow Survey
M 66 - 12 C.S. 58/139
July 13, 1977

R. B. Kimberling
S. J. Flause
Doug. Co. Surveyors
Office
Dec. 5, 1977
C.S. 59/42

C.S. 59/42

Romanso E. Ware
For: Revestco
June 1979
M 77 - 69

NE Corner Sec. 13, T27-9 (Closing corner) 48
Found - 1 orig. BT in 1975 which is a 12" Yew bearing N.5°W., 10 links.
Tree is down and has visible scribing on underside.
Set - A 1" I. P. from which:
10" D. Fir bears N.67 1/2°W., 14.5 ft.
10" Hemlock bears S.87°E., 17.6 ft.
This corner does not close on the township line.

SW Corner Sec. 18 49
Set - by single proportion. Chipped a notch into a rock face for the
section corner. Referenced the corner as follows:
12" D. Fir bears S.57°W., 17.3 ft. scribed STD CNT RP.
60" D. Fir snag bears S.64°E., 14.8 ft. scribed STD CNR RP

NE corner section 24, T27-9 50
The original stone and two BT's were found by Williams and Lester in 1969:
12" Yew bearing N.36°W., 19.8 ft. (down)
Fir snag bearing S.64°W., 7.2 ft.
Additional references:
16" Hemlock bears N.84 1/2°W., 32.0 ft.
14" Hemlock bears S.27°W., 40.7 ft.

North 1/4 Corner for Sec. 32 of T27 1/2S R8W. 51
Found - A 2 1-2" Iron pipe with brass cap set 12" above ground
marked: $\frac{1}{4}$ S32
T27 1/2S R8W
1961
A stump hole bears S.72 1/2°E., 30.4 ft. Remains of tree not found.
A 40" Hemlock stump bears S.36°W., 70.6 ft. with no visible blaze.
A 6" now 8" Yew bears S.36°E., (Rec. S.41°E.) 17.7 ft. scribing
"1/4 S32 BT" visible on partially healed blaze. Ren. #128.
Renewal - Stamped "N" on brass cap to read "N" 1/4 S32" T27 1/2S R8W 1961.
7/13/77
12/5/77

South 1/4 Corner Sec. 32. 52
Found - A 2 1/2" Iron pipe with brass cap set 2" above ground marked
SC "T27S R8W 1/4 S32 1961. (BLM).
A 51" Cedar stump, uprooted (stump hole) bears N.3°W., (Rec. N.8°W)
21.8 ft. with visible scribing "1/4 S32 CS BT" in a partially healed
double blaze.
New BT's- A 38" Fir stump bears N.39°W., 37.1 ft. with a boat spike driven in
center marked "BO2".
A 42" Fir stump bears S.11 1/2°W., 38.3 ft. with a boat spike
driven in top marked "BO 1".
Corner is 30 ft. south of logging road at edge of temporary landing..
12/5/77

Section corner for Secs. 9, 10, 16 and 15 53
Found - Unrecorded Weyerhaeuser Cor. and BT's.
Set - 5/8" Iron rod
BT's - 10" Hemlock bears N.32°W., 37.8 ft. (scribed "T27S R8W S9 BT")
8" Hemlock bears N.42°E., 19.4 ft. (scribed "T27S R8W S10 BT")
10" Hemlock bears S.32°E., 32.5 ft. (scribed "T27S R8W S15 BT")
28" Cedar bears S.52°W., 25.0 ft. (scribed "T27S R8W S16 BT")

1/4 Corner for Secs. 10 and 15. 54
Set - 5/8" Iron rod
BT's - 6" Fir bears S.10°E., 2.6 ft. scribed "1/4 S15 BT"
9" Fir bears N.8°E., 11.9 ft. scribed "1/4 S10 BT".
6/79