

Douglas County Surveyor's Record of

Government Corners Renewed

T 27

T. S.

R 8

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section corner for Secs. 10, 11, 14 and 15.

55

- Found - Unrecorded Weyerhaeuser corner and BT's.
- Set - 5/8" Iron rod
- BT's - 14" Fir bears N.80°W., 9.5 ft scribed "T27S R8W S10 BT".
- 18" Fir bears N.40°E., 5.5 ft. scribed "T27S R8W S11 BT"
- 18" Fir bears S.32°E., 18.5 ft. scribed "T27S R8W S14 BT"
- 12" Fir bears S.42°W., 17.8 ft. scribed "T27S R8W S15 BT"

Romanso E. Ware  
For: Revestco  
June 1979  
M 77 - 69

1/4 Corner for Secs. 10 and 11

56

- Found - Unrecorded 1" Iron pipe
- Set - 5/8" Iron rod
- From which: 1" iron pipe bears N.40°25'21"W., 7.21 ft.
- BT's - 10" Hemlock bears S.56°W., 21.5 ft. scribed "1/4 S/O BT".
- 8" Hemlock bears S.40°E., 15.2 ft. scribed "1/4 S11 BT".

1/4 Corner for Secs. 35 and 36

57

- Set - 1 1/2" iron pipe with brass cap
- BT's - 10" Douglas Fir bears N.49°E., 12.4 feet scribed "BT"
- 12" Douglas Fir bears S.89°W., 5.7 feet scribed "BT"
- Note - Weyerhaeuser Company tags nailed on BT's list the distance and bearing from the "W" nails, set in the root collars, to the corner monument.

Henry R. Reppeto  
For: Weyerhaeuser Co  
Nov. 1979  
C.S. 58/219

For OK 6/86  
R. Geisler  
C.S. 63/54

Section corner for Sections 29, 30, 31 and 32.

58

- Found - Orig. 14" now 18" fir stump which I open and find scribed "BT"
- Orig. 40" now 56" fir stump which I open and find scribed "BT"
- Orig. 36" now 47" fir stump with good scar
- Orig. 8" now 13" hemlock stump with good scar. Remainder of tree lying alongside shows scribed "30 T27S R8W WC" in previously opened blaze.
- Set - Using all four orig. BTs I SET 1" x 30" I.P. with brass cap attached marked "Douglas Co Surveyor T27S S30 S29 S31 S32 R8W 982".

The corner location matches record bearings to all four BTs and fits the distances fairly close if the distance is taken to the face of the tree. Bearings and distances used to set cor. are as follows:

- 18" fir stump bears N.23°E., 24.6 ft. to face. (Rec. 23.8 ft.)
- 56" fir stump bears S.46 1/2°E., 28.2 ft. to face (rec. 27.7 ft.)
- 47" fir stump bears S.47°W., 11.9 ft. to face. (Rec. 11.9 ft.)
- 13" hemlock stump bears N.50°W., 8.9 ft. to face. (Rec. 8.6 ft.)
- Brass cap protrudes 12" out of ground.

New Accessories:

- Set spike in top of said 18" fir stump bears N.23°E., 25.0 ft. to spike.
- Set spike in top of said 56" fir stump bears S.46 1/2°E., 28.8 ft. to spike.
- Set spike in top of said 47" fir stump bears S.47°W., 12.0 ft. to spike.
- Set spike in top of said 13" hemlock stump bears N.50°W., 9.1 ft. to spike.

4/26/82

Section corner for Secs. 28, 29, 32 and 33.

59

- Found - Unrecorded 1/2" x 24" I.P. lying on ground.
- Orig. 12" now 28" hemlock stump. I cut open and find scribed "S T R" positioned as per detail:



Rotted remains of two stumps probably the orig. N.E. and S.E. trees. Due to their condition plus disturbance by past logging I can not determine the exact limits of either stump. Orig. SW tree is gone.

- Unrecorded 15" hemlock stump with Weyerhaeuser "W" nail.
- Unrecorded 38" hemlock stump with Weyerhaeuser "W" nail.

Gregory Quibell  
Deputy, Doug. Co.  
Surveyors Office  
Karen Reed  
Terry Plouff  
April 27, 1982  
C.S. 61/30

Gregory Quibell, Deputy  
Douglas Co. Surveyors Office  
Karen Reed  
April 26, 1982  
C.S. 61/30