

Douglas County Surveyor's Record of  
Government Corners Renewed

T 27

T. S.

R 8

R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21991

C O N T. - - -

62

(1/4 Cor. Secs. 23 & 26)

Found 3/4" I.P. bears N.83°W., 1.6 ft. I do not disturb 3/4" I.P.

New Accessories:

Set spike in top of 36" fir stump bears N.23°E., 27.7 ft. Spike is stamped "BO"

1

Set spike in top of 30" fir stump bears S.5 1/2°E., 7.2 ft. Spike is stamped "BO"

2

Sketch of accessories in C.S. file.

5/6/82

1/4 Corner for Sections 23 and 24

63

Found - Orig. 36" fir, now 44" with two good scars plus numerous cruiser marks

Orig. 10" yew destroyed by cat trail.

Set - At record bearing and dist. (S.22°W., 31.7 ft.) from the orig. 36" now 44" fir BT, I SET a 1" x 30" I.P. with brass cap attached stamped "Douglas County Surveyors Office T27S 1/4 S23 S24 R8W 1982".

New BT's- 42" fir scribed "1/4 S23 CS BT" in double blaze, bears S.34°W., 20.3 ft.

30" fir scribed "1/4 S24 CS BT" in double blaze, bears S.52°E., 31.4 ft.

42" fir with "W" nail in face bears S.84°W., 11.7 ft. to nail.

Sketch of accessories in C.S. file.

5/10/82

Section corner for Secs. 20, 21, 28 and 29

64

Found - Orig. 30" hemlock now rotted remains of a stump.

Orig. 36" now 30" rotted hemlock snag 20 ft. tall.

Orig. 30" now 48" cedar with scribed "T27S R8W S29"

Orig. 24" now 28" cedar with face partially visible behind large down log.

Unrecorded 16" hemlock with Weyerhaeuser "W" nail.

Unrecorded 18" hemlock with Weyerhaeuser "W" nail.

Set - Using the orig. BTs found, I PLACE a 5/8" x 30" I.R. with alum. cap 6" below the ground mkd. "Douglas Co. Sec Cor 1982 Surveyor" I do not set a brass cap due to logging being in progress.

Bearings and distances used to set I.R. are as follows:

30" Hemlock stump bears N.59°E., 33.0 ft. (Rec. N.63°E., 33.0 ft.)

30" hemlock snag bears S.29°E., 54.1 ft. (same as record)

48" cedar bears S.55°W., 37.0 ft. (same as record)

28" cedar bears N.30°W., 31.7 ft. (same as record.)

New Accessories:

"W" nail in base of 48" cedar bears S.55°W., 34.3 ft.

"W" nail in base of 28" cedar bears N.30°W., 29.7 ft.

"W" nail in base of 16" hemlock bears S.60°E., 7.0 ft.

"W" nail in base of 18" hemlock bears N.38°E., 13.1 ft.

"PK" nail in base of 20" hemlock bears N.79°W., 26.6 ft.

5/3/82

Section corner for Secs. 22, 23, 27 and 26

65

Found - Unrecorded 3/4" I.P. firmly set protruding 6" out of ground.

Orig. "X" on rock appears to be buried by 4ft-6ft of dirt & slash from old logging.

Orig. 48" fir now 56" stump with good scar. I open blaze and find scribed "S 1" on a burned over face.

The other 3 orig. BTs are gone.

Set - Since the found unrecorded 3/4" I.P. does not fit the orig. BT at all, I SET the sec. cor. at record bearing and distance from original SE BT. (N.23°W., 50.1 ft.) Corner falls on large root from big fir stump & root wad buried by old logging activity. I therefore set a 5/8" x 15" I.R. with alum. cap in said root mkd. "Douglas Co. Sec Cor 1982 Surveyor".

Found 3/4" I.P. bears N.20°W., 32.7 ft. from set 5/8" I.R.

New Accessories:

23" cedar scribed "T27S R8W S27 CS BT" in double blaze bears S.47°W., 32.8 ft.

"PK" nail in top of 60" fir stump bears N.79°W., 33.7 ft. to nail. Corner lies approx 200 ft. below road on a very steep rock slope.

5/4/82

Gregory Quibell,  
Deputy, Doug. Co.  
Surveyors Office  
May 5, 1982  
C.S. 61/36

Gregory Quibell,  
Deputy, Doug. Co.  
Surveyors Office  
John Powell  
May 1982  
C.S. 61/36

Gregory Quibell, Deputy  
Doug. Co. Surveyors  
John Powell  
May 4, 1982  
C.S. 61/36