

Douglas County Surveyor's Record of
Government Corners Renewed

T 27 T. S. R 8 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

66

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
John Powell
May 10, 1982
C.S. 61/36

1/4 Corner for Sec. 24 and 25
Found - Orig. 18" now 23" hemlock with "BT: visible in previously opened face. Since tree has had a lot of axe work and cruiser marks I am not sure this is orig. scribing. Therefore I open upper part of face and find scribed "1/4S".
Orig. 20" hemlock has been taken out by cat trail.
Set - At record bearing & distance (N.28°E., 5.3 ft.) from orig. 18" now 23" hemlock BT, I SET a 1" x 30" I.P. with brass cap attached mkd. "Douglas Co Surveyor T27S 1/4 S24 S25 R8W 1982". Due to large root I could only set I.P. 8" into the ground. I then surround the I.P. with logs approx. 15" in diam. and then filled the center in with dirt making a mound approx. 3 ft. square and 15" deep.
New BT's -19" hemlock scribed "1/4 S25 CS BT" in double blaze, bears S.86°E., 69.6 ft.
42" hemlock scribed "1/4 S24 CS BT" in double blaze, bears N.68°W., 21.7 ft.
26" hemlock with "W" nail in face which I scribe "1/4 S24 CS BT" in double blaze bears N.3 1/2°E., 22.7 ft. to nail.
5/10/82

67

1/4 Corner for Secs. 16 and 21.
Found - Orig. 10" now 15" standing, dead cedar with rotted out faces in unhealed double blaze.
Orig. 15" now 17" cedar windfall with rotted out faces in unhealed double blaze.
Set - Using the record distances from the two orig. BTs, I SET a 1" x 30" I.P. with brass cap attached marked "Douglas Co. Surveyor T27S 1/4 S16 S21 R8W 1982", approx. 12" into the ground and then place pile of rock around I.P.
Bearings and distances used are as follows:
10" now 15" cedar bears N.77°W., 35.6 ft. (Rec. N.78°W.)
Stump hole from 15" now 17" cedar bears S.54°W., 35.6 ft. (Rec. S.67°W.)
New BT's- 9" hemlock with "W" nail in face scribed "1/4 S21 CS BT" in double blaze bears S.45°W., 33.7 ft. to nail.
10" hemlock scribed "1/4 S21 CS BT" in double blaze bears S.8 1/2°W., 11.9 ft.
48" fir with "W" nail in face bears N.10°E., 11.8 ft. to nail.
10" hemlock scribed "1/4 S16 CS BT" in double blaze bears N.53°E., 21.8 ft.
5/13/82

Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
John Powell
Terrie Plouff
May 12-18, 1982
C.S. 61/36

68

1/4 Corner for Sections 26 and 25.
Found - Unrecorded 1 1/4" I.P. protruding 8" out of ground.
Orig. 30" now 40" fir stump with well healed over double blaze.
Unrecorded 33" fir stump with healed up scar, I opened and found 1/4S BT in double blaze.
Orig. SW fir BT is completely gone.
Set - Using record bearing & distance from orig. 30" now 40" fir BT (S.40°W., 9.9 ft.) I SET a 1" x 30" I.P. with brass cap attached marked "Douglas Co. Surveyor T27S S26 S25 1/4 R8W 1982". Brass cap protrudes 9" out of ground.
Unrecorded 1 1/4" I.P. bears S.40°W., 1.65 ft. (appears to have been set by measuring from face of fir BT)
New BT's- 7" Chinquapin scribed "1/4 S25 CS BT" in double blaze bears S.60°E., 13.6 ft.
17" cedar stump with "W" nail in face and \mathcal{L} in bark bears S.75°E., 6.4 ft. to nail.
12" yew scribed "1/4 S25 CS BT" in double blaze bears N.16°E., 44.6 ft.
33" fir stump with found scribed "1/4 S BT" bears N.44°W., 35.1 ft. to PK nail set in face.
38" fir stump with "W" nail in face bears N.71°W., 45.6 ft. to nail