

Douglas County Surveyor's Record of
Government Corners Renewed

T 27

T. S.

R 8

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE., 21891

69

Section corner for Secs. 15, 16, 21 and 22

Found - Unrecorded 3/4" I.P. firmly set protruding 10" out of ground.
Orig. 18" cedar, now 24" stump with scribed "BT" visible in partially healed blaze.
Stump hole from orig. 16" cedar, rotted remains of tree lies downhill approx. 10 ft. from hole. An old tag is still on tree but no face visible.
Orig. 20" fir, now 25" stump shows good scar.
Orig. 6" madrone is completely gone.

Set - Using the three orig. BTs found, I SET a 1" x 30" I.P. with brass cap attached marked "Douglas County Surveyor T27S S16 S15 S21 S22 R8W 1982".

Bearings and distances used are as follows:

Orig. 18" now 24" cedar stump bears N.31°E., 20.5 ft.
Orig. 16" cedar now stump hole brars S.81°E., 10.6 ft.
Orig. 20" now 25" fir stump bears N.52°W., 25.1 ft. (rec.N.48°W.)
Found 3/4" I.P. bears S.46°W., 1.2 ft.

New Accessories:

Spike in top of 36" cedar stump bears S.43°E., 5.4 ft. to spike.
Spike in top of 38" fir stump bears S.28 1/2°W., 50.1 ft. to spike
Spike in top of orig. 18" now 24" cedar stump bears N.31°E., 20.5' to spike.
Spike in top of orig. 20" now 25" fir stump bears N.52°W., 23.9 ft to spike.

5/12/82

Section corner for Secs. 18, 17, 19 and 20

Found - Unrecorded 3/4" I.P. fir.y set, protruding 13" out of ground.
Orig. 36" Fir, now 47" stump with two good scars. I open upper blaze and find scribed "T27" 8 V

All other orig. BTs gone. Area logged over.

Set - Using record bearing and distance (S.78°W., 24.4 ft.) from orig. 36" fir, now 47" stump, I SET a 1" x 30" I.P. with brass cap attached marked "Douglas Co. Surveyors Office T27S S13 S17 S19 S20 R8W 1982".

Found 3/4" I.P. bears S.28°E., 17.3 ft.

New Accessories:

Spike in top of 37" fir stump bears N.12 1/2°W., 17.7 ft. to spike. This stump also has "W" nail in face.
Spike in top of 36" fir stump bears S.58°W., 55.3 ft. to spike.

5/19/82

Section corner for Secs. 27, 28, 33 and 34

Found - 60" fir, Orig. BT, now rotted snag, scribing visible bears S.58°W., 138 lks.

18" fir, OBT, windthrown, face evident bears N.82°E., 170 lks.

Set - 2" I.P. with brass cap marked "T27S R8W 8 27 33 34 1972".

New BT's- 4" incence cedar bears N.22°W., 13.1 ft.

6" chinquapin bears N.42°E., 27.3 ft.

8" fir bears S.66°W., 27.9 ft.

4" fir bears S.43°E., 14.4 ft.

All BTs marked "S _ T27S R8W BT". Placed Weyco tags and "W" nails on all new BTs.

1/16/73

1/4 Corner for Sections 14 and 15

Found - Unrecorded 3/4" I.P. firmly set protruding 7" out of ground.
From Which:

Orig. 12" hemlock, now 18" stump, previously opened showing scribed "1/4 S" bears N.31°E., 10.6 ft.

Orig. 6" fir now 76" stump, (it would appear orig. notes should have said 60" fir) bears N.54°W., 29.7 ft. to face. The stump is cut fairly low and does not show face.

Set - At the location of the found 3/4" I.P. I SET a 1" x 30" I.P. with brass cap attached protruding 9" out of ground. I place found I.P. along north edge of brass cap. Cap marked "Douglas Co Surveyor T27S S15 S14 1/4 R8W 1982".

New Accessories:

Spike stamped "B01" set in top of 76" fir stump bears N.54°W., 31.6'

Spike stamped "B02" set in top of 35" hemlock stump bears S.10°E., 34.9 ft.

W nail fd. in face of 20" hemlock stump bears N.76 1/2°W., 3.0 ft.

Gregory Quibell
Deputy, Douglas Co.
Surveyors Office
John Powell,
Terrie Plouff
May 12-19, 1982
C.S. 61/36

Craig Templin LS938
For: Weyerhaeuser Co.
Jan. 16, 1973
C.S. 58/271

Gregory Quibell, Deputy
Doug. Co. Surveyor Office
John Powell
June 3, 1982
C.S. 61/36

70

71

72