

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 27

T. S.

R8

R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

73

Southeast corner Section 35

Found - Marking on rock wall at the base of 100 ft. highbluff, including "B0, T27S, R8W", and "S46E, 16" which is the bearing and distance listed by Johnson in 1955. (Ren. #1)
No evidence of piton with circular ring, but evidence where originally driven in crack in rock face. Found no trace of 3/4" iron rod for corner.

Set - 1 1/2" iron pipe with brass cap using Johnson's bearing and distance measured from rock wall described above:

from which:

A 6" Douglas fir, scribed BT, bears N.52 1/2°E., 16.0 ft.

11/26/79

Henry Reppeto
For: Weyerhaeuser
Company
Nov. 26, 1979
C.S. 58/219

Section corner for Sections 1 and 2 only of T.28-8
Found - 1961 County Brass cap. Ren. #12

FIND OK 9/94 BY
DEGRADT M120-67

74

20" fir bears S.2 1/2°W., 73.5 ft. Closed face. (1961)
38" fir stump bears S.40 1/2°E., 57.42 ft. Chop marks visible on badly rotten stump. (See Ren. No. 88 of T.28-8)
36" laurel bears N.24°E., 117.0 ft. (Rec. 114.6 ft.) No scribing visible on double face. (1961)

New BT - 9" fir bears S.29°E., 72.6 ft. scribed T28S R8W S1 BT.

North 1/4 Corner for Section 1 only of T28-8

75

Found - 1960 1 1/2" I.P. set by Ramsey. (Ren. No. 91 of T.28-8)

31" white oak bears N.87°E., 218.5 ft. Rotted face (orig.)

44" black oak down and decaying. (orig.)

50" cedar bears S.36°W., 63.3 ft. (Rec. 57.4 ft.) Closed face. (1961)

New BT - 14" black oak bears S.24°E., 101.6 ft. scribed N 1/4 S1 BT.

Section corner for Sec. 36; and Sec. 31 of T.27-7 only.

76

Found - 1961 County brass cap. Ren. No. 14

Scribe marks on a fir stump which has been destroyed and dragged out of position.

New Bts - 4" fir bears N.46°E., 34.4 ft. scribed X BT.

8" fir bears N.78°W., 47.9 ft. scribed T27S R8W S36 BT.

1/4 Cor. Secs. 1 & 2

77

Found - 2 1/2" Iron pipe with top etched 1/4

40" Low stump bears S.20°W., 7.0'

44" Low stump bears S.60°W., 19.5' to mid stump (rec. S59°W 17.1' to face) WEYCO tag.

16" stump bears N.82°E., 19.5' to mid stump (rec. N.83°E., 18.6' to face), WEYCO tage and nail at base.

I tag a 5" D.Fir bearing S.31°E., 20.8'.

Corner lies on SW slope approximately 150' form the end of a dirt road.

See C.S. File 55/285 for March 1973 renewal information.

Center 1/4 Cor. Sec. 2

78

Set - 5/8"x40" iron rod with aluminum cap, mkd: LONE ROCK TIMBER T27S R8W C S2 1993 PLS 2291.

14" Hemlock bears N.17°30'W., 8.9', I scribe C 1/4 S2 BT and also put PK nail in face and tag tree.

17 1/2" D.Fir, bears N.82°40'E., 13.2', I scribe C 1/4 S2 BT and also put PK nail in face and tag tree.

24" D.Fir, bears S.54°E., 42.4', I scribe C 1/4 S2 BT and also put PK nail in face and tag tree.

18" Hemlock bears s.3°40'W., 32.8', I scribe C 1/4 S2 BT and also put PK nail in face and tag tree.

Corner sits on NE slope with lines blazed & painted running North & West from corner.

Ken Hoffine, L.S. #2291
For: Lone Rock Timber Co.
Feb. 1994
M 118-46