

Douglas County Surveyor's Record of
Government Corners Renewed

T 28 S. T. S. R 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

R. C. Grant
Lic. 2807
Nove. 10, 1961
C.S. File No.
51/218

1/4 Corner to Sections 11 and 12. 1
Corner was identified from cut Cedar Bearing Tree.
Renewed with 1" tubular steel and 2 new Bearing Trees;
10" I. C. N.2°W. 29.2 ft.
12" Hemlock S.11°E. 37.2 ft.
Best route to reach corner: Spur road from Sec. 11, Black Cr. Road.

Section Corner to Sections 26 - 27 - 34 - 35. 2
Found - Original Basalt Stone, from which a:
16" D.Fir, Orig. BT. with old face, bears N.58°E 27.7 ft. (Rec.29.0')
Orig. D. Fir, now blown down, bears SE. 16.5 feet.
16" Hemlock, Orig. BT with scribes bears S.24 1/2°W. 27.7 ft. (Rec.29.0')
Orig. Hemlock, now blown down, bears N.82°W. 29.0 ft.
New BT's: 6" Yew, I scribed "S35 BT", bears S.75°E. 5.0 ft.
8" Hemlock, I scribed "S27 BT", bears N.43 1/2°W. 12.0 ft.

Bruce A. Shaner
For Umpqua National Forest
July 15, 1963
C. S. File No. 51/259

Section Corner common to Sections 22 - 23 - 26 - 27. 3
Found - Orig. Basalt Stone, from which a:
26" D.Fir BT with old face bears N.62°E. 32.0 ft.
24" I.Cedar BT with scribes vis. bears S.5°E. 33.5 ft.
12" D.Fir BT with scribes visible, now blown down, bears SW. 10 feet.
36" D.Fir BT, now blown down, bears NE., 45 feet.
New BT's: 12" D.Fir, I scribed "S27 BT", bears S.81°W., 23.0 ft.
38" D.Fir, I scribed "T28S, RLW, S22 BT", bears N.52°W. 65.4 ft.

1/4 Sec. Corner common to Sections 14 and 23. 4
Found - Orig. Basalt Stone, from which a:
34" D.Fir, Orig. BT with old face, bears S.51°E. 43.0 ft.
(Record is SE, 44.9 ft.)
24" D.Fir, Orig. BT with old face, bears N15°W. 7.9 feet.

Bruce A. Shaner
For. U.S.
Forest Serv.
C.S. 51/259

1/4 Section Corner to Sections 16 and 21. 5
Found - Basalt Stone, from which a:
18" D. Fir BT. with scribes visible bears S.15°W. 9.9 feet.
18" D. Fir BT. with old face bears N.50°E. 6.6 ft.
New BT: 16" Doug. Fir, I scribed "1/4 S S21 BT" bears S.86°E. 84.0 feet.
August 24, 1964

MICROFILM TO HERE 10/67

Wit. Corner -

John M. Powell
Frank Jones & J. Brady
October, 1967
C. S. File No. 54/426

1/4 Corner to Sections 16 and 21. 6
Found - Orig. 18" D.Fir, now stump, S. 15° W. 9.9 ft., Tree has been opened, scribe marks visible. - see Ren.#5
Orig. 18" D.Fir, now stump, N. 50° E. 6.6 ft., shows good scar.
16", now 16" D.Fir, S. 86° E. 84.0 ft., pitched over face.
As Corner falls in new road, set Witness Corner 50.0 ft. East.
Set - Brass Cap at Wit. Cor. Mkd: County Surveyors T 28 S R 1 W
Office Wit. Cor. 50' West to
1967 1/4 S 16
S 21
New BT's: 15" D. Fir S. 16° W. 11.6 ft. mkd. W. C. 1/4 S21 CS BT.
11" D. Fir N. 54° E. 10.8 ft. mkd. W.C. 1/4 S16 CS BT.
Other BT to Original Corner becomes:
16" D. Fir S. 80° E. 35.6 ft. scribed 1/4 S21 BT.
Note - This corner will fall approx. 70.0 ft. East of Road which is not built yet. Road Station 17 1/2 + 36.

SEPT. 68

Oct. 27, 1967

Vernon "Ray" Tracy
& Crew
Oct. 21, 1968
C.S. File 54/40

Closing Corner to Sec. 6, T28-1W. and Sec. 1, T28-2W. 67
Found - Orig. 18", now 36" Fir, alive, S.71°E. 49.5 ft., shows good scar.
Orig. 12", now 24" Fir, alive, S.79°W. 41.6 ft., shows good scar,
we open & find scribe marks.
No trace of Corner Stone.
Set - Brass Cap at Cor. Mkd: County Surveyor's T27S
Office, 1968 T28S R2W S 1 | S 6 RLW
New BT's: 20" D.Fir S.10°W. 7.9 ft. mkd: T28S R2W S1 CC CS BT.
14" D.Fir S.42°E. 14.2 ft. mkd: T28S RLW S6 CC CS BT.
This corner lies on steep S.W. slope about 413' W. of Stan. Cor. T27-1&2 W.