

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

8

Standard Corner to Sec. 36, T27-2W. & Sec. 31, T27-1W.
Found - Orig. 16", now 38" Fir, alive, N. 71° W. 40.9 ft., shows faint scar.
We open & find scribe marks.

No trace of corner stone or mound of stone called for.

Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R1W S 36 | S 31
Office, 1968 SC T28S R2W S 31 | S 31 R1W

New BT's: 16" D. Fir N. 61° E. 34.0 ft. mkd: T27S R1W S31 SC CS BT.

(Orig. BT) 38" R. Fir N. 71° W. 40.9 ft. mkd: T27S R2W S36 SC CS BT.

This corner lies on very steep S. slope about 300 ft. S. of high rock bluff. The C. C. of T28-R's. 1 & 2W. bears west approx. 413 ft.

10/21/68

9

Section Corner to Sections 31 and 32 only, T27-1W.

Found - 12x8x6" Stone, firmly set, mkd. with grooves E - W.

12", now 26" Fir, N. 84° W. 37.0 ft., shows good scar.

20", now 30" Fir, N. 40° E. 21.1 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W

Office 1969 S 31 | S 32

T 28 S S 5

Bearing Trees O. K. and Tagged.

Found distance btwn. corners to be 15.5 ft. (Rec. 13.2).

11/16/69

Cl. C. Section Corner to Sections 5 and 6 only, T28-1W.

10

Found - No trace of corner stone.

12", now 26" D. Fir S. 22° W. 24.4 ft. (Rec. S22E 29.7), opened for scribing.

14", now 29" D. Fir, S. 75° E. 29.7 ft. (Rec. S75W 24.4), shows good scar.

Set - Brass Cap at C.C. Mkd: County Surveyor's T 27 S R 1 W

Office 1969 S 31

T 28 S S 6 | S 5

Bearing Trees O. K. and Tagged. Rec. Dist. btwn. Corners 15.5 ft.

11/17/69

11

Section Corner to Sections 3 and 4 only, T28-1W.

Found - 12x8x8 Stone at Closing Corner Mkd: "CC" & 3 notches on E - W. Sides.

10", now 15" Fir, S. 60° E. 11.9 ft., shows good scar.

12", now 17" Cedar, S. 12° W. 21.1 ft., scribe visible.

Set - Brass Cap at Cl. Cor. Mkd: County Surveyor's T27S R1W S 34
Office 1969 T28S R1W S 4 | S 3 C.C.

Bearing Trees all O. K. and Tagged.

11/24/69

12

Section Corner to Sections 33 and 34 only, T27-1W.

Found - 40" S. Pine, now down, N. 40° E. 7.3 ft., opened for scribe.

12", now 15" Fir, N. 14 1/2° W. 38.9 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R1W S 33 | S 34
Office, 1969 T28S R1W S 4

New BT: 18" Hemlock N. 43° E. 31.3 ft. mkd: "T27S R1W S34 CS BT".

11/24/69

13

1/4 Corner to Section 34 only, T27-1W.

Found - 30", now 47" D. Fir, N. 7° E. 23.8 ft., opened for scribe, "BT" and other marks. No trace S.E. BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 27 S R 1 W

Office 1969 S 34

T 28 S

New BT: 10" Hemlock N. 77° E. 20.4 ft. mkd: "1/4 S34 CS BT".

12/12/69

14

1/4 Corner to Sections 1 and 12.

Found - Stone, right size, firmly in ground, possible 1/4 corner.

8", now 16" D. Fir, N. 34° E. 36.3 ft., opened for scribing.

18", now 25" D. Fir, S. 25° W. 24.6 ft. (Rec. 18.5), shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 28 S R 1 W

Office 1969 S 1

S 12

New BT: 14" D. Fir N. 87° E. 15.2 ft. mkd: "1/4 S 1 CS BT".

12/15/69

Vernon
"Ray"
Tracy &
Crew
C.S. File
No.
54/40

John M. Powell
Frank Jones & W. Penley
Nov. 1969. C.S. File No. 54/94

RE-OPENED NO. 23

RE-OPENED NO. 24