

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 28 S. T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

John M. Powell  
Frank Jones & W. Penley  
C. S. File No. 54/94

15  
 $\frac{1}{4}$  Corner to Section 32 only, T27-1W.  
 Found - 18x12x6 Stone, firmly in ground, mkd: " $\frac{1}{4}$ " on north face.  
 18", now 34" D.Fir, S.32°W. 9.9 ft., opened for scribe " $\frac{1}{4}$ ".  
 16" D.Fir, now snag, N.45°W. 9.2 ft., scribe visible.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R1W S 32  
 Office, 1969 T28S  
 New BT's: 30" D.Fir N.40°W. 22.5 ft. mkd: " $\frac{1}{4}$ " S32 CS BT".  
 28" D.Fir N.51°E. 21.7 ft. mkd: " $\frac{1}{4}$ " S32 CS BT".  
 I open & destroy scribing of S.E. BT, as this cor. does not refer to Sec. 5.  
 12/12/69

16  
 Closing Cor. to Sections 1 and 2 only, T28-R1W.  
 Found - 15x12x10 Stone, firmly set, mkd: 1 notch east side.  
 16", now 30" D.Fir, S.61°W. 44.9 ft., shows good scar.  
 12" D.Fir, now stob, S.18°E. 24.4 ft., found scribing "S1BT".  
 Set - Bradd Cap at Cor. Mkd: County Surveyor's T27S R1W CC S 36  
 Office, 1969 T28S S 2 | S 1  
 New BT: 6" Cedar S.88°E. 15.2 ft. mkd: "T27S R1W S1 CC CS BT".  
 This corner lies 25 ft. E. of spring branch & 99.0 ft. E. of  
 Sec. Cor. to 35/36, T27-1W., see below.  
 12/15/69

17  
 Section Corner to Sections 35 and 36 only, T27-1W.  
 Found - 12x10x6 Stone, no marks found.  
 10", now 10" Hemlock, N. 2° W. 5.3 ft., scribe visible.  
 30", now 40" Hemlock, N.46° E. 72.6 ft., scribe visible.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R1W S 35 | S 36  
 Office, 1969 T28S S 2  
 All Bearing Trees O. K. and Tagged.  
 This corner lies about 60 ft. W. and 25 Ft. S. of spring branch, and  
 99.0 ft. W. of Sec. Cor. 2/1, T28-1W., see corner above.  
 12/15/69

18  
 Closing Corner to Sections 4, 5, and 33, T. 28 S. R. 1 W.  
 Found - 12x8x8 corner stone in place and marked 4 notches East & 2 on West  
 plus two good BT's.  
 14" D.Fir, now 26", S.15°E. 25.7 ft., shows good axe face.  
 12" D.Fir, now 20", S.45°W. 44.9 ft., opened and found scribing  
 of "BT".  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R1W S 33  
 Office, 1970 T28S CC S 5 | S 4  
 Note: No new Bearing Trees needed. This C.Cor of 4, 5, lies 10.4 ft. East  
 of the sec. cor of 32, 33 on Township Lines of T27S and T28S.  
 1/9/70

19  
 Section Corner to Sections 32 and 33, T. 27 S. R. 1 W.  
 Found - No trace of Hemlock cor. post. But found one good BT and one down BT.  
 10" D.Fir, now 14" windfall, N.56°E. 16.5 ft., shows open rotted  
 face, no scribing.  
 18" D.Fir, now 29", N.42°W. 28.4 ft., opened and found scribing of  
 "3" and other marks.  
 Set - Brass Cap at Cor. Mkd: County Surveyor's T27S R1W S 32 | S 33  
 Office, 1970 T28S S 5  
 New BT's: 36" D.Fir N.18°W. 27.4 ft., scribed "T27S R1W S32 CS BT".  
 18" D.Fir N.20 $\frac{1}{2}$ °E. 41.5 ft., scribed "T27S R1W S33 CS BT".  
 See corner of 32, 33 lies 10.4 ft. West of the C.Cor. of 4,5 on the Township  
 Line of T27S, and T28S.  
 1/9/70

MARCH '71

20  
 $\frac{1}{4}$  Corner to Sections 8 and 9.  
 Found - Stone, firmly set at corner mkd: " $\frac{1}{4}$ " on West face.  
 12" Pine, now down, N.50°E. 13.2 ft., shows scar.  
 12", now 14" Fir, N. 55°W. 5.3 ft., shows good scar.  
 Set - Brass Cap alongside Stone Mkd: County Surveyor's T. 28 S. R. 1 W  
 Office, 1971  $\frac{1}{4}$  S 8 | S 9  
 New BT: 8" Hemlock S. 22° E. 12.8 ft. scribed " $\frac{1}{4}$ " S 9 CS BT".  
 9/3/71