

Douglas County Surveyor's Record of
Government Corners Renewed

T28 T. S. R1 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21081

Gary L Langlitz Closing Corner to Secs. 3 & 4. T.29-R1 25
Clell E Goodwin Found-A 2" Iron pipe, leaning slightly in the ground, with
M.Lenora Ladig Brass cap attached, marked:
6/4/75
C.S. 57730

U.S. GENERAL LAND OFFICE T 28S R1W S33
SURVEY 1922 S4 S3

From Which: An orig. 10" now 22" Sugar pine bears S.39°E., 4.6 ft.
alive and well healed and
an orig. 6" chinquapin, now a 7" rotten snag bears
S.42°W., 14.5 ft., with some illegible scribing
remaining on a well rotted unhealed face.

We mark a new bearing tree as follows:
A 9" Grand fir bears S 37°W., 5.3 ft., scribed "T 29S
RLW S4 CC CS BT" on a double blaze.
Compass Declination 20°E.

Gary L Langlitz
Clell E Goodwin
M.Lenora Ladig
6/4/75
C.S. 57730

1/4 Corner of sec. 33 only 26
Found: A stone, 5"X 16"X 10" above ground, firmly set and
marked with a chiseled "1/4" on the north face,
From which: An orig 9" Fir, still 9" in diameter bears N.30°W
10.6 ft., alive and well-healed. and
an orig. 15" now 19" fir bears N.14°E., 11.2 ft.,
alive and well-healed.

At the corner point, we set a 1"X30" Iron pipe with Brass cap
attached, Marked:
County Surveyors T28S R1W
Office 1975 1/4 S33

We placed the original stone alongside the brass cap.
Compass Declination setting: 20° East

Gregory E Quibell
Gary L Langlitz
C.S. 57/30
6/24/75

Sec. Corner to Sections 7, 8, 17, and 18. 27
Found: Basalt stone as described in orig. notes.
From which: An orig. 12" now 18" Fir bears N31°E., 15.7 ft.
(Rec. N 26°E., 16.5 ft.) Alive with well healed blazes.
An orig. 18" now 36" Hemlock bears S.40°E., 26.4 ft., alive
with scribe marks visible in unhealed blaze.
An orig. 12" now 22" Hemlock bears S54°W., 101.6ft., alive
with rotted face showing through unhealed blaze.
An orig. 18" now 39" Fir bears N40°W., 41.6ft. Scribe marks
facing south are visible in unhealed blaze.
At the Cor. point we set 1" X 30" iron pipe with brass cap mark,

COUNTY SURVEYORS OFFICE T 28 S
1975 S 7 | S 8
S18 | S17
RLW

We place orig. stone along south side of brass cap. 28

6/24/75

Sec. corner to Sec. 3, 4, 9, & 10,
Found: A stone 12"X10"X5" (Rec. 15"X10"X5"), buried in debris,
marked with 5 notches on the south edge and 4 notches
on the east edge (Rec. 3 notches)
From which: An orig, 12" now 15" red cedar bears N41°E., 14.5ft.
scribe marks visible through small unhealed opening.
An orig. 14" now 19" D. Fir bears S45°E., 21.8ft. (Rec. S50°E.,
21.8ft.), alive and well- healed.
An orig. 12" now 13" D Fir bears S 48°W., 25.7ft., Alive and well
healed.
An orig. 12" now 18" D Fir bears N 38°W., 26.4 ft., alive and
well healed.
At the corner point we set a 1"x30" Iron pipe with brass cap
attached, marked:

COUNTY SURVEYORS OFFICE T 28 S
1975 S4 S3
S9 S10
R 1 W

We place the orig. corn. stone alongside the brass cap.
Compass Declination setting: 20° East