

Douglas County Surveyor's Record of  
Government Corners Renewed

T 28

T. S.

R 1

R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97501

34

Dennis Gaylord  
USFS Deputy  
Doug. Co. Surveyors  
Office  
Jan. 12, 1978  
C.S. 59/46

1/4 Corner for Sec. 31 only, T27-1.  
Found - A 19" Fir stump bears S.21°W., 5.28 ft. (Rec. S.15°W., 5.28 ft.)  
scribing visible on partly healed blaze, "1/4 S6 BT".  
A 40" Fir stump bears N.4°E., 36.3 ft. (Rec. N.10°E., 36.3 ft.).  
Has a healed scar.

Orig. Corner stone called for in GLO notes is gone.  
Set - Using the record BT distnaces as reference, I chain from BT  
stumps & set a s 1/2" brass cap on a 1" I.P. stamped:  
County Surveyor's Office 1978

T 27 S R 1 W  
1/4 S 31  
S.C.

New BT's and accessories:  
A 15" White Fir bears S.55°W., 86.7 ft. scribed "1/4 S31 CS BT"  
on a double blaze.  
A point of rock 10' x 6' x 4' above ground. On the ESE face I  
mark "X BR" 1 ft. above ground. "X" mark bears N.24°E., 14.0 ft.  
A 13" White Fir bears S.74 1/2°E., 121.0 ft. scribed "1/4 S31  
CS BT" on a double blaze.

Placed County BT signs on 2 stumps & 2 new BT's.  
Corner located in SW corner of a clearcut unit. This is a standard  
corner on the 6th standard parallel south.

1/12/78

35

Glenn Baughman  
For: U.S. Forest  
Service  
Nov. 21, 1978  
C.S. 58/176

1/4 Corner for 6 and 7.  
Found - 8" x 8" x 10" high stone with 5 notches on south face.  
20" D. Fir, 7 foot high stump with good healed blaze and "BT"  
tag bearing N.52°E., 31.4 ft.  
36" D. Fir, 1 foot high stump with partial healed and "BT"  
tag bearing S.81°E., 33.5 ft.

I scribed:  
26" D. Fir bears N.72°E., 51.1 ft. scribed "T28S R1W S6 BT".  
48" D. Fir bears S.14°E., 100.0 ft. scribed "T28S R1W S7 BT".

11/21/78

1-79

36

Gregory E. Quibell  
Deputy, Doug. Coun.  
Surveyors Office  
Debbie Stewart,  
witness  
July 13, 1981  
C.S. 61 / 27

Sec. corner for Sec's. 18 & 19 only. 1922 Resurvey.  
Found - Orig. stone, 8" x 8" x 12", partially tipped over to the North.  
Fd. 3 notches on the North & South edges. Did not find any  
trace of the S18 & S19 marked on the stone in 1922.  
48" Fir (Orig. 40") with well healed blaze bears S.55°E., 10.6-ft.  
36" Fir stump (Orig. 24"), 15" tall, with possible partial  
blaze, bears S.75°W., 39.4-ft. (REC. 40.9-ft).  
38" Fir (Orig. 30") snag, still solid, with well healed blaze,  
bears N.60°W., 4.0-ft.  
Badly decayed stump (Orig. 30" Hemlock) bears N.42°E., 11.9-ft.  
(REC. N.45°E., 12.2-ft.)

Set - At the exact position of the orig. stone, I set a Brass Cap mkd.  
Douglas Co. Surveyor | S18 T28S  
| S19 R 1W 1981

protruding 3" above ground. I bury orig stone 0.4-ft East  
of B.C., 3" in ground, with notched edges facing North & South.  
New BT's-11" Fir bears S.4°W., 26.5-ft., scribed T28S R2W S13 CS BT  
in a double blaze.  
11" Fir bears N.65°E., 17.5-ft., scribed T28S R1W S18 CS BT  
in a double blaze.

\* NOTE - All BT's tagged with DCSO BT tags. 7/13/81

37

Karen Reed, Douglas  
Co. Surveyor Office  
Terrie Plouff  
August. 4, 1982  
C.S. 62/1

1/4 Corner for Sections 18 and 19  
Found - A 15" x 12" x 5" basalt stone buried 6 ins. in the ground.  
No visible marks as recorded in 1902 survey at record  
bearing and distance from NW BT.  
An orig. 14" fir, now a 22" Hemlock bears N.30°W., 11.9 ft. dist.  
with partially healed single blaze. Visible scribe " ' C ".  
An orig. 24" fir, now a 43" bears S.48 1/2°E., 36.3 ft. (Rec. SE.)  
with previously chopped single blaze now healed over.

Set - Since no markings were fojnd on stone, I pulled record distances  
from both original BTs at this point the bearing for the NW  
tree was good. Holding this position I set 1 1/2" x 30" iron pi  
with brass cap stamped "Douglas Co. Surveyor T28S R1W 1/4 S18  
S19