

Douglas County Surveyor's Record of
Government Corners Renewed

T 28

T. S.

R 1

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

C O N T - - - -

(1/4 Cor. Secs. 18 & 19)

37

Karen Reed, Doug. Co.
Surveyors Office
Terrie Plouff
Aug. 4, 1982
C.S. 62/1

of stone. Placed original stone south side of cap beneath surface. This position falls on the found stone.
New BTs - A 7" Hemlock bears N.29 1/2°E., 25.3 ft. dist. scribed "1/4 S18 CS BT" in a double blaze.
A 14" diam. Hemlock bears S.36 1/2°W., 23.0 ft. dist. scribed "1/4 S19 CS BT" in a double blaze.
Corner falls on a SW slope approx. 26°. Sketch in C.S. file.

8/4/82

1/4 Corner for Section 10 and 15

38

Maurice E. Farr
For U.S. Forest
Service
August, 1983
C.S. 62/10

Found - 12" x 10" x 6" stone set 8" in the ground with marks "1/4" faintly visible on north face.
Orig. BT, a 40" D. fir snag, N.9°W., 58.2 ft. with scribe mark "1/4S" visible on decayed blaze.
Set - At position of corner stone, I set a 2 1/2" x 30" iron post with 2 1/2" brass cap, 16" in the ground with a 3 ft. diam. mound of stone up to brass cap. Cap marked T28S RLW 1/4 S10 S15 1983.
Original stone buried alongside.
New BTs - 10" D. fir, S.14°W., 15.7 ft. scribed "1/4 S15 BT" on a single blaze.
A 12" D. fir, N.51°W., 12.6 ft. scribed "1/4 S10 BT" on a single blaze.
Magnetic declination was 18°E.

8/83

1/4 Corner for Sections 5 and 8.

39

James N. Landrum
L.S. 2024
For U.S. Forest
Service
March 29, 1984
~~C.S. 59/30~~
MOVED TO
CS 62/50-13

REFERENCED OUT CORNER REPORT ONLY.
Found - Basalt stone 10" x 4" x 6" high (rec. 12"x10"x6") No marks visible. (Set by Angell, 1902)
14" hemlock, N.30°E., 10.6 ft. (Rec. N.25°E.) with a healed blaze. Painted 6" red bank around tree.
Pine snag, 18", S.22°W., 36.7 ft. (Rec. 37.6 ft.) with a healed blaze. Painted 6" red bank around tree.
No monument set at this time. Monument should be set after timber unit is cut.
Set - 40d nail in base of 10" hemlock. Nail head bears S.79 1/2°E., 10.0 ft. Painted 6" red bank around tree.
40d nail in base of 18" hemlock. Nail head bears S.28 1/2°W., 8.8 ft. Painted 6" red band around tree.
Set guard post with 54-4 sign, N.60°W., 1.9 ft.
Corner falls ± 200 ft. inside proposed clear cut.

3/29/84

Closing Corner for Sections 3 and 4 only of T.29-1

40

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
June 13, 1985
C.S. 62/28

Found - 1922 US GLO brass cap on a 2" I.P. protruding 15" above ground and leaning 10" westerly, properly marked. Ren. # 25
10" dia. now 24" dia. 2 ft. high sugar pine stump with a single well healed blaze bears S.34°E., 5.0 ft. (Rec. S.39°E., 4.6 ft. dist. is to face of blaze.) (Orig.)
6" dia. now 7" dia. 25 ft. high chinquapin snag with rotted evidence of a blaze bears S.42°W., 14.5 ft. (Dist. is to center of root crown and face of blaze due to leaning growth of tree) (orig.)
9" dia. grand fir now a 12" dia. white fir with a double well healed blaze bears S.42 1/2°W., 5.8 ft. (Rec. S.37°W., 5.3 ft. is to cap on leaning monument.)
Set - Straightened GLO cap on pipe to plumb and surrounded by a 24" dia. 15" tall mound of stone. Because both orig. face measurements and one orig. brg. agree with plumb position, we accept plumb position.
New BT - 28" dia. sugar pine double blazed and scribed "b29S RLW S4 CC CS BT" bears S.70 1/2°W., 50.1 ft.
From end of USFS Rd. #2813- 607 proceed easterly 600 ft. ± along ridge and cut line then south below ridge 40 ft. ± to corner.

6/13/85