

Douglas County Surveyor's Record of
Government Corners Renewed

T 28

T. S.

R 1

R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

41

South 1/4 Corner for Section 33 only.

Found - 1975 County brass cap on I.P. firmly set and protruding 8" above ground. Ren. #26

A stone, from orig. survey, marked 1/4 on North face, protrudes approx 5" from ground at NE edge of brass cap. Portion of stone exposed measures approx. 5 x 13 inches.

Orig. BT, a fir 12" dia. now a 19" dia. 42" tall fir stump bears N.14°E., 11.2 ft. This tree has a well healed single blaze pointing approx. S.54°W.

Orig. BT, a cedar, 24" dia. now a 36" dia. 15" tall cedar stump, bears S.16°W., 29.7 ft. Shows signs of 1922 obliteration of original blaze (This is no longer a BT for the S 1/4 of S.33).

1922 BT, a fir, 9" dia. now a 9" dia. 26" tall fir stump, bears N.30°W., 10.6 ft. Well healed single blaze.

Monument position is accepted as found.

New Accessories:

A boat spike stamped BT 1 set in a 30" dia. 16" tall fir stump, and bearing N.86 3/4°E., 27.0 ft. dist.

A boat spike stamped BO 2 set in a 31" dia. 18" tall fir stump, and bearing N.42 1/4°W., 55.4 ft. dist.

From the end of USFS Rd. #2813-607, monument bears east approx. 40 ft. dist. and slightly lower than road. Corner is in clear cut. No trees available for scribing.

6/13/85

42

1/4 Corner for Sections 7 and 18

I searched for and did not find original corner stone. This area was clearcut in 1983. The stone was not found by district personnel prior to the timber cutting. In my visit to the site in July, 1983, the corner point was covered by freshly fallen and bucked timber. In August, 1985, the area was covered with slash and had obviously been disturbed. Record bearing tree distances from center of trees wouldn't intersect, but distances measured from the blazed faces match the record bearings.

Found - Original bearing trees established by Homber D. Angell, Deputy Surveyor, in 1902:

A 28" W. fir stump, N.44°E., 16.5 ft. to face, 17.4 ft. to 60d nail set in center of stump. (Rec. Hemlock, 16.5 ft.) with scribe marks "S7 BT" visible on single blaze which I opened.

A 40" D. fir stump, S.21°W., 15.8 ft. to face, 17.0 ft. to 60d nail set in center of stump. (Rec. Hemlock, 15.8 ft.) with healed single blaze.

Set - At the intersection of the record bearings and distances from the blazed faces, I SET a 2 1/4" outside dia. iron pipe, 30" long, set 12" in the ground with a 4 ft. dia. mound of stone to the top with a brass cap marked "T28S R1W 1/4 S7 S18 LS 1181 1985". Inside the iron pipe I placed a 1/2" wire rope, 12" long with bell on the base as a memorial.

I set a 6 ft. steel fence post, east, 3.0 ft. driven 1.5 ft. in the ground as a guard post with forest sign #54-4 attached.

New BTs - In 1983, an 8" hemlock, N.10°E., 76.7 ft. scribed "1/4 S7 BT" on a single blaze.

In 1985, a 5" hemlock, S.45 1/4°E., 86.2 ft. scribed "1/4 S18 BT" on a single blaze with a 3/4" brass washer, stamped "LS 1181" nailed flush to base of blaze.

Note: Corner is 2 ft. south of draw which drains N.70°W and 60 ft. south of the timber line in unit #14 of the Red Idiot Timber Sale. Corner is approx. 300 ft. north of Forest Rd. #2792.

8/14/85

43

1/4 Corner for Section 5 and 8

Found - A 10" x 10" x 4" stone, with no marks, firmly set and protruding 3" above ground. Stone recorded as a 10"x4"x6" in Ren. #39 and originally as a 12"x10"x6".

10" now 16" dia. 6 ft. high hemlock stump with a fully healed single blaze bears N.30°E., 10.6 ft. Original BT. Agrees with Ren. 39

10" pine now 16" dia. 6 ft. high stump (species of tree may be wrong bark looks similar to W. Fir) has a fully healed single blaze, opened and scribing found "4S" bears S.22°W., 36.7 ft. Original BT.

18" now 18" dia. 5 ft. high Hemlock stump with nail in base on North side, bears S.32°W., 8.8 ft. to head of nail. (Record, S.28 1/2°W., 8.8 ft.) per Ren. #39.

C O N T. N E X T P A G E - - -

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
June 13, 1985
C.S. 62/28

Maurice E. Farr, U.S.F.S.
Leonard Herzstein, Party Chief
Randy Lopez, Witnesses
1983-85
C.S. 62/26

Douglas County
Surveyors office
Randall Smith
Stephen J. Flause
March 23, 1988
C.S. 62/50