

Douglas County Surveyor's Record of
Government Corners Renewed

T 28 T. S. R 1 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 81881

43

CONT. - - - - -

(1/4 Cor. 5 and 8)
Found - 10" Hemlock, uprooted and out of ground (rec. S.79½°E., 10.0 ft.)
Metal witness post and sign bears N.50°W., 1.9 ft. (Rec. N.60°W.,
1.9 ft. Per. Ren. No. 39)
Set - Position of stone is referenced and a 2 3/8" brass cap on a 1" x 32"
long iron pipe set at referenced position, protrudes 6" above
ground. Cap is mkd. "Douglas County Surveyors T28S R1W 1/4 $\frac{S5}{E8}$
1988 Office".
Stone is set along northeast edge of BC/IP flush with ground.
New Accessories:
20" dia. 14" high D. fir stump with a boat spike stamped "BO 1"
set through a bearing tree tag into top of stump near center.
Spike bears N.89°E., 10.6 ft.
15" dia. 12" high Hemlock stump with a boat spike stamped "BO 2"
set through a bearing tree tag into top of stump near center.
Boat spike bears N.40°W., 43.5 ft.
Corner lies approx. 300 ft. west of east edge of clear cut and approx.
250 ft. east of landing at end of spur road.

Doug. Co. Surveyor
Randall Smith and
Stephen J. Flause
March 23, 1988
C.S. 62/50

3/23/88

44