

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 2 W. R.W.W.M.

KONE-CHAPMAN CO., EUGENE, ORE. 21881

John H. Markham, Jr.
Witness: J. R. Markham
December 1961
C. S. File No. 51/221

South $\frac{1}{4}$ Corner Section 31, only, as det. by Old BT's. 76 1
10" Dead Cedar Snag bears N. 6°E. 13.2 ft., fd. scribe O.B.T.
22" Cedar-Stump, logged, bears N. 71°W. 12.5 ft., fd. scribe, O.B.T.,
Notes call for N. 17°W.
At Cor. Point Found Stone & Set $1\frac{1}{4}$ " x 36" Axle with flange up from which:
2" Fir bears S. 8°W. 22.2 ft. mkd: X X X.
 $1\frac{1}{2}$ " Fir bears S. 55°E. 10.2 ft., not mkd:
Centerline Road bears West 36.0 ft. Corner lies in old logging.

N. E. Corner Section 6, T29S-R2W, as det. by Old BT's: 2
26" Hemlock Snag bears S. 59°E. 18.5 ft., fd. scribe O.B.T.
At Cor. Pt. Set 1" x 30" I. P. from which:
1 $\frac{1}{2}$ " Fir bears N. 70°E. 2.6 ft., not mkd.
5" La. bears S. 56°E. 28.0 ft. mkd: S 6 R2W B.T. 77
3" Fir Bears S. 41°E. 19.0 ft. mkd: S5 XX B.T.
#3" Fir bears S. 1°W. 45.5 ft. mkd: S 6 B.T.
Skid Road bears South 35.0 ft.
Corner lie in old logging, a real brush pile.

South $\frac{1}{4}$ Corner Section 32, as det. by Old BT's.: 3
40" Hemlock Stump, logged, bears N. 11°E. 44.8 ft., fd. scribe O.B.T.
40" Hemlock Stump, logged, bears N. 13°W. 18.5 ft., fd. scribe, O.B.T.
At Cor. Pt. Set $1\frac{1}{4}$ " x 30" Axle with flange up, from which:
9" Hemlock bears S. 47°W. 56.5 ft. mkd: $\frac{1}{4}$ S32 B.T.
14" Hemlock bears S. 13°W. 61.0 ft. mkd: $\frac{1}{4}$ S32 B.T.
Road bears East 130.0 ft. distance.

N. W. Corner Section 4, T29S-R2W, as det. by Old BT's: 4
12" Hemlock Snag, live, bears S. 50°E. 27.0 ft. O.B.T.
At Cor. Pt. Set 2" x 30" I. P. from which:
12" Hemlock bears N. 66°E. 79.7 ft. mkd: S32X B.T.
9" Hemlock bears N. 45°E. 78.5 ft. mkd: S32 XX B.T.
East end of a 16" medal culvert thru dam bears N. 59°E. 51.0 ft.
Road bears West 120.0 ft. - Corner lies on S.W. edge of small lake.

$\frac{1}{4}$ Corner to S36/S31 T28S 5
R3W R2W
Found - Stone at Corner & BT's. all as recorded.
S.W. BT. has previously opened, shows good scribing.
Set - Brass Cap alongside Corner Stone & Mkd: County Surveyor's Office,
 $\frac{1}{4}$ S36/S31 T28S 1962
R3W R2W
New BT: 13" R. Fir bears S. 41°W. 10.0 ft. scribed $\frac{1}{4}$ S36 CS BT.

Section Corner to Sections 19 and 30, T28-2W & Secs. 24 & 25, T28-3W. #106 6
Found - Stone at Corner & all BT's., except S.E. BT. S.W. BT., now dead.
Distance to S.W. BT. should be 18.0 ft. not 31.0 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's $\frac{S24}{S19}$ T28S
Office, 1962 R3W $\frac{S25}{S30}$ R2W
New BT: 36" Hemlock bears S. 14°E. 23.4 ft. scribed S30 T28S R2W CS BT.

$\frac{1}{4}$ Corner to Sec. 30, T28-2W. & Sec. 25, T28-3W. 7
Found - Orig. S.E. BT., shows good scribing. We also find placed Stone
at corner which checks record size but do not find chisled Marks.
Do not find Original N.W. Bearing Tree.
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's Office, 1962
 $\frac{1}{4}$ S25/S30 T28S
R3W R2W
New BT's: 10" Hemlock bears North 15.4 ft. scribed $\frac{1}{4}$ S25 CS BT.
7" Hemlock bears S. 24°E. 6.6 ft. scribed $\frac{1}{4}$ S30 CS BT.

James W. Byron, Deputy County Surveyor
John Powell
Wm. Stoffel
July 10, 1962
C. S. File No. 52/126