

Douglas County Surveyor's Record of
Government Corners Renewed

T 28 T. S. R 2 R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

102

Dennis Gaylord, USFS
Deputy, Doug. Co.
Surveyors Office
Roland Simshauser
April 20, 1978
C.S. 59/46

Section corner for Secs. 35 and 36 only. (South)
Found - A 1923 US GLO brass cap properly stamped on a 1 1/2" I.P. 3"
above ground.
A 10" Chinquapin snag bears N.71°W., 11.88 ft. scribing visible
"T28S R2W S35 BT"
A 15" White Pine bears N.50°E., 45.54 ft. has a healed blaze.
Placed County BT signs on both trees.
No new monument set.
New BT's- A 13" D. Fir bears N.84°E., 30.6 ft. scribed "T28S R2W S36 CS BT"
on a double blaze.
A 7" D. Fir bears N.34°30'W., 14.1 ft. scribed "T28S R2W S35
CS BT" on a double blaze.
Placed County BT signs on both trees.

4/20/78

103

Dennis Gaylord, USFS
Deputy, Doug. Co.
Surveyors Office
Roland Simshauser
April 20, 1978
C.S. 59/46

1/4 Corner for Sec. 1 ^{North} ~~(South)~~ only, T. 29-2
Found - 1917 US GLO brass cap on a 1" I.P. 14" above ground & solidly
set i place. I add "T29S R2W" to brass cap below the 1/4 Sl.
A 21" D. Fir bears S.24°15'E., 22.4 ft. (Rec. distance is 21.78')
Has a healed scar.
A 13" D. Fir bears S.51°30'W., 5.6 ft. (Rec. 5.28 ft.) Has a
healed scar.
Placed County BT signs on both trees.
No new monument or accessories set.

4/20/78

104

Dennis Gaylord, U.S.F.S.
Deputy for Doug. Co. Surveyor
Witness: Juan Ortegon
June 16, 1978
C.S. 60/11

1/4 Corner for Secs. 26 and 35
Found - 1923 U.S. GLO 2 1/2" brass cap on a 3/4" I. rod properly stamped.
Monument has been removed from ground by logging activities and
is lying at approx. corner location.
Orig. 10" now 15" Hemlock bears S.82°W., 17.82 ft. Has a healed
scar.
Orig. 14" now a 18" D. Fir bears N.39°30'W., 19.8 ft. Has a
healed scar.
Placed County BT signs on both BT's.
Using the orig. BT's for reference, I RE-SET the G.L.O. brass cap and build
a mound of stone around pipe. I ADD "T28S R2W" to brass cap.
No new accessories.

6/16/78

105

Section corner for Secs. 26, 25, 35 and 36.
Found - 1923 U.S. GLO brass cap on a 1 1/2" I. Rod firmly set in the
ground and properly stamped. Protrudes 10" above the ground
surface.
A 7" Chinquapin stump bears S.17°W., 6.8 ft. (Rec. S.20°W., 7.26 ft.)
Portion of healed face is visible.
A 8" (Orig. 6") Chinquapin bears N.71°W., 11.9 ft. (Rec. 13.8 ft.)
Scribing visible on partly healed face, "T28S R2W S2 6 B" A5"
Chinquapin snag bears N.11°E., 14.52 ft. The partly healed face
is rotted out.
No trace of SE BT.
No new monument set.
New BT's - A 9" Chinquapin bears S.31°45'E., 17.4 ft. scribed "T28S R2W
S36 CS BT" on a double blaze.
A 35" D. Fir bears S.37°W., 41.2 ft. scribed "T28S R2W S35 CS BT"
on a double blaze.
A 22" White Pine bears N.54°E., 30.6 ft. scribed "T28S R2W S25
CS BT" on a double blaze.
Placed County BT signs on Orig. and new bearing trees.

6/16/78

106

Victor M. McLind
For: Umpqua Nat'l
Forest
Sept. 1978
M 70 - 36

Section corner for Secs. 19 and 30; and 24 & 25 of T.28-3
Found - 1" I.P. with 1962 County brass cap. Ren. #6
40" Hemlock bears S.14°E., 23.4 ft. Face with scribing visible
36" D. Fir snag bears S.29°W., 19.7 ft. healed face. Did not open.
36" D. Fir snag bears N.50°W., 15.8 ft. Face with scribing visible.
New BT - 18" Chinquapin bears S.14°30'W., 102.5 ft. I blazed & scribed
"T28S R3W S25 BT".

9/78

RE-REVIEWED #144