

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 28

T. S.

R 2

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Victor M. McLind
For: Umpqua Nat'l.
Forest
Sept. 1978
M 70 - 36

107

1/4 Corner for Sec. 19 and Sec. 24 of T.28-3
Set - Concrete monument approx. 6" wide on top, 12" wide at bottom
18" high on steep NW rock slope.
Set - 3" brass disc in top of conc. mon. stamped T28S R3W 1/4 S24 S19
R2W RLS 934 1978
From which:
10" Yew OBT bears S.13°E., 15.2 ft. (23 Lks.) good face with
scribing visible. Tree is down but alive.
16" Hemlock OBT, bears N.58°W., 24.4 ft. (37 lks.). No remains
of face found. Tree is down and almost completely rotted away.
Rotted stump hole apparent.
New BT - 10" Hemlock, bears N.6°30'W., 26.9 ft. I blazed & scribed "T28S
R3W 1/4 S24 BT".
12" Hemlock bears N.83°E., 5.8 ft. I blazed * scribed "T28S R2W
1/4 S19 BT".

9/78

1-79

108

Angle Point for Sec. 3; and Sec. 34 of T.27-2
Found - Orig. 30" now 36" Fir stump bears N.10°E., 9.9 ft. from face.
Faint scribing visible on a bark blaze.
Orig. 18" now 24" Fir windthrow has double bark blaze, but no
scribing visible. This tree has been recently chopped open.
No sign of an inner face. I can tell quite accurately where
this tree stood and the original location of the face bears
S.50°W., 8.6 ft.
Set - Referencing from the above evidence, I SET a 1 1/2" I.P. with
2 1/2" brass cap stamped County Surveyors Office A.P. T27S S34
T28S S3 R2W 1979. I. Pipe 32" into the ground, Brass cap is
4" above ground.
BT's- A 10" Cedar bears N.2°W., 41.6 ft. scribed "AP CS BT" on a double
blaze.
A 6" Yew bears N.43°E., 30.9 ft. scribed "AP CS BT" on a double
blaze.
A 6" Yew bears S.52°W., 47.5 ft. scribed "AP CS BT" on a double
blaze.

Placed County BT signs on all BTs.

1/18/79

Dennis Gaylord
U.S.F.S.
Deputy, Douglas Co.
Surveyors Office
Witness: Lee Zink
Jan. 18, 1979
C.S. 60/24

109

Angle Point for Sec. 3; and Sec. 33 of T27-2
Found - Orig. 30" Cedar is now a 52" Cedar, bears N.85°W., 42.24 ft. to
face. Faint scribing visible on bark blaze.
Orig. 36" Fir is a windfall. (Lying on face). Location of face of
tree when standing bears N.65°E., 71.28 ft.
Orig. 6" Fir BT is gone.
Set - Measuring from face of Cedar and approx. face of Fir as determined
from rootwad hole, I SET a 1 1/2" I.P. 36" Long 24" into ground.
A 2 1/2" Brass cap attached is stamped County Surveyors Office
A.P. T27S S33 T28S S3 R2W 1979.
New BTs- A 20" D. Fir bears S.75°E., 70.5 ft. scribed "AP CS BT" on double
blazes.
A 14" D. Fir bears N.51°E., 65.6 ft. scribed "AP CS BT" on
double blazes.

Placed County BT signs on orig. and new BT's.

This corner falls in the edge of a small creek. CC for Secs. 3 and 4, is a
Brass cap and bears S.78°30'W., 112.4 ft. (Rec. West, 110 ft.).

1/18/79

110

Center 1/4 Corner for Section 7
Found - Alum. cap on 1" iron pipe. Ren. #23
A 30" Fir stump, S.46°E., 23.2 ft. visual scribes #151
A 30" Fir stump, N.52°W., 27.1 ft. visual scribes.
New BT's- A 6" Oak, S.4°E., 13.4 ft. scribed C 1/4 S7 BT.
A 13" D. Fir, N.80°E., 20.0 ft. scribed C 1/4 S7 BT.

4/80

Ronald A. Quimby LS1654
BHW, Eng.
For: U.S. Forest Serv.
April 1980
C.S. 58/229

111

Section corner for Secs. 7, 8, 17 and 18.
Found - Alum. cap on 1" iron pipe set by Thomas Scrum Jr. in 1962. Ren.#20
A 12" Hemlock bears N.80.5°W., 14.6 ft. good face (orig. tree)
A 25" Cedar N.17°E., 15.5 ft. good face (orig. tree)
A 9" Yew, S.40.5°E., 14.8 ft. good face (orig. tree)
New BT- We scribed a 50" D. Fir, S.54°W., 47.5 ft. "T28S R2W S18 BT"

4/80