

Douglas County Surveyor's Record of
Government Corners Renewed

T28

T. S.

R 2

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31281

CONT. - - -

Closing Corner to Sec. 34 and 35 (cont.) #125
 Fd. - 48" Cedar stump bears S. 62°E., 25.6 ft. with visible scribe.
 12" Cedar bears N. 41°E., 58.1 ft. with visible scribe.
 Original 36" Fir bears N. 78°W., 60.7 ft. shows axe work.
 New BT's - 11" Yew bears S. 76°E., 207.0 ft. scribed "T28S R2W S2 BT".
 11" Hemlock bears N. 12°W., 184.0 ft. scribed "T27S R2W S34 BT".
 Note - Set post and sign 6.6 ft. North of corner. Brass washer mkd. RLS
 1005 set in BT faces.

1/4 Corner to Sec. 34, T.27S. R.2W only #126
 Set - 2 1/2" Iron pipe with brass cap mkd: "T27S R2W 1/4 S34 RLS
 1654 1980" at proportionate location.
 BT's - 12" Cedar bears N. 84°E., 19.9 ft. scribed "1/4 S34 BT"
 18" Fir bears S. 30°W., 50.7 ft. scribed "1/4 S34 BT" #148
 Note - Set post and sign 2.0 ft. East of corner. Brass washers mkd.
 RLS 1654 set in BT faces.

Closing Corner to Secs. 33 and 34, T.27-2W. #127
 Fd. - Original 40" now 48" D. Fir bears N. 42°30'W., 26.4 ft. with
 visible scribing.
 Original 14" now 36" Hemlock bears N. 1°30'E., 43.6 ft. with old
 scar. I rescribed "CC T27S R2W S34 BT".
 Set - 2 1/2" Iron pipe with Brass Cap mkd: "T27S R2W CC S33, S34;
 S3 1980 RLS 1654."
 Note - Brass washer mkd. RLS #1005 set in BT face. Also set post and
 sign 5.0 ft. North of corner.

Closing Corner to Sec. 2 and 3 #128
 Fd. - 3/4" Iron Rod with aluminum cap mkd: "USPC PROP COR T27S S34
 S3, S2 T28S R2W RE4287". (NOT OF RECORD).
 30" Cedar stump bears N. 18°E., 26.6 ft. with visible scribes.
 11" Cedar stump bears S. 50°E., 56.6 ft. with visible scribes.
 New BT's - 8" Fir bears S. 74°E., 9.9 ft. scribed "T28S R2W S2 BT".
 6" Yew bears S. 16°W., 23.3 ft. scribed "T28S R2W S3 BT".
 8" Cedar bears N. 28°W., 50.5 ft. scribed "T27S R2W S34 BT".
 Note - Brass washer mkd. RLS #1654 set in BT faces and set post and sign
 2.7 ft. West of corner.

CONDITION REPORT ONLY See Ren. #50 #129
 Closing Corner to Secs. 1 and 2
 Fd. - 2" Iron pipe with Brass Cap mkd. "General Land Office Survey T27S
 R2W S35, T28S R2W S2, S1 CC 1923".
 30" D. Fir bears S. 5°W., 75.2 ft. with visible scribes.
 18" D. Fir bears S. 34°E. 5.0 ft. with good scar.
 14" D. Fir bears S. 73°W. 12.3 ft. with good scar.
 24" D. Fir bears S. 68°E., 147.2 ft. with visible scar.
 Set post and sign 3.0 ft. North of corner.

Angle Point for Sec. 6 and Sec. 31 of T.27-2 #130
 Found - 1" I.P. with alum. cap marked U.S. P.C. Prop. Cor. T27S R2W
 AP 31 6 T28S R2W RE 4287 1968. Ren. #60
 8" Madrone, N. 3°W., 27.7 ft. vis. scribes
 6" D. Fir, S. 43°W., 23.1 ft. vis. scribes
 Set - Fiberglass post with signs 54.2 ft. and 54.4 ft. East.

Closing Corner for Secs. 6 and 5 only. #131
 Found - 1 1/2" I.P. with brass cap marked County Surveyors Office
 "T27S S31 S6 S5 R2W C.C. T28S 1968. Ren. #55
 50" D. Fir, S. 34°E., 55.5 ft. vis. scribes
 44" D. Fir, S. 45°W., 7.2 ft. Good scar.
 8" Madrone, S. 1°W., 44.0 ft. vis. scribes
 Set - Fiberglass post & signs 4.0 ft. South.

Ronald A. Quimby LS#1654
 Romano E. Ware LS#1005
 For: U.S. Forest Service
 May 1980
 M 79 - 45

Ronald A. Quimby
 LS #1654
 For: U.S. Forest Ser.
 May 1980
 M 79 - 46

Romanso E. Ware
 Ronald Quimby
 For: U.S. Forest
 Service
 July 1980
 M 79 - 49