

Douglas County Surveyor's Record of  
Government Corners Renewed

T 28

T. S.

R 2

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

132

Section corner for Secs. 31 and 32 only of T.27-2  
Found - 1968 County Brass cap properly marked Ren. #56  
6" Madrona, N.78°E., 21.4ft. vis. scribes  
12" D. Fir, N.12°W., 14.7 ft. Good scar.  
Set - Fiberglass post & sign 3.0 ft. North of corner.

133

Angle Point for Sec. 5 and Sec. 32 of T.27-2  
Found - Unrecorded 3/4" Iron pipe. Ren. #66  
24" Cedar stump, S.18°E., 6.3 ft. vis. scribe.  
20" Cedar stump, S.62°E., 5.3 ft. Good face.  
20" Cedar, N.35°E., 23.9 ft. vis. scribe.  
Set - 2 1/2" I.P. with brass cap marked T27S R2W AP S32 S5 T28S RLS 1654  
1980, over top of 3/4" I.P.  
New BT's- 22" Cedar, South 41.7 ft. "AP S5 BT". Brass washer set in BT face.  
Set - Post & sign 4.0 ft. North.

134

1/4 Corner for Sec. 32 only (South) of T.27-2  
Set - 2 1/2" I.P. with brass cap marked T27S R2W 1/4 S32 RLS 1654 1980.  
New BT's - 7" W. Fir, N.47°W., 23.5 ft. "1/4 S32 BT".  
12" W. Fir, N.28°E., 27.4 ft. "1/4 S32 BT".  
Brass washer marked RLS 1654 set in BT faces.  
Set - Post & sign 5.0 ft. North.

135

Closing Corner for Secs. 5 and 4 only.  
Found - 18" Madrona, S.68°W., 11.2 ft. vis. scribes Ren. #64  
32" D. Fir, S.62°E., 34.7 ft. Good scar.  
Set - 2 1/2" I.P. with brass cap over top of 3/4" I.P. marked: T28S  
R2W S5 S4 C.C. RLS 1654 1980.  
BT's - Rescribed 32" D. Fir "C.C. T28S R2W S4 BT"  
Brass washer marked RLS 1654 set in BT face.  
Set - Post & sign 3.0 ft. West.

136

Angle Point for Sec. 4 and Sec. 32 of T28-2  
Found - 3/4" I.P. Ren. #67  
30" D. Fir, N.45°E., 5.9 ft. vis. bark scribe.  
32" D. Fir, N.25°W., 3.3 ft. Good scar.  
3" D. Fir, S.27°E., 11.4 ft. Good scar.  
13" D. Fir, N.17°W., 11.2 ft. Good Scar.  
Set - 2 1/2" I.P. with brass cap marked T27S R2W AP S32 S4 T28S RLS  
1654 1980, over top of found I.P.  
Set - Post and sign 54-9 2.0 ft. East

137

Witness Corner for Closing Corner for Secs. 32 and 33 only of T.27-2  
Found - Orig. Corner tree fd. 7.0 ft. S.0°0'45"E., 26" D. Fir with healed  
blazes & 4 notches on the East side and healed blazes on the  
North & West sides. See Ren. #152 in T.27-2  
26" D. Fir, N.44°E., 23.1 ft. Good scar.  
32" D. Fir, N.59°W., 25.1 ft. Good scar.  
Set - 2 1/2" I.P. with brass cap marked T27S R2W WC CC S32 S33 S4 T28S  
R2W 1980 RLS 1005 S 7.0.  
New BT - 12" D. Fir, S.50°E., 12.4 ft. "W.C. T27S R2W S32 S33 BT"  
Rescribed 26" D. Fir, N.53°E., 18.6 ft. "W.C. T27S R2W S33 BT"  
Rescribed 32" D. Fir, N.70°W., 22.0 ft. "W.C. T27S R2W S32 BT".  
Set - Fiberglass post & sign 3.0 ft. West.

7/80

138

West 1/4 corner of Sec. 2. ONLY  
Found - Orig. 1923 GLO Brass Cap firmly set, & protruding 10" above  
ground, marked: 1/4 S2  
1923  
7" dia. dead fork (Orig. 12") of a Yew with unhealed blaze  
scribed 1/4 S2 BT, bears N.64°E., 9.9-ft.

Romanso E. Ware  
Ronald A. Quimby  
For: U.S. Forest Service  
July 1980  
M 79 - 49

Larry E. Monrean  
Deputy, Doug. Cou.  
Surveyors Office  
Terrie Plouff,  
witness  
July 13, 1981  
C.S. 61 / 27