

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 28 S. T. S. R 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

-CONTINUED FROM PREV. PAGE-

**138**

Larry E. Monrean  
Deputy, Doug. Co.  
Surveyors Office  
Terrie Plouff,  
witness  
July 13, 1981  
C.S. 61 / 27

Found - 6" Yew with unhealed, rotting blaze scribed 1/4 S2 BT bears S.53°E., 11.1-ft. to tree center at base, and 12.1-ft. to tree center at top of blaze (REC 12.5-ft.).  
New BT's- 12" W. Fir blazed & scribed 1/4 S2 CS BT bears S.79°E., 38.3-ft.  
10" W. Fir blazed and scribed 1/4 S2 CS BT bears N.42°E., 47.6-ft.  
\*NOTE - The monument marking the East 1/4 corner of Sec. 3 bears South, 40.8-ft.  
7/13/81

1/4 corner to Sec. 3 only. (EAST)

**139**

Found - 10" x 6" x 6" stone sitting loose on top of ground with a very faint 4 & no other marks distinguishable (REC 10" x 10" x 12"). The mound of stone from the 1909 Orig. survey notes not found.  
Orig. BT NOT found.  
A badly decayed Fir stump bears S.84°W., 34.3-ft. 1923 Resurvey.  
No scribing found.  
26" Fir (Orig. 12") snag bears N.53°W., 40.9-ft. Tree has well healed blaze. We open a portion of blaze & find a scribed S.  
Set - At position of found stone, we set a 1" x 36" I.P. with a B.C. attached, marked Douglas County Surveyor T28S R2W 1/4 S3 1981.  
We bury found stone along West side of monument.  
New BT's- 12" W. Fir, blazed & scribed 1/4 S3 CS BT bears S.39°W., 10.0-ft.  
10" W. Fir, blazed & scribed 1/4 S3 CS BT bears N.81°W., 25.9-ft.  
\*NOTE - The monument marking the West 1/4 corner of Sec. 2 bears North, 40.8-ft.  
7/13/81

1/4 corner between Sec's. 5 & 8.

**140**

Found - Orig. stone mon. NOT fnd.  
34" Fir (Orig. 30")—snag bears S.40°E., 12.5-ft. Found bark scribing S8 BT.  
Orig. NW BT NOT fnd...An approximate 4-ft.dia. hole bears N.30°W., 8.3-ft. (REC to orig. BT is N.24°W., 11.2-ft.).  
Set - As the scribed S.E. BT is the only good evidence remaining of the orig. corner monument or accessories, at record bearing & distance from the S.E. BT, we set a 1" x 36" I.P., with Brass Cap attached on bedrock with mound of stone; Cap is stamped Douglas Co. Surveyor T28S R2W 1/4 S5 S8 1981.  
New BT's- 48" D. Fir, bark scribed 1/4 S8 CS BT bears S.83°W., 16.6-ft.  
10" D. Fir, blazed & scribed 1/4 S5 CS BT bears N.17°W., 22.8-ft.  
12" D. Fir, blazed & scribed 1/4 S8 CS BT bears S.56°E., 28.4-ft.  
40" D. Fir, bark scribed 1/4 S8 CS BT bears S.27°E., 26.4-ft.  
\*NOTE - This corner lies on a steep SW slope with shallow soil-bedrock.  
7/13/81

Sec. corner for Sec's. 18 & 19 only of T.28S, R.1W. 1922 Resurvey.

**141**

Found - Orig. stone, 8" x 8" x 12", partially tipped over to the North. Fnd. 3 notches on the North & South edges. Did NOT find any trace of the S18 & S19 marked on the stone in 1922.  
48" Fir (Orig. 40") with well healed blaze bears S.55°E., 10.6-ft.  
36" Fir stump (Orig. 24"), 15" tall, with possible partial blaze, bears S.75°W., 39.4-ft. (REC 40.9-ft.)  
38" Fir (Orig. 30") snag, still solid, with well healed blaze, bears N.60°W., 4.0-ft.  
Badly decayed stump (Orig. 30" Hemlock) bears N.42°E., 11.9-ft. (REC N.45°E., 12.2-ft.).  
Set - At the exact position of the orig. stone, I set a Brass Cap mkd. Douglas Co. Surveyor 

S18	T28S
S19	R 1W 1981

 protruding 3" above ground. I bury orig. stone 0.4-ft. East of B.C., 3" in ground, with notched edges facing North & South.  
New BT's- 11" Fir bears S.4°W., 26.5-ft., scribed T28S R2W S13 CS BT in a double blaze.  
11" Fir bears N.65°E., 17.5-ft., scribed T28S R1W S18 CS BT in a double blaze.  
\*NOTE - ALL BT's tagged with DCSO BT tags. 7/13/81

Gregory E. Quibell  
Deputy, Doug. Co.  
Surveyor Office  
Debbie Stewart,  
witness  
July 13, 1981  
C.S. 61 / 27

Larry E. Monrean  
Deputy, Doug. Co. Surveyors Office  
Terrie Plouff, witness  
July, 1981  
C.S. 61 / 27